

ELITE®

Interior Matt

Product base code: EIM





Product description

Haymes Elite Interior Matt is a premium quality, low VOC, water-based 100% acrylic paint. Designed for trade applicators it has fantastic application properties with superb coverage. The washable matt finish minimises light reflection and assists hide surface imperfections, making it ideal for large, open areas.

Key features & benefits

Washable matt finish	Minimises light reflection.
Superior coverage	Solid, even finish.
99% VOC free	No lingering fumes or odours.

 INTERIOR USE ONLY	 WATER WASH-UP	 COVERAGE UP TO 16m ² /L	 RE-COAT 2 HRS
--	--	---	--

Where to use

Substrates:	Suitably prepared brick, concrete, masonry, paper-faced plasterboard, set plaster, timber and pre-painted surfaces.
Interior:	Interior walls including; bedrooms, dining rooms, feature walls and living areas.

Product properties

Colour & tint bases	White
Gloss level	60° 2 - 2.5 85° 1.6 - 2.1
Clean-up	Water
Dry time – touch dry	20 minutes
Dry time - recoat	2 hours
Coverage per litre	Up to 16m ² /L dependent upon surface porosity, profile and method of application.
Sizes	4 L, 10 L, 15 L
VOC	< 1 g/L
Volume solids	35%
Film build wet	62µm
Film build dry	22µm

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Provide adequate ventilation during application and the drying period.
- For bright and deep colours, to ensure colour accuracy and opacity, apply the specified tinted undercoat prior to the application of Haymes Expressions.
- If more than one can is required for the final coat, mix all cans together prior to commencing.
- Under normal conditions, the coating may require up to seven days curing to develop hardness and properties.
- **Please check the colour for accuracy before application. Haymes Paint accepts no responsibility for the application of incorrect colours.**

Surface Preparation

Preparation: All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting.

Previously painted surfaces	Conduct an adhesion test ¹ , followed by a compatibility test ² . Scrape all loose flaking paint. Sand glossy surfaces to a dull finish and remove all dust. Apply one coat of Haymes Elite Acrylic Sealer Undercoat to any patched areas followed by one coat over the entire surface.
Brick, concrete, masonry	New concrete must be left to cure for 28 days before painting. Wash with Haymes Unikleen & rinse with clean water. Apply one coat of Haymes Elite Acrylic Sealer Undercoat.
Paperfaced plasterboard	Apply one coat of Haymes Elite Acrylic Sealer Undercoat.
Set plaster	Apply one coat of Haymes Ultralock.
Timber- internal	Apply one coat of Haymes Elite Acrylic Sealer Undercoat. On tannin-rich timber and timbers prone to knot bleeding, apply one coat of Haymes Ultralock. For pre-primed timbers, please refer to the manufacturer's painting specification ³ .

Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply two coats.
- Application methods;

Brush: Use a quality synthetic brush

Roller: Use a 11-12mm nap length on smooth to semi-smooth surfaces. A longer nap is required for textured or rough surfaces.

Spray: For airless spray use a 15 – 17 thou @ 2000-2500 psi
The use of low-pressure tips will require a lower pressure range.

Thinning

Thinning is not recommended unless spraying; add up to 100mL clean water per litre of paint to achieve acceptable atomisation. Up to 50mL of clean water can be added per litre of paint to ease application under very warm conditions.

¹ To check the adhesion of an existing coating, cut an 'X' lightly into the coating and firmly apply adhesive tape across the cut and then remove tape. If the tape removes the existing coating, remove all previous coatings before painting.

² Test for compatibility with a previous coating by sanding and cleaning a small inconspicuous area. Apply 1 coat of the desired topcoat and allow to dry. After 24 hours conduct an adhesion test. If the tape removes the coating, remove all previous coatings before painting. It is recommended to conduct the compatibility test in several areas.

³ Some primers used on pre-primed timber are of low quality. Unless a painting specification is supplied by the timber manufacturer, the timber must be sanded back to bare timber before coating.

Care and Maintenance

New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for seven days. After seven days, the finish can be cleaned with a mild detergent solution and a soft cloth.

Storage

Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks.

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

Protect our environment

Do NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current before specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices comply with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded. Document valid unless superseded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
www.haymespaint.com.au

Date of Preparation 17/08/2020