

HAYMES ARTISAN COLLECTION

Sand

Product Code: ACSF

Product description

Haymes Artisan Collection Sand exudes a fine texture that produces a versatile authentic sand finish. It is a tough finish that is well suited to high-traffic areas including large commercial or retail environments.



Key Features;

- ✓ Bespoke texture
- ✓ Handcrafted finish
- ✓ Premium quality
- ✓ Interior and exterior sealed with Haymes Rendertex Rendershield Matt.

Where to use

Interior and exterior sealed surfaces including; plaster, plasterboard, masonry sheeting, bricks and render.

Note: For exterior usage Artisan Sand must be sealed with one coat of Rendertex Rendershield Membrane Matt.

Typical properties

Gloss	Matt texture; <5
Application tools	Brush, medium-long-nap synthetic roller, mitt, stainless steel trowel, airless or conventional spray
Clean-up	Water
Dry time	Touch dry 2 hours Recoat 6 hours when applied by Brush or Roller. Recoat 12 hours when applied by Mitt.
Coverage	Up to 4-6m ² /L depending on application technique and substrate porosity.
Colour	Tintable base to a range of colours.
Sizes	1 L, 4 L, 15 L
VOC	<8.5 g/L
Volume solids	55%

Surface preparation	
General surface preparation	<ol style="list-style-type: none"> 1. Scrape all loose/flaking paint. Sand smooth and dust down. 2. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. 3. Sand gloss surfaces to a dull finish. Remove all dust. 4. Prime bare surfaces with appropriate Haymes undercoats or primers.
Previously painted surfaces	<ol style="list-style-type: none"> 1. Ensure surface to be coated is clean, dry and free of wax, grease and other contaminants.
Paper-faced plasterboard	<ol style="list-style-type: none"> 1. Prepare any damaged areas as per General Surface Preparation. 2. Apply one coat of Haymes Ultraseal.
Masonry, brick, concrete	<ol style="list-style-type: none"> 1. Prepare any damaged areas as per General Surface Preparation. 2. Prime and seal with Haymes Rendertex Masonry Sealer.

Directions for use
<p>Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period. All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.</p> <ol style="list-style-type: none"> 1. Stir contents thoroughly before and during use with a broad, flat stirrer, using an upward action, or preferably use a power-driven mixing paddle. 2. Apply 1-2 coats using the same application technique. Do not apply in direct sunlight. 3. <u>Brush, Roller or Mitt application</u>; These methods will enable various finishes to be achieved. When using these application methods dilute up to 70ml of clean water per litre of paint. A medium-long nap synthetic roller may be used depending on desired texture. 4. <u>Trowel application</u>; Apply with a stainless steel trowel as smoothly as possible. The finish will vary depending upon trowel size. The trowel application is recommended for experienced applicators only. 5. <u>For Exterior use</u>: Apply one coat of Artisan Sand in desired application method followed by one coat of Rendertex Rendershield Membrane Matt with a 16-20mm nap roller (see PDS). <p>IMPORTANT NOTE: The finished result of decorative finishes will vary dependent upon the applicator and the application technique used. Haymes Paint recommends a sample application be conducted prior to undertaking your project to ensure consistency in finish. This is due to the variance that may be experienced between the Haymes finished sample and that achieved by the applicator. We recommend viewing our instructional videos located at www.haymespaint.com.au/artisancollection</p>

Thinning
<p>Thinning is recommended when being applied by brush and maybe desired when applying by roller or mitt. We recommend thinning at a rate up to 70ml of clean water per litre of paint. When applied by spray it can be thinned up to 30ml of clean water per litre of paint and up to 125ml when applied by conventional spray. Product should be applied undiluted when using a trowel.</p>

Care and maintenance
<p>Due to the finish exuding a textured finish we recommend the appropriate care is taken with items such as furniture and clothes that may come in contact with the finish. The textured nature of the finish may cause scratching to furniture and grabbing of clothes if contact is made.</p>

Storage
<p>Protect from extremes of temperature. Store between 5°C and 30°C.</p>

Safety and First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapours. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried under well-ventilated conditions that prevent inhalation of vapours. If swallowed **DO NOT INDUCE VOMITING**. Drink plenty of water and seek immediate medical advice. Contact a Doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Versioned: 17/11/2020 updates 3rd April, 2020