

HAYMES ARTISAN COLLECTION

Chalkboard Paint

Product Code: ACCB

Product description

Haymes Artisan Collection Chalkboard Paint allows you to transform just about any surface into a Chalkboard. The low odour, fast-drying, water-based paint dries to a flat, slightly abrasive finish that enhances chalk writing. It provides excellent coverage and is perfect for small or large chalkboards in areas such as children's play areas, kitchens, café menu boards, furniture or even in the office.



Key Features

- ✓ Bespoke texture
- ✓ Handcrafted finish
- ✓ Premium quality
- ✓ Interior and exterior

Where to use

Suitable for most suitably prepared interior and exterior surfaces such as plasterboard, timber, masonry and previously painted surfaces.

Typical properties

Gloss	Flat
Application tools	Brush, Roller or Spray
Clean-up	Water
Dry time	Touch dry 30 mins Recoat 2 hours
Coverage	Up to 14m ² /L
Colour	Black
Sizes	500ml, 1Lt, 4Lt
VOC	58 g/L
Volume solids	41%
Film build	Wet 72um Dry 29um

Surface preparation

General surface preparation	<ol style="list-style-type: none">1. Fill cracks, nail holes and imperfections with Haymes Unifill.2. Scrape all loose/flaking paint. Sand smooth and dust down.3. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.4. Clean surface with Haymes Unikleen and rinse with clean water.5. No primer is required when coating onto timber, particle board or MDF. Prime all external and other bare substrates with appropriate Haymes undercoats or primers.
Previously painted surfaces	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation.2. Sand gloss surfaces to a dull finish. Remove all dust.

Application

Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice. All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

1. Stir thoroughly before and during application.
2. Apply two coats for best results.

Thinning

Thinning not required. Up to 50ml of clean water can be added per litre of paint to ease application under very warm conditions.

Care and maintenance

Wipe over the painted surface with a damp cloth to remove all traces of chalk dust. When the surface becomes smooth and the chalk does not write properly, apply another coat of Artisan Collection Chalkboard Paint.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety and First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when using. Handling and usage of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Versioned: Updated 18th May, 2020
Replaces version dated 12th December 2019