

# HAYMES ARTISAN COLLECTION

## Scumble Medium

Product Code: ACSM

### Product description

Haymes Artisan Collection Scumble Medium is a water-based medium that modifies flat or low sheen water-based paints into broken colour finishes. Suitable for colour washing and other interior Artisan Paint techniques it provides translucency and pattern holding ability in the finish.



#### Key Features;

- ✓ Bespoke texture
- ✓ Handcrafted finish
- ✓ Premium quality
- ✓ Interior

### Where to use

For creating decorative paint finishes on interior walls, furniture and other surfaces.

### Typical properties

Gloss	Satin
Application tools	Brush, muslin, rage or decorative roller
Clean-up	Water
Dry time	Touch dry 2 hours Recoat 16 hours
Coverage	Dependent on application technique
Colour	Semi-Transparent
Sizes	500 ml, 2 L
VOC	252g/L
Volume solids	18%

## Application

Scumble Medium is not suitable for use as a finish on its own but increases transparency and extends the drying time of water-based paints.

Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period. All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity drying, times will be extended.

1. The area to be painted must be clean and in sound condition. Best results are achieved over low sheen paint finishes. Semi-gloss and gloss finishes must be sanded to a dull finish.
2. For a glaze, mix x1 part Scumble Medium with x1 part water-based paints and x ½-1 part water.
3. For a colour wash, mix x2 parts Scumble Medium with x1 part water-based paint and x6 parts water.
4. Prepare the glaze or colour wash and mix thoroughly with a broad flat stirrer.
5. Prior to commencing application to the whole job, practice your application technique on an offcut or large piece of board.
6. Apply using your preferred application technique.
7. Allow 16 hours to dry.

**IMPORTANT NOTE:** The finished result of decorative finishes will vary dependent upon the applicator and the application technique used. Haymes Paint recommends a sample application be conducted prior to undertaking your project to ensure consistency of finish. This is due to the variance that may be experienced between the Haymes finished sample and that achieved by the applicator.

## Thinning

Thin as required with water.

## Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

## Safety and First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

## Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website [www.paintback.com.au](http://www.paintback.com.au) for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

## Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint [www.haymespaint.com.au](http://www.haymespaint.com.au). We are continually updating materials and methods, so please ensure you have the latest information.

## Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Free call 1800 033 431  
Free fax 1800 801 892  
[www.haymespaint.com.au](http://www.haymespaint.com.au)

**Versioned:** Updated 3<sup>rd</sup> April, 2020  
Replaces version dated 12<sup>th</sup> December 2019