

# ARTISAN COLLECTION

## Matte Polish

Product Code: ACMP

### Product description

Haymes Artisan Collection Matte Polish is an understated silken metallic. The simple trowel application brings the material to life creating a low lustre overlapping pattern. Highlights and lowlights are accentuated through the fall of light onto the wall. The colours are luxe and sophisticated as is the finish with its subtle nuances and beauty.



### Key Features

- ✓ Bespoke Texture
- ✓ Handcrafted finish
- ✓ Premium Quality
- ✓ Interior

### Where to Use

All prepared interior surfaces such as broad wall plaster, plasterboard, iron, cement and timber.

### Typical properties

Gloss	Low Sheen
Application tools	Brush, trowel
Clean-up	Water
Dry time	Touch dry 2 hours Recoat 6 hours
Coverage	Up to 8-10m <sup>2</sup> /L depending on application technique
Colour	Tintable Pearl Base
Sizes	500 ml, 1 L, 4 L
VOC	40 g/L
Volume solids	17%

## Surface Preparation

General Surface Preparation	<ol style="list-style-type: none"><li>1. Fill cracks, nail holes and imperfections with Haymes Unifill.</li><li>2. Scrape all loose/flaking paint. Sand smooth &amp; dust down.</li><li>3. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.</li><li>4. Remove all traces of efflorescence or mould using a 10% bleach solution, especially on masonry or concrete surfaces.</li><li>5. Clean surface with Haymes Unikleen and rinse with clean water.</li><li>6. Prime bare plaster, timber and metal areas with appropriate Haymes undercoats or primers.</li><li>7. When using the trowel technique the substrate must be straight and smooth.</li><li>8. Apply one coat of Artisan Collection Base Coat in the recommended colour to match your selected topcoat.</li><li>9. For best results a solid coverage is necessary which may require a second coat.</li></ol>
Previously Painted Surfaces	<ol style="list-style-type: none"><li>1. Sand gloss surfaces to a dull finish. Remove all dust.</li><li>2. Prepare surface following General Surface Preparation.</li></ol>

## Application

Do NOT apply if ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period.

1. Mask up all edges with Haymes 14 day masking tape.
2. Apply the Artisan Collection Base Coat in the recommended colour for your topcoat.
3. Stir contents thoroughly before and during use with a broad flat stirrer, using an upward action.
4. Prior to commencing application to your project, practice your application technique on an offcut or large piece of board.
5. Sand Base Coat lightly to allow free flowing trowel movements.
6. Apply 1-2 generous coats of Matte Polish with a 75-100mm brush.
7. Switch tools to the trowel. Place at a 45° angle and glide the trowel over the applied product in fluid overlapping movements, smoothing out the brush strokes making an overlapping pattern.
8. Continue along the wall working in 1m<sup>2</sup> areas at a time until you reach the bottom corner. Ensure you keep a wet edge at all times.
9. Periodically, wipe any excess product from the trowel onto the wall. If any grit makes its way onto the edge of the trowel, simply wipe with a clean damp cloth.

All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

**Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.**

## Thinning

Thinning may be required when brushing. Thin up to 50ml of clean water per litre of paint.

## Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

## Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when using. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

### Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website [www.paintback.com.au](http://www.paintback.com.au) for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

### Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint [www.haymespaint.com.au](http://www.haymespaint.com.au) . We are continually updating materials and methods, so please ensure you have the latest information.

### Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Free call 1800 033 431  
Free fax 1800 801 892  
[www.haymespaint.com.au](http://www.haymespaint.com.au)

**Date of Preparation**      01/03/2019