

# Woodcare®

## Rapid Prep

**Product Base Code:** WPRP

	<b>Product Description</b>	
	<p>Haymes Paint Woodcare Rapid Prep is a simple to use, one-step preparation product for new bare exterior timber. Rapid Prep skips the weathering period, allowing immediate coating. It effectively removes tannins, extractives and mill glaze from the surface of the timber to allow the effective performance of the finish coat.</p>	
	<b>Key Features &amp; Benefits</b>	
   	<p><b>Removes surface tannins and extractives</b></p>	<p>Optimises the performance of the finish coat</p>
	<p><b>Allows immediate coating</b></p>	<p>Complete your project quicker</p>
	<p><b>Simple one step preparation</b></p>	<p>Prepares and cleans the timber in one application.</p>

Where to use	
Substrate :	Timber-Decking, Timber-Exterior, Timber-Tannin Rich and Timber-Weatherboard
Exterior :	Cladding and Decking

Typical Properties	
Application method	Scrubbing brush, stiff bristle broom
Clean-up	Water
Dry time - recoat	24 hours
Coverage	25-30 sq.metres per 300 grams once mixed.
Sizes	300gm, 900gm

Precautions
<ul style="list-style-type: none"> <li>Wear rubber gloves, covered footwear and safety glasses during use.</li> <li>In hot conditions, Do NOT apply in direct sunlight.</li> <li>If cleaning in close proximity to vegetation and metal surfaces, hose down areas prior to and after applying Haymes Woodcare Wood Cleaner. If contact occurs, immediately rinse with water.</li> <li>Ensure Haymes Woodcare Rapid Prep is thoroughly removed from surface. Failure to remove all traces of Rapid Prep may result in timber discolouration and/or poor coating adhesion.</li> <li>Timbers with a very high tannin content may darken after treatment with Haymes Woodcare Rapid Prep. To restore the original appearance please use Haymes Woodcare Wood Cleaner, following application</li> </ul>

**Precautions**

instructions.

**Surface Preparation**

Water penetration test

Sprinkle water onto the dry surface. If water penetrates the surface, the timber is ready for coating. If water beads and does not penetrate the surface, repeat the cleaning process and conduct the test again. Continue the process until water does not bead on the surface.

**Application**

- In a plastic container, mix 300gm of Haymes Woodcare Rapid Prep with five litres of hot water.
- Apply to the timber surface using a scrubbing brush, stiff broom or garden sprayer. Scrub surface thoroughly. Allow to stand for 10 minutes. Do NOT let solution dry on the timber. If necessary, apply more Rapid Prep during this period to prevent solution from drying.
- Wash surface thoroughly with a pressure washer or a high-pressure garden hose. All traces of Rapid Prep must be removed prior to application of any finishing coats.
- Allow the surface to thoroughly dry for at least 24 hours.
- Conduct a water penetration test as outlined above prior to applying finishing products.
- After 24 hours, coat cleaned timber promptly with a suitable exterior Haymes Woodcare finish to maintain the rejuvenated appearance.

**Storage**

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

**Safety & First Aid**

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

**Protect our Environment**

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit [www.paintback.com.au](http://www.paintback.com.au) for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

**Manufacturer's comment**

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for

#### Manufacturer's comment

which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website [www.haymespaint.com.au](http://www.haymespaint.com.au). Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

#### Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at [www.haymespaint.com.au](http://www.haymespaint.com.au) to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

#### Version

Version and Date Issued	Version 2.0 Date 10/08/2021
Supersedes	Version 1.0 Date 21/10/2016

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Park  
Ballarat Vic 3355  
Freecall 1800 033 431  
[www.haymespaint.com.au](http://www.haymespaint.com.au)