

NEW LOOK

Exterior Low Sheen

Product base code: NLELS

Product description

A durable acrylic finish specially formulated for use on exterior surfaces. No primer required on most surfaces. 15 Year Warranty*.



Key features

- Superior UV block out
- No primer required
- Easy to clean & care
- Made for Australian conditions

Typical properties

Colours & tint bases	White*, Ultra Deep, Dark tint, Extra Dark tint
Gloss level	60° 10 – 15 85° 19 – 24
Clean-up	Water
Application method	Airless spray, brush, roller.
Dry time – touch dry	30 minutes
Dry time - recoat	2 hours
Coverage per litre	Up to 16m ² /L depending upon surface texture, porosity and application method.
Sizes	1 L, 4 L, 10 L, 15 L* (white only)
VOC	<45 g/L

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- Do NOT apply if rain or dew is expected within 24 hours of application.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Do NOT paint in direct sunlight.
- Please consider the use of dark colours on exposed building materials, and follow the manufacturer's light reflectance value (LRV) recommendation.
- Under normal conditions, the coating may require up to seven days curing to develop hardness and properties.
- If more than one can is required for the final coat, mix all cans together prior to commencing.
- **Please check the colour for accuracy before application. Haymes Paint accepts no responsibility for the application of incorrect colours.**

Preparation

- Ensure surface is clean, dry and free from chalking, dirt, wax, grease and other contaminants. All loose, peeling or flaking material must be removed.
- Uneven surfaces should be sanded smooth with fine abrasive paper and all dust removed.
- Fill holes and cracks with a suitable filler and sand lightly to an even finish.
- If mould is present, clean surface with household bleach then rinse well with clean water and allow to dry.
- Test soundness of previously painted surfaces by cutting a small 'X' in the coating with a sharp blade. Stick a piece of tape firmly over the X and pull off. If the paint pulls away, the surface is unsound. Repeat at random in a number of areas. Unsound surfaces should be stripped.
- Sand gloss surfaces to a dull finish. Remove all dust.

TIMBER: Some primers used on pre-primed timbers are of poor quality. Unless a painting specification is supplied by the timber manufacturer, pre-primed timber should be sanded back to bare before coating to ensure durability. Knots in LOSP treated timber may be a source of tannin bleed. Please use an oil-based timber primer for these areas.

CONCRETE: Ensure all new cement and concrete surfaces are fully cured prior to painting. Typically this may take a minimum of 4-6 weeks. Ensure concrete surfaces are free from any bond breakers, formwork release agents, curing compounds and efflorescence.

STEEL & WROUGHT IRON: Remove all loose rust or mill scale by wire brushing, scraping or sanding. Two coats of New Look Exterior may be used to finish, however for longer lasting corrosion protection, the Haymes Rustlock metal protection system is recommended.

GALVANISED IRON: Degrease new sheets with a non-metallic scourer. Wash with sugar soap and then rinse with clean water. Treat rusted areas on old galvanised iron as for bare steel.

ZINCALUME®: Ensure Zincalume® or weathered Colorbond® surfaces are clean and free of salts or other deposits. New Colorbond® should be scoured with a nylon scourer if painting is required.

Surface Type	Preparatory Coats
Previously Painted Surfaces	Apply one coat of New Look Primer Sealer Undercoat to any patched areas.
Timber	Remove any grey timber. Apply three coats of New Look Exterior. For tannin rich timbers apply one coat of Haymes Ultralock .
Masonry, Brick, Concrete, Render	Wash with Haymes Unikleen & rinse with clean water.
Steel & Wrought Iron	Apply one coat of Haymes Ultraprime .
Galvanised Iron	Apply one coat of New Look Primer Sealer Undercoat .
Zincalume®	Apply two coats of New Look Exterior direct to prepared surface.

Application

- Stir thoroughly before and during application.
- Apply 2 coats by brush, roller or spray.

Thinning

Thinning is not recommended unless spraying, add up to 100mL clean water per litre of paint to achieve acceptable atomisation. Up to 50mL of water can be added per litre of paint to ease application under very warm conditions.

Care and Maintenance

Regular cleaning of the surface will assist removing dirt, dust and contaminants, which will result in a longer coating life.

Storage

Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks.

*Warranty

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

We provide the following in relation to our New Look Exterior Low Sheen (Product). The benefits of this warranty are in addition to any rights and remedies imposed by Australian State and Federal legislation that cannot be excluded. Nothing in this warranty excludes, restricts or modifies any State or Federal legislation applicable to the supply of goods which cannot be so excluded, restricted or modified.

GUARANTEE

We warrant that, subject to the exclusions and limitations below; the Product will be free from peeling, flaking and blistering (Defects) for 15 years. The warranty period commences on the date of sale of the Product.

If a Defect appears in the Product before the end of the warranty period and we find the Product to be defective, we will provide, free of charge, sufficient paint to rectify the area affected by the Defect. We reserve the right to provide paint of similar quality, grade and composition where an identical paint is not available. We reserve the right to change or discontinue our product ranges at any time without notice and without liability.

EXCLUSIONS

This 15-year warranty does not apply in the following circumstances:

- (a) where Haymes cannot establish a Defect with the Product;
- (b) where there is damage to the surface prior to the application of the Product;
- (c) where the Product is not applied in accordance with the preparation instructions or Product Data Sheet;
- (d) where surface preparation is not completed in line with instructions;
- (e) where the Product has been adulterated in any way;
- (f) where there has been a breakdown of previous coatings on the surface to which the Product has been applied.

HOW TO CLAIM

Any claims for warranty should be made with proof of purchase and full details of the alleged Defect, to the address listed below **within 30 days** of the Defect occurring. Photographs of the Defect must be provided to Haymes for assessment, and a site visit by a Haymes representative may be requested. The cost of delivery of paint to rectify any Defect will be the responsibility of Haymes on the determination of a valid warranty claim by Haymes.

LIMITATIONS

We make no express warranties, or representations other than as set out in this Warranty. The provision of sufficient paint to rectify the area affected by the Defect is the absolute limit of our liability under this Warranty.

CONTACT

Henry Haymes Pty Ltd
PO Box 167, Wendouree VIC. 3355
Phone: 1800 033 431 Email: info@haymespaint.com.au

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes, use under well ventilated conditions to prevent inhalation of vapours. Wear suitable protective clothing, eye protection and impervious gloves. If affected by inhalation, remove to fresh air. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Should any symptoms persist seek prompt medical advice.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current before specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices comply with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded. Document valid unless superseded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3350
Free call 1800 033 431
www.haymespaint.com.au

Date of Preparation 07/09/2020
Supersedes Version with preparation date 13/09/2019.