

HAYMES ANCILLARY

Unistrip Paint Remover

Product Code: UPR

Product description

Unistrip paint, lacquer, and varnish remover is a dichloromethane-based product designed to remove most surface coatings.



Key Features

- √ Suitable for use on vertical surfaces
- √ Fast acting
- ✓ Strips several layers of paint in one application

Where to Use

Timber, metal and masonry surfaces. Do not use on plastics.

Typical properties	
Application tools	Brush
Clean-up	Water or Haymes Methylated Spirits.
Coverage	4-6m²/litre depending on surface and application method.
Sizes	250ml, 500ml, 1L, 2L, 4L, 20L

Application

- Prior to commencing application to the whole job, test on a scrap, off-cut or inconspicuous area to determine requirements for next stripping action.
- Brush a generous coating (at least 2mm thick) onto the surface to be stripped and allow at least 15 minutes for the product to act.
- Make sure the coating has softened and blistered before removing using a flat (non-plastic) scraper. For very thick coatings, re-application may be required.
- Wash the surface thoroughly with water or preferably Haymes Methylated Spirits (which unlike water will not cause swelling of the timber grain). Allow the surface to dry before sanding to the desired smoothness.
- All traces of Unistrip must be removed before a new coating is applied.
- To avoid skin contact, we recommend the use of disposable or rubber gloves.
- Under normal conditions (25oC, 50% humidity) the product is active for 15 to 30 minutes.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid

SAFETY DIRECTIONS

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Causes damage to organs. Obtain special instructions before use. Do not breathe dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and suitable respirator. Store locked up. Store in a well ventilated place. Keep container tightly closed.

FIRST AID

If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126). If medical advice is needed, have product container or label at hand. SWALLOWED: If swallowed, rinse mouth. Do NOT induce vomiting. Give a glass of water. Call a POISON CENTRE or doctor/physician if you feel unwell. EYE: If in eyes, hold eyes open, flush with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes and see a doctor. SKIN: If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. INHALED: Remove from contaminated area – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Seek medical advice.

Dangerous Goods Classification

POISON TOXIC LIQUID, ORGANIC NOS UN 1593

Contains 130g/L Methanol & 960g/L Dichloromethane

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd A.B.N. 14 004 201 638 Waringa Drive Wendouree Industrial Estate Ballarat Vic 3350 Free call 1800 033 431 Free fax 1800 801 892 www.haymespaint.com.au

Date of Preparation 20/09/2016