

# ULTIMATE

## Single-Pack Anti-Graffiti Clear Gloss

Product Code: USEGC

### Product Description

Haymes Ultimate Single-Pack Anti-Graffiti Clear Gloss is primarily used on exterior applications as a sacrificial coating to guard against graffiti damage. Perfect for concrete substrates, this water-based clear is ideal for painting over sound, previously painted or prepared masonry surfaces to provide better durability. It is easy to use, has strong UV resistance, and allows for easy removal of graffiti.



#### Key features:

- ✓ Fast drying
- ✓ Excellent chemical resistance
- ✓ Low odour / VOC
- ✓ Excellent UV resistance
- ✓ Non-yellowing

### Typical Applications

Primarily used as a protective topcoat over interior and exterior masonry and most previously painted surfaces including:

Noise walls  
Shopping precincts  
Exterior walls and public areas

**Not for use on tiles or uncoated bricks.**  
Suitable on bricks coated with 100% acrylic paint and suitably prepared bare masonry surfaces.

### Typical Properties

Vehicle type	Nano grade self cross-linking acrylic
Finish	Gloss: 50 - 70%
Colour	Clear
Sizes	4 L, 15 L
Clean-up	Water
Coverage	Up to 6.8 m <sup>2</sup> /L
Dry times	Touch dry: 30 mins Dry to handle: 1 hour Recoat: 1 hour Hard dry: 3 days
Film build	Wet: 145 um Dry: 35 um
Application tools	Airless Spray (11 – 13 thou tip) at 1700 - 2100 psi Synthetic brush 5 -10mm synthetic roller sleeve

### Technical Data

Volume solids	30%
VOC	24.41 g/L
Abrasion resistance	Very good
Chemical resistance	Excellent to a wide range of chemicals. Contact Haymes Paint for further information.
Bacterial resistance	Good
Dry heat resistance	Excellent
Solvent resistance	Excellent
Salt spray resistance	Good
Durability	Excellent

## Surface Preparation

General surface preparation	<ol style="list-style-type: none"><li>1. All surfaces must be structurally sound, clean, dry and free of contamination, particularly salt deposits.</li><li>2. Existing coatings should be thoroughly abraded.</li><li>3. Loose or flaking paint must be removed by abrasive blast cleaning, power tool cleaning or sanding, to AS1627.</li><li>4. Oil, grease, dirt, and other contaminants must be removed with detergent and water blasting or solvent cleaning to AS1627.1.</li></ol>
Application over pigmented paint system	<ol style="list-style-type: none"><li>1. Apply two coats Haymes Solashield as per substrate directions.</li><li>2. Apply two coats Ultimate Single-Pack Anti-Graffiti Clear.</li></ol>
Concrete	<ol style="list-style-type: none"><li>1. Prepare as for general surface preparation.</li><li>2. New concrete must be cured for a minimum of 28 days before painting.</li><li>3. Tilt-up or precast panels must be cleaned with Rendertex Tilt Panel Prep solution and rinsed by pressure washing to remove bond breakers.</li><li>4. Test for water beading by applying water to the dry surface. If water beads then repeated cleaning is required. The surface is only suitable for painting when water beading does not occur.</li></ol>

## Precautions

- DO NOT apply if the ambient temperature is less than 10 °C or greater than 35 °C or if conditions will drop below 10 °C during the drying period.
- Not to be applied above 80% relative humidity.
- **You must ensure adequate airflow over coated surfaces to ensure the coating dries and hardens.** As the size, location and weather conditions of projects vary, you must consult with a Haymes Paint representative on the need for industrial exhaust fans and ventilators to provide adequate airflow for your project.

## Application

- Stir thoroughly before and during application.
- Apply two coats by brush, roller, or spray to achieve sufficient film build.
- Ensure adequate airflow and ventilation during both application and drying period.
- All times quoted assume ambient conditions of 25 °C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

## Thinning

Maybe thinned with up to 10% clean water to achieve acceptable atomisation. Thinning may necessitate the application of additional coats to achieve sufficient film build.

## Clean-up

Do not allow material to remain in hoses, gun, or spray equipment. Thoroughly flush all equipment with water. Clean all equipment after use with water, detergent solution, or methylated spirits. It is good work practice to periodically flush out spray equipment during the course of the working day. Frequency of cleaning will depend upon amount sprayed, temperature and elapsed time.

## Care and Maintenance

To rejuvenate the surface coating and extend the longevity regular cleaning is recommended. Clean the entire surface using a pressure washer to remove dirt and debris.

## Safety and First Aid

Keep out of reach of children. Avoid eye contact and repeated or prolonged skin contact and inhalation of any vapour.

For further safety information please refer to the product Safety Data Sheet available at:

<https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>

## Storage

Store in a cool, dry, well-ventilated place and out of direct sunlight.

## Protect Our Environment

Even though the Ultimate range of low VOC and low odour products are water-based, NEVER allow any leftover product to enter drains or waterways. Retain in a marked, sealed container for future use or dispose of via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities. If they cannot be recycled, dispose of contents to an approved waste disposal plant and containers to landfill.

## Manufacturer's Comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions may result in detrimental effects on product performance for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of safety data and product information sheets from Haymes Paint (1800 033 431). We continually update materials and methods; please ensure you have the latest information.

## Disclaimer

**Due to the chemical composition of tyres, contact between tyres and this coating may result in tyre staining.** It is important to understand the limitations of this coating product for resistance to tyre staining also known as "paw printing". Given the wide variation in tyre composition and age, Haymes Paint makes no warranties as to the performance of the coating and potential tyre staining and **will not be held liable** for any claims made where tyre staining occurs. You must read the specific product data sheet and fact sheet on tyre staining before commencing application of this product. These documents provide information about the suitability and application of the product for specific purposes. If you require more information or a product with resistance to tyre staining, then you must contact Haymes Service Express who can refer a technical representative for specific recommendations for your project before commencing any work.

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time; those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Freecall 1800 033 431  
Freefax 1800 801 892  
[www.haymespaint.com.au](http://www.haymespaint.com.au)

Date of Preparation: Versioned 10/11/20 updates version 4/11/2020