





PRODUCT DATA SHEET

HAYMES CHLORINATED RUBBER WHITE

QUICK CHECK

-  Industrial
-  TZCR Zinc & Chlorinated Rubber Thinners
-  Roller or Brush
-  Recoat – 4 hours

GENERAL DESCRIPTION

A chlorinated rubber finish that is resistant to salt and fresh water and splash of mild aqueous chemicals. This product is not resistant to vegetable and animal fats or oil and solvents.

USES

Light industrial applications including masonry and steelwork. **Not suitable for automotive use or immersion. Do not use in swimming pools.**

COLOURS

Available in white.

SIZES

Available in 4 litre, and 15 litres.

COVERAGE

Up to 10 square metres per litre.

APPLICATION

Stir well before and during application. Roll or brush. Minimum recommended dry film build 70um.

PROVIDE ADEQUATE VENTILATION DURING USE.

DRYING TIMES

Touch Dry Time - 10 minutes.

Recoat Dry Time - 4 hours.

Drying times refer to normal conditions (25°C, 50% humidity). Under cooler, humid or still conditions, drying times will be extended.

DO NOT USE IN TEMPERATURES BELOW 10°C OR ABOVE 30°C.

DANGEROUS GOODS CLASSIFICATION

Highly Flammable

Class 3

UN 1263

SURFACE PREPARATION

Previously Painted Surfaces:

Remove all grease, dirt and other surface contaminants. Remove any chalked paint. Scrape all loose and flaking paint. Sand glossy and enamel surfaces thoroughly and wipe clean.

Bare Masonry:

Remove all grease, dirt and other surface contaminants. Rinse well to remove all salts.

Bare Metal:

Remove all grease, dirt and other surface contaminants. Rinse to remove salts prior to abrasive cleaning.

Remove all rust by abrasive blasting or mechanical sanding.

THINNING & CLEAN UP

Thin and cleanup with TZCR, Zinc & Chlorinated Rubber Thinners.

COATING CONDITIONS

Do not apply if the temperature is below 10°C or above 30°C. Provide adequate ventilation with good airflow. Avoid painting in direct sunlight.

STORAGE

Protect from extremes of temperature. Store between 5°C and 30°C.

PRECAUTIONS

- **Safety Directions:** Keep out of reach of children. DO NOT SWALLOW. Harmful by inhalation and in contact with skin. Handling and use of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. Use appropriate breathing equipment when ventilation is restricted. May cause sensitisation by skin contact. Irritating to skin. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when using. Keep containers closed when not in use. This product is flammable; eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.). DO NOT SMOKE. Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water for 24 hours prior to disposal.
- **First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, DO NOT INDUCE VOMITTING, drink plenty of water and seek immediate medical advice. Contact a doctor or Poisons Information Centre (Phone 13 1126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.
- **Protect Our Environment:** Ensure paint does not enter gutters or drains. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities. Do not re-use empty containers.
- **Manufacturer's Comment:** This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty Ltd cannot be held responsible.

**For further information or to place an order, call
Service Express direct: Phone - 1800 033 431
or email – info@haymepaint.com.au**