

HAYMES

Exterior Roof & Metal Paint

Product Code: RPA

Product description

Haymes Roof & Metal Paint is a high quality oil based, aluminium formulation with excellent adhesion and corrosion resistance for iron roofs.

Key Features

- ✓ Ideal for metal roofing
- ✓ Corrosion resistant
- ✓ Suitable for the collection of drinking water

Where to Use

Metal roofing, galvanised iron fencing and the exterior of rain-water tanks and guttering.

Typical properties

| | |
|-------------------|--------------------------------------|
| Gloss | 24-29 @ 20° |
| Application tools | Brush, roller, spray |
| Clean-up | Mineral Turpentine |
| Dry time | Touch Dry 4 hours Recoat 24 hours |
| Coverage | Up to 16m ² /L |
| Colour | Aluminium |
| Sizes | 1, 4, 10L |
| VOC | 460g/L |
| Volume solids | 32% |
| Film build | Wet 62um Dry 20um |

| Surface Preparation | |
|--|---|
| General Surface Preparation | <ol style="list-style-type: none"> 1. Surfaces must be free from dirt, mould/algae and grease. 2. Loose rust must be removed & surface rust treated with Haymes Derustit |
| Galvanised Iron and Zinalume | <ol style="list-style-type: none"> 1. Degrease. 2. Rinse with a high pressure water wash. Allow to dry thoroughly. 3. Apply 1 coat of Haymes Ultracover. Allow to dry 2 hours. |
| Iron & Steelwork | <ol style="list-style-type: none"> 1. Degrease 2. Remove all mill scale and surface rust. 3. Treat rusted areas with Haymes Derustit. 4. Prime bare areas with Haymes Ultraprime. |
| Previously Painted Surfaces 1. Remove loose and flaking paint | <ol style="list-style-type: none"> 1. Remove loose and flaking paint 2. Check adhesion of remaining paint. 3. Treat any rusted areas with Haymes Derustit. 4. Spot prime bare areas with Haymes Ultraprime. |



| Application |
|---|
| <p>Do NOT apply if ambient temperature is less than 10°C or greater than 30°C. Ensure surface to be painted is above 10°C.</p> <ul style="list-style-type: none"> • Test for loose residues with adhesive tape. All loose material including dust must be removed prior to painting. • Stir thoroughly before and during application using a broad flat stirrer. • Apply 2 generous topcoats by brush, roller or spray. • All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended. • Avoid painting if rain, frost or dew is expected within 24 hours. |

| Thinning |
|--|
| <p>If thinning is required use approximately 50ml of Haymes Mineral Turpentine per litre. For spray application use up to 100ml per litre.</p> |

| Care and Maintenance |
|--|
| <p>The surface can be periodically spot hosed to remove soiling. Spot repair damage and imperfections.</p> |

| Storage |
|--|
| <p>Protect from extremes of temperature. Store between 5°C and 30°C.</p> |

| Safety & First Aid |
|--|
| <p>Read label before use. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Harmful in contact with skin. Causes skin irritation. IF ON SKIN OR HAIR: Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash skin with plenty of soap and water. If skin irritation occurs get medical advice. IF IN EYES: Wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. Harmful if swallowed. IF SWALLOWED: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water. Call a POISON CENTRE or doctor/physician if you feel unwell. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection. Wash exposed skin thoroughly after handling.</p> |

| Dangerous Goods Classification | |
|---|---|
|  <p>Packaging Group III PAINT UN1263</p> |  <p>Warning</p> |

| Protect our environment |
|--|
| DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities. |

| Manufacturer's comment |
|--|
| This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information. |

| Disclaimer |
|--|
| The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded. |

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Date of Preparation 02/11/2016