

Ultra Premium

Prepcoat Ultrahold®

Product Base Code: UPUH

	Product Description	
	<p>Haymes Paint Ultrahold® is a quick-drying, interior undercoat that creates a barrier to prevent existing stains from penetrating new coatings. It is ideal for rapid sealing of stains such as water, smoke, fire damage and mould. Ultrahold® delivers superb adhesion and is suitable for use with both water-based and oil-based paints.</p>	
Key Features & Benefits		
 Interior use only	Superior stain blocker	Prevents stains to prevent bleed-through topcoats.
	Rapid 1-hour recoat	Allows quick application of the topcoat.
	Superior adhesion	Bond to a wide range of surfaces with minimal preparation.
 Methylated Spirits wash-up	 Coverage Up to 16 sqm/L	 Recoat 1 Hr

Where to use	
Substrate :	Stain sealing
Interior :	Ceilings and Walls
<p>Note: Suitable for sealing stains including; coffee, grease, mould & mildew, nicotine/tobacco, pet stains, rust, smoke and water damage, sap and tannin bleed.</p>	

Typical Properties	
Colour	White
Application method	Brush, roller, spray
Clean-up	Methylated Spirits
Dry time - touch dry	15 minutes
Dry time - recoat	1 hour
Coverage	Up to 16 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	1L, 2L, 4L
VOC	602 g/L
Volume solids	25%
Film build wet	63 µm
Film build dry	16 µm

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Provide adequate ventilation during application and the drying period.
- Due to the quick-drying nature of the product, do not overwork the product or overlap into partially dried areas.
- Soak all cloths with traces of paint or solvent in water to prevent spontaneous combustion.

Surface Preparation

General surface preparation	All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting.
Previously painted surface	Conduct an adhesion test [1], followed by a compatibility test [2]. Scrape all loose flaking paint. Sand surface smooth to a dull finish and remove all dust.
Stain sealing	Wash the surface thoroughly with Haymes Unikleen to remove as much stain as possible and allow to dry. Apply one coat of Haymes Ultrahold. Some stains may require a second coat.
Adhesion test	[1] To check the adhesion of an existing coating, cut an 'X' lightly into the coating and firmly apply adhesive tape across the cut and then remove tape. If the tape removes the existing coating, remove all previous coatings before painting.
Compatibility test	[2] Test for compatibility with a previous coating by sanding and cleaning a small inconspicuous area. Apply 1 coat of the desired topcoat and allow to dry. After 24 hours, conduct an adhesion test. If the tape removes the coating, remove all previous coatings before painting. It is recommended to conduct the compatibility test in several areas.
IMPORTANT:	You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply one coat.
- Application methods:
 - Brush: Use a quality synthetic brush.
 - Roller: Use a 10-12 mm nap length on smooth to semi-smooth surfaces.

Thinning

Thinning is not generally recommended. Under warm conditions the product can be thinned using up to 50mL of methylated spirits per litre of paint.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and

Storage

transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. Only use this product in a well ventilated space and away from ignition sources. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.0 Date 27/06/2022
Supersedes	Version 1.0 Date 21/09/2016



Australia's first family of paint. SINCE 1935

Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymepaint.com.au