

Woodcare®

Wood Putty

Product Base Code: WPWP

	Product Description			
	<p>Haymes Paint Woodcare Wood Putty is an interior and exterior water-based timber filler designed to create a smooth, professional finish that resists cracking and shrinkage. This easy-to-sand, quick-drying filler saves your time when preparing timber for coating. It is suitable for use with water-based or oil-based coatings.</p>			
 Interior & Exterior	 Water wash-up	 Quick Dry	Key Features & Benefits	
			<table border="1"> <tr> <td>Quick-drying</td> <td>Get the job done faster, you can apply 2 coats in one day.</td> </tr> <tr> <td>Easy to sand</td> <td>Quick preparation</td> </tr> </table>	Quick-drying
Quick-drying	Get the job done faster, you can apply 2 coats in one day.			
Easy to sand	Quick preparation			

Where to use	
Interior :	Doors, Flooring, Furniture, Skirting and Architraves, Trims and Walls
Exterior :	Cladding, Doors, Decking, Outdoor Furniture, Trims, Walls and Window Frames

Typical Properties	
Colour	Cedar, Hardwood, Jarrah, Merbau, Pine and Walnut
Application method	Putty knife
Clean-up	Water
Dry time - recoat	One hour for small holes & cracks up to 2mm, Two or more hours required for larger deeper areas
Sizes	150gm, 500gm
VOC	19 g/L

Precautions
<ul style="list-style-type: none"> • Ensure you have selected Haymes Woodcare Wood Putty which closely matches the colour of your timber. • Do NOT smear Wood Putty into areas surrounding holes, cracks and imperfections. • Allow one hour drying time for small holes and cracks up to two millimetres deep. Two or more hours drying time may be required for larger holes and cracks. • All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity, drying times will be extended. • To prevent Haymes Woodcare Wood Putty from hardening, keep container tightly closed when not in use.

Surface Preparation

General surface preparation	<ol style="list-style-type: none">1. Ensure surface is clean, bare, dry and free of mould, wax, grease and other contaminants prior to applying Haymes Woodcare Wood Putty.2. Ensure all holes are free of loose material.
-----------------------------	---

Application

- If a clear finish is desired apply first coat of finish before filling. Fill nail holes, cracks and surface imperfections with Haymes Woodcare Wood Putty. Fill deep holes in 6mm layers, allowing 2 hours drying time between application of each layer. Wipe off excess putty with a damp, lint-free cloth then allow to dry. Sand surface in the direction of the grain with 240-grit sandpaper until smooth.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.0 Date 10/08/2021
Supersedes	Version 1.0 Date 01/10/2012

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymespaint.com.au