

PRODUCT DATA SHEET

HAYMES BLACK STALLION

GENERAL DESCRIPTION

A 100% acrylic for use on exterior timber. This self priming product contains no harmful additives, is safe for use around horses and livestock while offering great protection and a long lasting finish.

USES

A quality Low Sheen finish for exterior timber including horse and livestock fencing, paddock and paling fences.

COLOURS

Black.

SIZES

Available in 15 and 200 Litres.

COVERAGE

Coverage up to 16 square meters per litre.

APPLICATION TOOLS

Roller, Brush or Airless Spray.

DRYING TIMES

Touch Dry Time – 20 minutes.

Recoat Dry Time - 2 hours.

Drying times refer to normal conditions (25°C, 50% humidity). Under cooler, humid or still conditions, longer drying times may be necessary.


***OPTIMUM APPLICATION CONDITIONS
BETWEEN 10°C AND 30°C.***

DANGEROUS GOODS CLASSIFICATION


Not classified as Dangerous Goods.

QUICK CHECK

 Exterior

 Water Wash Up

 Roller, Brush or Spray

 Recoat – 2 hours

SURFACE PREPARATION

General Surface Preparation:

Scrape off all loose and flaking paint. Ensure surfaces are clean and free of dust.

FINISHING

Apply 2 coats of Haymes Black Stallion to pre-coated timber or 3 coats to bare timber.

APPLICATION

Roller, Brush or Spray.

To avoid skin contact, we recommend the use of disposable or rubber gloves.

Stir thoroughly before and during application using a broad flat stirrer.

THINNING & CLEAN UP

This product should not be thinned unless the surface is very porous or required for spraying. If necessary add up to 100ml clean water per litre of paint. Clean equipment with water immediately after use.

COATING CONDITIONS

Optimum application conditions are between 10°C and 30°C. Under warmer conditions refer to thinning advice.

STORAGE

Protect from extremes of temperature. Store between 5°C and 30°C.

PRECAUTIONS

- **Safety Directions:** Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapours. Wear suitable protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilated conditions that prevent inhalation of vapours.
- **First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing persists or occurs later, consult a doctor. If swallowed, DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 1126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.
NOTE: Further information is available in the form of Material Safety Data and Product Information Sheets from your local Haymes Paint Distributor or Freecall Haymes Paint on 1800 033 431. We are continually updating materials and methods, so please ensure you have the latest information
- **Protect Our Environment:** Do NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via council metal recycling facilities.
- **Manufacturer's Comment:** This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible.

**For further information or to place an order, call
Service Express direct: Phone - 1800 033 431
or email - info@haymespaint.com.au**