

HAYMES ANCILLARY Unifill

Product Code: HUF

Product description

Haymes Unifill is a ready mixed, tough and durable multi-purpose filler suitable for patching Interior and Exterior surfaces.



Key Features

- ✓ Durable
- ✓ Multi-purpose
- ✓ Quick Drying
- ✓ Interior and Exterior

Where to Use

Plaster, Brick, Concrete, Stone, Masonry & Timber

Typical properties	
Application tools	Putty Knife, Filling Blade or trowel. Smooth off with wet knife
Clean-up	Water
Dry time	30mins
Sizes	750g, 1.75kg

Application

- Ensure surface to be filled is dry and clean.
- Press filler firmly into crack/hole and smooth off surface.
- Do not overfill. Excess amounts of dry Unifill are not easily removed by sanding.
- Large holes (5mm or over) must be filled in layers.
- Allow a minimum of 3-4 hours before sanding and painting with water-based paints.
- Allow at least 24 hours before painting with solvent based paints.
- Drying times specified are at 25°C, 50% humidity.

Storage

Store between 5°C and 30°C

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable protective clothing when using. If swallowed, drink plenty of water. Contact a doctor or Poisons Information Centre (Phone 131126). If skin contact occurs wash skin thoroughly with soap and water. If symptoms persist seek medical advice.

Contact Haymes for disposal advice.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint <u>www.haymespaint.com.au</u>. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd A.B.N. 14 004 201 638 Waringa Drive Wendouree Industrial Estate Ballarat Vic 3350 Free call 1800 033 431 Free fax 1800 801 892 www.haymespaint.com.au

Date of Preparation 20/09/2016