

PRODUCT DATA SHEET

HAYMES ACRYLIC FENCE FINISH



GENERAL DESCRIPTION

An acrylic fence finish that dries to an attractive low sheen finish, providing good coverage on rough surfaces.

USES

Suitable for use on rough sawn timber and picket fences.

COLOURS

Charcoal, Farm White, Mission Brown, Pinewood Green and Redwood.

SIZES

Available in 4 Litre and 10 Litre.

COVERAGE

Approximately 8-10 square metres per litre depending upon surface porosity and application method.

APPLICATION TOOLS

Brush or Spray.

PROVIDE ADEQUATE VENTILATION DURING USE.

DRYING TIMES

Touch Dry Time – 20 minutes.

Recoat Dry Time - 2 hours.

Drying times refer to normal conditions (25°C, 50% humidity). Under cooler, humid or still conditions, longer drying times may be necessary.

DO NOT USE IN TEMPERATURES BELOW 10°C OR ABOVE 30°C.


DANGEROUS GOODS CLASSIFICATION


Not classified as Dangerous Goods.

QUICK CHECK

 Exterior

 Water Wash Up

 Brush or Spray

 Recoat – 2 hours

SURFACE PREPARATION

Recommended for direct application to rough sawn timber surfaces therefore preparation is minimal. Simply ensure that the palings are clean and firmly fixed and there are no ragged edges to provide areas for water ingress. In hot weather to ease application, hose fence down. Allow excess to dry off, and then apply two coats of Acrylic Fence direct from the can.

FINISHING

Apply one or two coats of Acrylic Fence Finish as required.

THINNING & CLEAN UP

May be thinned with up to 100ml of water per litre, if spraying. Clean equipment with water immediately after use.

COATING CONDITIONS

Do not apply if the temperature is below 10°C. In hot weather avoid painting in direct sunlight. Very warm or porous surfaces may be dampened with clean water prior to the application of Acrylic Fence Finish. Avoid applying in the late afternoon or in doubtful weather as frost, dew or rain is likely to impair the durability of the coating.

STORAGE

Protect from extremes of temperature. Store between 5°C and 30°C.

PRECAUTIONS

- **Safety & First Aid Directions:** Provide adequate ventilation with sufficient air flow for a comfortable working atmosphere. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor or Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice if irritation persists.
KEEP OUT OF REACH OF CHILDREN.
- **Protect Our Environment:** **DO NOT** pour left over product down the drain. Retain it in a marked sealed container for future use or disposal via chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council metal recycling facilities. Do not re-use empty cans.
- **Fire:** Low hazard, water based product. Use water, carbon dioxide or dry chemical agent to extinguish burning dried residue. Avoid breathing products of combustion.

For best results, preparation is vitally important when repainting. Always ensure that the adhesion of old paint is sound before proceeding.

**For further information or to place an order, call
Service Express direct: Phone - 1800 033 431
or email at - www.haymespaint.com.au**