

# HAYMES PAINT INDUSTRIAL COATING SOLUTIONS

## Antistatic Cleaner (Plastic)

Product Code: IACP

### Product description

Haymes Paint Industrial Coating Solutions Antistatic Cleaner (plastic) is a solvent-based cleaner designed to assist in reducing static discharge from plastic substrates.



#### Key Features

- ✓ Reduces static charge from plastic
- ✓ Ready for use

Product Name	Volume Solids %	Weight Solids %	Density g/mL	VOC g/L
Antistatic Cleaner (Plastics)	0.0	0.0	0.806	806.1

### Where to Use (Substrates)

Any substrates suitable for painting, always check first.

### Surface Preparation



#### All substrates

- Soak cloth thoroughly in Haymes Paint ICS Antistatic Cleaner.
- Wipe area to be painted and allow cleaner to dry.
- Apply Plastic Primer.

### Product Preparation



#### Reducer

N/A – product supplied ready for use.

### Remarks



Stir all products thoroughly each time before use.  
Stir the mixture well after the weigh-out of the components.

## Remarks



Surface temperature must always be a minimum of 3°C (5°F) above dew point.

## Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

## Shelf Life

36 months in an unopened container at room temperature away from sunlight.

## Safety & First Aid

For automotive and industrial use only by professional painters. Not recommended for sale to, or use by the general public.

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

## Protect our environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit [www.paintback.com.au](http://www.paintback.com.au) for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

## Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website [www.haymespaint.com.au](http://www.haymespaint.com.au). Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

## Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at [www.haymespaint.com.au](http://www.haymespaint.com.au) to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Free call 1800 033 431  
Free fax 1800 801 892  
[www.haymespaint.com.au](http://www.haymespaint.com.au)

Version	Version number	Date
Current	3.0	23/05/2023
Supersedes	2.0	19/05/2022