

HAYMES

Water-Based Decking Finish

Product Codes: WBDFN4, WBDFN10, WBDFM4, WBDFM10.

Product description

Haymes Water-Based Decking Finish is an easy to apply, two coat system, designed to withstand the harsh Australian climate. Delivering superior performance over traditional decking oils, Haymes Water-Based Decking finish uses advanced formulation technology to enhance the appearance of your deck and protect it from harmful UV exposure.

Key Features

- ✓ Quick Drying
- ✓ Easy to use
- ✓ Water wash-up
- ✓ Low sheen finish

Where to Use

Decking, weatherboards, garden furniture, cladding, garage doors, fencing screens and pergolas

Typical properties

Gloss	Low Sheen
Application tools	Deck brush, brush, mohair roller, lambswool applicator
Clean-up	Water Wash Up
Dry time	Touch Dry 20 minutes Recoat 2 hours
Coverage	Up to 12m ² per litre
Colours	Natural and Merbau
Sizes	4L, 10L
Recommended film build	84mm WFT 22mm DFT per coat
Volume Solids	26%
VOC	53 GL

Surface Preparation	
General Surface Preparation	<ol style="list-style-type: none"> 1. Ensure all surfaces are clean, bare, dry and free of mould, wax, grease and other contaminants prior to applying Haymes Water-Based Decking Finish. The presence of contaminants will cause rejection and delamination. 2. Clean the surface thoroughly with Haymes Simply Woodcare Wood Cleaner, ensuring you follow application instructions. 3. Rinse surface clean using a pressure washer and allow to dry. 4. Check timber is ready for coating by sprinkling with water. Ensure water penetrates the timber otherwise a repeat application of Haymes Simply Woodcare Wood Cleaner is required. 5. If necessary, fill cracks, nail holes and imperfections with Haymes Simply Woodcare Wood Putty. Sand smooth and dust down.
New Unweathered Timber Surface Preparation	<ol style="list-style-type: none"> 1. Prepare unweathered timber with Haymes Simply Woodcare Rapid Prep according to label instructions. 2. If timber has been weathered refer to General Surface Preparation. 3. Rinse clean with a pressure washer. 4. Check timber is ready for coating by sprinkling with water. Ensure water penetrates the timber otherwise a repeat application of Haymes Simply Woodcare Rapid Prep is required.
Previously Coated Surfaces	<ol style="list-style-type: none"> 1. For best results we recommend removal of all previous coatings.

Application
<p>Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice</p> <ul style="list-style-type: none"> • Do not apply to hot surfaces, in direct sunlight or if rain is expected within 24 hours. • Stir thoroughly before and during application using a broad flat stirrer. • Apply two coats by brush, roller or applicator at recommended coverage rate. • Apply along the length of the board including all exposed edges and end grain. • Appropriate preparation and application thickness is vital to the performance and longevity of the product. • All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity drying times will be extended • Water based coatings can turn milky and soften if exposed to high levels of moisture during the drying phase. Once the moisture or water has evaporated the coating will return as normal however please treat with care while this takes place. <p>Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.</p>

Thinning
Thinning is not recommended, however under warm conditions up to 50mL of water per litre of product may be added to ease application.

Care and Maintenance
Protect the coating from abrasive contact for seven days. Maintenance or re-coating of timber should occur at the first signs of deterioration. Periodically cleaning the surface with a mild detergent or Haymes Simply Woodcare Wood Cleaner to remove harmful contaminants will rejuvenate the surface and extend surface life. It is important to recoat Haymes Water-Based Decking Finish when the coating begins to show signs of wear.+

Storage
Protect from extremes of temperature, store between 5°C and 30°C.

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with water for at least 15 minutes and seek medical advice.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as paintback®. Check on the paintback® website, paintback.com.au for details of the nearest collection depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from www.haymepaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending, or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Manufactured by;
Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymepaint.com.au

Date of Preparation 09/06/2017