

MetalPlus

Rust Converter Primer Sealer

Product Base Code: MPRCPS

	Product Description									
	<p>MetalPlus Rust Converter Primer Sealer is a 2-in-1 product that blocks and converts surface rust and is the first step in preparing visibly rusted metal surfaces to prevent future rust. This product is suitable for use once you have sanded, or wire brushed as much rust as possible to treat any traces of rust that remain on the substrate.</p>									
<table border="0"> <tr> <td style="text-align: center;"></td> <td style="text-align: center;"></td> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> <tr> <td style="text-align: center;">Interior & Exterior</td> <td style="text-align: center;">Water wash-up</td> <td style="text-align: center;">Recoat 16 hrs</td> <td style="text-align: center;">Coverage 6 m²/L</td> </tr> </table>					Interior & Exterior	Water wash-up	Recoat 16 hrs	Coverage 6 m ² /L	Key Features & Benefits	
	Interior & Exterior	Water wash-up	Recoat 16 hrs	Coverage 6 m ² /L						
	Prep and Prime in one	2 - in - 1 rust converter and primer								
Seals and protects from rust	Seals existing rust and protects against further rusting									
Easy to apply	Simple brush on application									

Where to use

Substrate : Steel (Rusted)

Typical Properties

Application method	Brush
Clean-up	Water
Dry time - touch dry	2-3 hours
Coverage	6.0 m ² /L
Sizes	500ml
VOC	270g/L

Surface Preparation

General surface preparation	Remove loose rust and contamination from the metal using a wire brush or abrasive pad. Check remaining rust is adhering before converting. Clean the metal with water to ensure the surface is dust free. Surface must be dry and free from contamination before application.
-----------------------------	---

Application

- Shake bottle thoroughly before use. Wear gloves and safety glasses for protection. Only apply to rusted surfaces in low corrosion environments. Remove loose rust and surface contamination before applying. Apply one coat using a brush. Leave for 2-3 hours until surface significantly darkens. No sanding required prior to applying topcoat. Ensure surface has dried for at least 2 hours before applying MetalPlus Universal Primer or directly topcoat with MetalPlus UV Superior Enamel.

Care and Maintenance

Protect the surface against knocks and abrasion for 7 days. Maximum adhesion may take several days to develop depending on film build and drying conditions.

Storage

Store in a cool, dry, well-ventilated place and out of direct sunlight. Keep containers closed when not in use. Check regularly for leaks.

Safety & First Aid

Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126). If medical advice is needed, have product container and label at hand. If SWALLOWED, do NOT induce vomiting, drink water and seek medical advice. If in EYES, hold eyes open and flush with water for at least 15 minutes and seek medical advice. If SKIN contact occurs, remove contaminated clothing and wash skin thoroughly. If IRRITATION occurs, seek medical advice. If INHALED, remove from contaminated area, and seek medical advice.

Clear area of all unprotected personnel. Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labelled drums. Refer to State/Territory Land Waste Management Authority for disposal.

Protect our Environment

Do NOT pour left over product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via council recycling facilities. Do not re-use empty containers.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.



Australia's first family of paint. SINCE 1935

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 1.0 Date 14/3/2024
-------------------------	----------------------------

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymespaint.com.au