

NEW LOOK

Acrylic Trim Enamel Gloss

Product base code: NLATEG

Product description

A hardwearing, quick drying water-based enamel paint, specially formulated for use on interior and exterior trim surfaces. The low odour product provides a long-lasting finish for contact areas such as doors, skirting boards and window frames.



Key features

Suitable for doors, Windows & Trim

Hard-wearing durable finish

Fast drying with no lingering odour

Non yellowing

Typical properties

Colour(s)	White
Gloss level	20° 40 - 55 60° 75 - 85
Clean-up	Water
Application method	Airless spray, brush, roller.
Dry time – touch dry	20 minutes
Dry time - recoat	2 hours
Coverage per litre	Up to 16m ² /L dependent upon surface porosity, profile and method of application.
Sizes	1 L, 2 L, 4 L, 10 L,
VOC	58 g/L

Precautions

- Do NOT apply if rain or dew is expected within 24 hours of application.
- Provide adequate ventilation during application and the drying period.
- Do NOT paint in direct sunlight.
- Please consider the use of dark colours on exposed building materials, and follow the manufacturer's light reflectance value (LRV) recommendation.
- For bright and deep colours, to ensure colour accuracy and opacity, apply the specified tinted undercoat prior to the application of the top coat(s).
- Under normal conditions, the coating may require up to seven days curing to develop hardness and properties.
- If more than one can is required for the final coat, mix all cans together prior to commencing.
- Please check the colour for accuracy before application. Haymes Paint accepts no responsibility for the application of incorrect colours.

Surface Preparation

Preparation: All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting.

Previously painted surfaces - water based	No undercoat required on correctly prepared sound surfaces. Apply one coat of New Look Primer Sealer Undercoat where required to create an even base over patched or damaged surfaces, or to maximise opacity of finish coat.
Previously painted surfaces – oil based	Apply one coat of New Look Primer Sealer Undercoat to correctly prepared surfaces
Bare timber & MDF	Apply one coat of New Look Primer Sealer Undercoat to correctly prepared timber. On tannin rich timbers apply one coat of Haymes Ultralock .
Steel & Wrought Iron	Remove all loose rust or mill scale by wire brushing, scraping or sanding. Two coats of New Look Acrylic Trim Enamel may be used to finish, however for longer lasting corrosion protection, the Haymes Rustlock metal protection system is recommended. Apply one coat of Haymes Paint Ultraprime.

Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply two coats by brush, roller or spray.

Thinning

Thinning is not recommended unless spraying, add up to 100mL clean water per litre of paint to achieve acceptable atomisation. Up to 50mL of water can be added per litre of paint to ease application under very warm conditions.

Care and Maintenance

Protect the coating against abrasive contact for seven days. After seven days, the finish can be cleaned with a mild detergent solution and a soft cloth.

Storage

Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks.

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

Protect our environment

Do NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current before specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices comply with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded. Document valid unless superseded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3350
Free call 1800 033 431
www.haymespaint.com.au

Date of Preparation 17/11/2021