

NewLife®

NewLife Stain & Finish

Product Base Code: NSF

				Product Description			
				<p>Haymes Paint NewLife Stain & Finish is an easy to apply, semi-transparent, stain and finish in one. Ideal for coating interior and exterior trim, it is the convenient solution to enhancing the appearance of your timber.</p>			
 Interior & Exterior				 Mineral Turpentine wash-up			
 Recoat 6 - 8 hrs				Key Features & Benefits			

Where to use	
Substrate :	Timber-Exterior and Timber-Interior
Interior :	Doors and Trims
Exterior :	Doors and Trims
Interior trim, doors, balustrades, exterior windows and doors, weatherboards, garden furniture, cladding and garage doors.	

Typical Properties	
Colour	Natural, Natural - 3 Coat, Stain Tint and Stain Tint - 3 Coat
Application method	Brush
Gloss level	60° 65 - 75
Clean-up	Mineral Turpentine
Dry time - touch dry	6 hours
Dry time - recoat	6-8 hours
Coverage	Up to 12 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	1L, 4L
VOC	466 g/L
Volume solids	39%
Film build wet	83 µm

Film build dry	33 µm
----------------	-------

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period.
- Do not apply to hot surfaces, in direct sunlight or if rain is expected within 24 hours.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity drying times will be extended.
- Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.

Surface Preparation

General surface preparation	Ensure all surfaces are clean, bare, dry and free of mould, wax, grease and other contaminants prior to applying Haymes Paint NewLife Stain & Finish. The presence of contaminants may cause rejection and delamination.
Previously coated surface	For best results, we recommend the removal of all previous coatings.
New timber	Lightly sand surface and remove surface dust and dirt. If sanding fails to remove stubborn stains, clean the surface thoroughly with Haymes Paint Woodcare Wood Cleaner, following label application instructions. Apply first coat of NewLife Stain & Finish. If necessary, fill cracks, nail holes and imperfections using Haymes Paint Woodcare Wood Putty to match timber colour. Sand smooth in the direction of the grain and dust down. Apply second and subsequent coats of Haymes Paint NewLife Stain & Finish. Note: When applying Newlife Stain & finish ensure you lay off in the direction of the grain.
Weathered or greyed timber	Clean the surface thoroughly with Haymes Paint Woodcare Wood Cleaner following label application instructions. Apply first coat of NewLife Stain & Finish. If necessary, fill cracks, nail holes and imperfections with Haymes Paint Woodcare Wood Putty to match timber colour. Sand smooth in the direction of the grain and dust down. Apply second and subsequent coats of Haymes Paint NewLife Stain & Finish.

Application

- Apply a minimum of two coats for interior and three coats for exterior applications by brush at the recommended coverage rate.
- Apply along the length of the timber including all exposed edges and end grain.
- Appropriate preparation and application thickness is vital to the performance and longevity of the product.
- Lightly sand between coats.

Thinning

Thinning is not recommended.

Care and Maintenance

Protect the coating from abrasive contact for seven days. In dusty or high-use areas wash down periodically with a mild detergent solution to refresh and preserve the coating. Re-application should be carried out when the previous coating begins to show signs of deterioration.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. Only use this product in a well ventilated space and away from ignition sources. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version



Australia's first family of paint. SINCE 1935

Version and Date Issued	Version 2.1 Date 19/03/2024
Supersedes	Version 2.0 Date 28/06/2022

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymepaint.com.au