

RENDETEX™

Masonry Sealer

Product Code: RMS

Product Description

Haymes Rendertex Masonry Sealer is a clear penetrating solvent-based acrylic sealer for concrete surfaces. It is especially suitable as a sealer for precast and tilt-up concrete panels ensuring adequate adhesion for Rendertex coating specifications.



Product Features;

- ✓ Penetrating sealer
- ✓ Binds concrete surfaces
- ✓ Excellent adhesion

Typical Applications

Interior and Exterior precast, tilt slab or glass reinforced concrete (GRC) and other vertical concrete surfaces. Not suitable for use on previously painted surfaces or rendered expanded polystyrene (EPS).

Typical Properties

Application tools	Brush, roller, spray
Wash up	Zinc and Chlorinated Rubber Thinners
Dry-time	Recoat 4 Hours Topcoat with 7 days to prevent recontamination of the surface.
Coverage	Up to 10m ² / L. Coverage will be dependent on application technique.
Colour	Clear
Sizes	15 L
VOC	555 g/L
Volume solids	14%
Film Build per coat	Wet 100 um Dry 14 um

Surface Preparation

General surface preparation

1. All surfaces must be in sound condition.
2. New concrete must be fully cured for a minimum of 28 days. Check for moisture by sealing an impervious plastic sheet over a 1 m² area and leave for 24 hours. Darkening of the surface indicates the presence of moisture and unsuitability for painting.
3. Patch holes with an appropriate filler and allow to dry.
4. All surfaces must be clean, bare, dry and free of wax, grease, bond breakers and other contaminants that may affect the adhesion.
5. Use Rendertex Tilt Panel Prep followed by pressure washing to remove any mould release agents. Test the surface for suitability by a water beading test. Beading of water indicates that the surface is not suitable for painting and requires further cleaning.

Precautions

- DO NOT apply if the ambient temperature is less than 10°C or above 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- At times quoted assume ambient conditions of 25 °C and 50 % relative humidity. At cooler temperatures or higher humidity, dry times will be extended.
- Do not apply if rain or dew is expected within 24 hours.
- Not recommended for walk-on surfaces.

Application

- Stir thoroughly before and during application.
- Apply one coat by brush, roller or spray.
- Do not apply heavily as this will result in a glossy finish that is difficult to recoat.

Thinning

Thinning is not recommended.

Safety and First Aid

CAUTION

KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Harmful if inhaled. May cause drowsiness or dizziness. Keep out of reach of children. Read label before use. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep away from all sources of ignition – no smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and suitable respirator. Wash contaminated clothing before reuse.

Call a POISON INFORMATION CENTRE (13 11 66) or doctor/physician if you feel unwell. If medical advice is needed, have product container or label at hand. **If swallowed:** Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. **If on skin (or hair):** Remove/take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs, get medical advice/attention. **If inhaled:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.

For further safety information please refer to the product Safety Data Sheet available at www.haymepaint.com.au/products/product-information

Storage

Protect from extremes of temperature. Store between 5 °C and 30 °C. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep away from all sources of ignition – no smoking.

Protect Our Environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's Comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint (1800 033 431). We continually update materials and methods; please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Freecall 1800 033 431
Freefax 1800 801 892
www.haymespaint.com.au



Dangerous Goods

Flammable Liquid 3

Packaging Group II

UN1263

FLAMMABLE LIQUID, N.O.S.

CONTAINS:	HYDROCARBON SOLVENT	30 – 60%
	XYLENE	10 – 30%
	INGREDIENTS DETERMINED TO BE NON-HAZARDOUS	to 100%

UN 1993

PAINT

Date of Preparation: 9/ 9/ 2019 Final PDS