

## NEW LOOK

### New Look Ceiling White

Product base code: NLCW

#### Product description

A flat finish with low roller splatter. Ideal for use on ceilings in bedrooms, living rooms and hallways. Not suitable for wet areas such as bathrooms and laundries. For ceilings in wet areas use New Look Interior Low Sheen.



#### Key features

- Helps hide surface imperfections
- Low roller splatter
- Superb coverage

#### Product properties

Colour(s)	White
Gloss level	60° 1.8 – 2.4 85° 0.8 – 1.4
Clean-up	Water
Application method	Airless spray, brush, roller.
Dry time – touch dry	30 minutes
Dry time - recoat	2 hours
Coverage per litre	Up to 14m <sup>2</sup> /L dependent upon surface porosity, profile and method of application.
Sizes	2 L, 4 L, 10 L, 15 L
VOC	<50 g/L

#### Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply two coats by brush, roller or spray.

#### Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Provide adequate ventilation during application and the drying period.
- If more than one can is required for the final coat, mix all cans together prior to commencing.
- **Please check the colour for accuracy before application. Haymes Paint accepts no responsibility for the application of incorrect colours.**

## Surface Preparation

**Preparation:** All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting.

Previously painted surfaces - water based	No undercoat required on correctly prepared sound surfaces. Apply one coat of <b>New Look Primer Sealer Undercoat</b> where required to create an even base over patched or damaged surfaces, or to maximise opacity of finish coat.
Previously painted surfaces – oil based	Apply one coat of <b>New Look Primer Sealer Undercoat</b> to correctly prepared surfaces.
Bare timber & MDF	Apply one coat of <b>New Look Primer Sealer Undercoat</b> to correctly prepared timber. On tannin rich timbers apply one coat of <b>Haymes UltraLock</b> .
Bare cement, render, brick, fibre cement, masonry	Apply one coat of <b>New Look Primer Sealer Undercoat</b> to correctly prepared surfaces.
New paper-faced plasterboard	Apply one coat of <b>New Look Primer Sealer Undercoat</b> to correctly prepared surfaces.

## Thinning

Thinning is not recommended unless spraying, add up to 100mL clean water per litre of paint to achieve acceptable atomisation. Up to 50mL of water can be added per litre of paint to ease application under very warm conditions

## Care and Maintenance

New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for seven days. After seven days, the finish can be cleaned with a mild detergent solution and a soft cloth.

## Storage

Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks.

## Safety & First Aid

**Keep out of reach of children.** Avoid contact with skin and eyes, use under well ventilated conditions to prevent inhalation of vapours. Wear suitable protective clothing, eye protection and impervious gloves. If affected by inhalation, remove to fresh air. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Should any symptoms persist seek prompt medical advice.

## Protect our environment

Do NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website [www.paintback.com.au](http://www.paintback.com.au) for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

## Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint [www.haymespaint.com.au](http://www.haymespaint.com.au). We are continually updating materials and methods, so please ensure you have the latest information.

## Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current before specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices comply with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded. Document valid unless superseded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Free call 1800 033 431  
[www.haymespaint.com.au](http://www.haymespaint.com.au)

**Date of Preparation** 07/09/2020  
**Supersedes** Version with preparation date 13/09/2019.