

HAYMES ARTISAN COLLECTION

Rendercoat

Product Code: AACR

Product description

Haymes Artisan Collection Rendercoat is a highly durable, textured acrylic high build product that is resistant to the extremes of weather, mould and fungal growth. Suitable for interior and exterior it provides the ultimate solution to transform surfaces through the beauty of paint, offering the perfect Artisan finish with a bespoke textural look and feel.



Key Features;

- ✓ Bespoke texture
- ✓ Handcrafted finish
- ✓ Premium quality
- ✓ Interior and exterior

Where to use

Ideal for use on surfaces such as; plasterboard, masonry, brick and cementitious surfaces including broad exterior walls, retaining walls, garden beds and water features (above the waterline).

Typical properties

Gloss	Flat
Application tools	Texture roller, trowel, lambswool mitt.
Clean-up	Water
Dry time	Touch dry 4 hours Recoat 24 hours
Coverage	Up to 3m ² /L depending upon surface porosity and application method.
Colour	Tintable
Sizes	15 L
VOC	46.0 g/ L
Volume solids	55.6%

Surface preparation	
General surface preparation	<ol style="list-style-type: none"> 1. Fill cracks, nail holes and imperfections with Haymes Render Patch. 2. Scrape all loose/flaking paint. Sand smooth & dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. 3. Apply one coat of Haymes Renderprime where required.
Masonry, brick, concrete and render	<ol style="list-style-type: none"> 1. New concrete must be cured for at least 28 days prior to coating. 2. Wash with Haymes Unikleen Sugar Soap and rinse with clean water. 3. Apply a coat of Haymes Rendertex Masonry Sealer 4. Complete General Surface Preparation
Precast concrete / tilt slab panels	<ol style="list-style-type: none"> 1. New concrete must be cured for at least 28 days prior to coating. 2. Prior to coating ensure any bond breaker/mould release agents are removed. If present, wash using Rendertex Tilt Panel Prep following label recommendations. 3. Test the surface for water beading. If water beading occurs repeat Step 2 until there is no water beading. 4. Complete General Surface Preparation. 5. Apply one coat of Haymes Rendertex Renderprime or Rendertex Masonry Sealer.

Application
<p>Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period. All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.</p> <p>Do not apply if rain or dew is expected within 24 hours.</p> <ol style="list-style-type: none"> 1. Stir thoroughly with a power stirrer before and during application. 2. Mask adjacent areas and place a drop cloth below areas to be painted. 3. For vertical surfaces work from top to bottom. 4. It is recommended to trial your preferred application tool to check profile. A fine texture roller will provide a more subtle finish compared with a coarse texture/spaghetti roller. 5. Apply even coats by texture roller, trowel or lambswool mitt ensuring that the application rate is controlled to achieve the desired film build. 6. <ol style="list-style-type: none"> a. MITT: Using the mitt spread Rendercoat generously over the surface with a circular motion. b. MITT/ TROWEL: To create a scratched texture look, place the trowel flat onto the mitt finish and in a circular motion smooth it out. Then use the trowel edge to scratch over the product with both vertical and horizontal strokes. For this application technique, apply only one coat of Rendercoat over an Artisan Basecoat or Low Sheen Acrylic matched to your chosen Rendercoat colour. c. ROLLER: Dip a Medium or Coarse textured roller into the Rendercoat and generously spread keeping a consistent texture. d. ROLLER/ TROWEL: To achieve a smooth finish allow the product to set for 10 minutes then smooth in a circular motion using a plastic trowel. 7. Two to three coats may be required dependent upon any joints that are to be covered and the chosen application technique and finish. 8. Additional durability can be achieved through applying a coat of Haymes Rendertex Rendershield or two coats of Haymes Solashield. <p>Please check the colour for accuracy prior to application. Haymes paint accepts no responsibility for the application of incorrect colours.</p> <p>IMPORTANT NOTE: The finished result of decorative finishes will vary dependent upon the applicator and the application technique used. Haymes Paint recommends a sample application be conducted prior to undertaking your project to ensure consistency of outcome. This is due to the variance that may be experienced between the Haymes finished sample and that achieved by the applicator. We recommend viewing our instructional videos located at www.haymespaint.com.au/artisancollection</p>

Thinning

Thinning is not recommended.

Care and maintenance

Due to the finish exuding a textured finish we recommend the appropriate care is taken with items such as furniture and clothes that may come in contact with the finish. The textured nature of the finish may cause scratching to furniture and grabbing of clothes if contact is made.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety and First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Versioned: Updated 13th August, 2021
Replaces version dated 27th July, 2020