

## TAR SOLVE 150

### DESCRIPTION

**TAR SOLVE 150** is a fast acting solvent degreaser which cuts through buildup of asphalt or heavy grease. Emulsifies tar, asphalt, grease and oil for removal from cars, engines, trucks, heavy equipment and other industrial parts.

### APPLICATIONS

Suitable for machine shops, industrial plants, trucks, cars, repair shops, pipeyards, drilling rigs, equipment, machinery, walls, tools, pipe fittings and floors.



### TECHNICAL DATA

<b>FORM:</b> Liquid	<b>FLASH POINT:</b> 70°C
<b>ODOUR:</b> Pine	<b>FLAME EXTENSION:</b> LEL 0.6% - VEL 7.0%
<b>COLOUR:</b> Green	<b>SOLUBILITY IN WATER:</b> Emulsifies
<b>DETERGENCY:</b> Low	<b>SPECIFIC GRAVITY:</b> 0.85g/ml
<b>TOXICITY:</b> Poison S5	<b>%VOLATILE BY VOLUME:</b> 99.9%
<b>WETTING ABILITY:</b> Fair	<b>pH:</b> NA
<b>STORAGE ABILITY:</b> 1 Year	<b>PROPELLANT:</b> Nil
<b>COLD STABILITY:</b> Good	<b>EVAPORATION RATE:</b> Rapid
<b>PHOSPHATES:</b> Nil	<b>BIODEGRADABILITY:</b> No

### DIRECTIONS FOR USE

**TAR SOLVE 150** can be applied undiluted to surface to be cleaned. Apply with sprayer or brush on. For floors, use mop and allow 5 minutes for penetration. Rinse with steam or water. May be diluted with up to 10 parts of water or aliphatic solvent for light duty applications. Add 10%-20% **MA TRUCK WASH** so as to make **TAR SOLVE 150** stay wet on the sides of equipment for much longer periods. **MA TRUCK WASH** helps slow down the evaporation rate of the product therefore helping to remove more tar and bitumen. **DO NOT USE ON PLASTIC.**