

CIRCLE SPRAY

DRY MOLY LUBRICANT

DESCRIPTION

CIRCLE SPRAY is a dry moly lubricant designed to handle extreme pressure while being non-greasy which aids in resisting dust and abrasives.

APPLICATIONS

For use on grader circles, back hoe slides, crane booms, engine assembly and roller doors.



TECHNICAL DATA

FORM: Aerosol
ODOUR: Strong
COLOUR: Black
DETERGENCY: N/A
TOXICITY: Low
WETTING ABILITY: N/A
STORAGE ABILITY: 1 Year
COLD STABILITY: Stable
PHOSPHATES: No

FLASH POINT: <63°C
FLAME EXTENSION: 0.6% LEL - 7.0% VEL
SOLUBILITY IN WATER: No
SPECIFIC GRAVITY: 0.9 g/ml
%VOLATILE BY VOLUME: 60%
pH: N/A
PROPELLANT: Butane
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

DIRECTIONS FOR USE

CIRCLE SPRAY is generally used where a non-greasy film is required. **CIRCLE SPRAY** resists dirt and helps to stop friction on metal to metal applications. Handles high temperatures. The major use for circle spray is on graders; helps to reduce wear and tear on the circle.