

FLAT BLACK

SPRAY PAINT

DESCRIPTION

FLAT BLACK is a high quality aerosol spray paint, That leaves a smooth flat finish.

APPLICATIONS

For interior and exterior use on cupboards, doors, gates, wrought iron, screens, trellises, in fact anywhere that a quality finish is required.

Touch dry in 10 minutes.



TECHNICAL DATA

FORM: Aerosol
ODOUR: Solvent
COLOUR: Black
DETERGENCY: N/A
TOXICITY: Not scheduled
WETTING ABILITY: N/A
STORAGE ABILITY: 1 year +
COLD STABILITY: Do not freeze
PHOSPHATES: None

FLASH POINT: -80°C
FLAME EXTENSION: LEL 1.1% - UEL 7.4%
SOLUBILITY IN WATER: Immiscible
SPECIFIC GRAVITY: 0.85g/ml
%VOLATILE BY VOLUME: 95%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Faster than butyl acetate
BIODEGRADABILITY: No

DIRECTIONS FOR USE

SURFACE PREPARATION

Surface must be free of dust, wax and rust. All bare timber should be undercoated and bare metal should be primed with metal primer. Newspapers or plastic drop sheets should be spread around work to protect adjoining areas from overspray.

ADJUST THE SPRAY PATTERN

The fan jet may be adjusted for horizontal or vertical spraying by turning the jet to the horizontal or vertical position.



SPRAY APPLICATION

Applying several light coats rather than one heavy coat will achieve the best results. If a second coat is required, apply after 1 hour and before 2 hours. If this is not possible, wait 4 days before re-coating.

AFTER USE

Turn can upside down and spray until jet clears. Any overspray may be cleaned up with mineral turps.