

June 2017 Technical Data Report

TAKE OFF

DESCRIPTION

Directions: This product is a very aggressive floor stripper. Please read all instructions carefully for proper use.

APPLICATIONS

Dilutions: Light Duty Stripping/Automatic Scrubbing: 1:10 - Medium Duty Stripping/Touch Up: 1:5 - Heavy Duty Stripping: 1:1.

1. Remove baseboards or kickplates from any shelving or wall units in order to get access to the edges. Strip these surfaces separately using an aerosol foam or gel stripper to maintain good contact/dwell time and for clinging to vertical surfaces. If not removable and/or if prohibitive, they can be stripped in place but be sure to do so prior to floor stripping to prevent run off onto stripped floor surfaces.

2. Dilute with cold water to proper level and apply liberally to floor. Cover completely and allow the stripper to stand for 5 to 10 minutes. **DO NOT ALLOW THE FLOOR TO DRY. 3.** Agitate with a mop to loosen the finish or use a stripping pad on a 175 RPM buffing machine. Pick up solution with a wet/dry vacuum. **NOTE:** The solution may be mopped up but a second person may be needed to follow with a clear water rinse to prevent any emulsified finish from redepositing on the floor. It may be necessary to apply a small amount of stripper and touch up mop any deposits still remaining. **4.** Once floor is dry, check for dusty residue. If solution is not fully removed, indicated by remaining residue, a clear water rinse may be necessary. **5.** Recoat with finish per the instructions on label copy. **IMPORTANT:** Do not allow contact with aluminium surfaces.

TECHNICAL DATA

FORM: Liquid COLOUR: Clear DETERGENCY: Ok TOXICITY: Toxic WETTING ABILITY: Excellent STORAGE ABILITY: 2 year EVAPORATION RATE: Slow PHOSPHATES: Nil

ODOUR: Sweet

SOLUBILITY IN WATER: Soluble SPECIFIC GRAVITY: 1.0g/ml %VOLATILE BY VOLUME: Nil pH: >11.5 COLD STABILITY: Stable BIODEGRADABILITY: Yes

