

TAR SOLVE 200

DESCRIPTION

TAR SOLVE 200 is a fast acting solvent degreaser which cuts through buildup of asphalt or heavy grease. Emulsifies tar, asphalt, grease and oil for removal from cars, engines, trucks, heavy equipment and other industrial parts.

APPLICATIONS

Suitable for machine shops, industrial plants, trucks, cars, repair shops, pipeyards, drilling rigs, equipment, machinery, walls, tools, pipe fittings and floors.



TECHNICAL DATA

FORM: Liquid	FLASH POINT: 70°C
ODOUR: Pine	FLAME EXTENSION: LEL 0.6% - VEL 7.0%
COLOUR: Green	SOLUBILITY IN WATER: Emulsifies
DETERGENCY: Low	SPECIFIC GRAVITY: 0.85g/ml
TOXICITY: Poison S5	%VOLATILE BY VOLUME: 99.9%
WETTING ABILITY: Fair	pH: NA
STORAGE ABILITY: 1 Year	PROPELLANT: Nil
COLD STABILITY: Good	EVAPORATION RATE: Rapid
PHOSPHATES: Nil	BIODEGRADABILITY: No

DIRECTIONS FOR USE

TAR SOLVE 200 can be applied undiluted to surface to be cleaned. Apply with sprayer or brush on. For floors, use mop and allow 5 minutes for penetration. Rinse with steam or water. May be diluted with up to 10 parts of water or aliphatic solvent for light duty applications. Add 10%-20% **MA TRUCK WASH** so as to make **TAR SOLVE 200** stay wet on the sides of equipment for much longer periods. **MA TRUCK WASH** helps slow down the evaporation rate of the product therefore helping to remove more tar and bitumen. **DO NOT USE ON PLASTIC.**