

June 2014 **Technical Data Report** 

# **OPTIMAX TOP COAT**

METAL CROSSLINKED FLOOR POLISH

## **DESCRIPTION**

**Optimax Top Coat** is a high solids floor polish for all types of floors. Extremely durable coating providing unsurpassed gloss with low maintenance requirements. **Optimax Top Coat** has multi-speed and extended wear properties that allows for heavy traffic areas to retain a high gloss finish with infrequent maintenance schedules.



#### **APPLICATIONS**

Institutions, Hospitality, Hospitals flooring coating and sealing, polishing contractors. Commercial cleaning contractors.

# **TECHNICAL DATA**

FORM: Liquid ODOUR: Faint

SOLUBILITY IN WATER: Soluble SPECIFIC GRAVITY: 1.0g/ml % VOLATILE BY VOLUME: N/A

pH: 7-8

**EVAPORATION RATE: Slow** 

**COLD STABILITY: Stable** 

COLOUR: White DETERGENCY: No TOXICITY: N/A

WETTING ABILITY: N/A STORAGE ABILITY: 2 Years

PHOSPHATES: Nil BIODEGRADABILITY: Yes

### **DIRECTIONS FOR USE**

Used in a spray buff application, dilute Optimax Top Coat at between 4 and 7 to 1 with water.

STRIPPING INFO: Minehan Agencies "Take Off" Heavy Duty Stripper is recommended.

DIRECTIONS FOR USE: As a permanent high gloss polish the more coats applied the longer the polish will last.

SPRAY BUFF METHOD: Spray with a trigger sprayer over small areas and then buff.

REVITALIZER: If working on an area that is excessively soiled, a pH neutral cleaner should be used and the area damp mopped before applying a solution of approximately 3 to 1 with water.

SAFETY: Keep out of the reach of children. Wash thoroughly after use and before eating or drinking.

FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre - Phone 131126. If swallowed, do NOT induce vomiting. Rinse mouth thoroughly and give a glass of water to drink. If in eye/s, hold eye/s open, flood with water for at least 15 minutes and seek medical attention immediately. If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water.