



Technical Data Sheet PART A & PART B

EPiC AquaEpoxy PART A

Product Description EPiC AquaEpoxy is a high strength, water based 2 pack epoxy coating which provides excellent protection for concrete, timber, masonry and primed metal surfaces. EPiC AquaEpoxy has been developed to provide excellent durability for INTERIOR only applications with the benefits of excellent hardness, abrasion and scuff resistance. As a water based coating, EPiC AquaEpoxy is low VOC and ideal as an environmentally friendly alternative to traditional solvent based epoxy coatings. EPiC AquaEpoxy provides excellent protection against petrol, oil, fatty oils, alkali and acid making it ideal for a wide variety of applications such as commercial and industrial floors and walls. EPiC AquaFloor has a high resistance to corrosion and is impervious to water and moisture. EPiC AquaEpoxy is also rated for food stuffs and can be used in a variety of areas including Restaurants, Hospitals and Supermarkets etc.

EPiC AquaEpoxy

Features:

- Excellent interior and exterior durability
- Hard wearing finish
- Excellent adhesion
- Excellent hardness
- High resistance to Abrasion
- Impervious to Water and Moisture
- Resistant to bacterial growth
- Easy application by brush, roller or spray

Safety Precautions: Observe all Occupation Health and Safety (OH&S) precautions. Refer to the relevant Safety Data Sheets (SDS) for product safety related information. For further information and support: **Nutech Paint 03 9770 3000**
www.nutechpaint.com.au

Provisions:

Chemical Type: Water based Epoxy

Product Attributes Per Cent Volatiles (VOC): 6%
Solubility: In Water
Minimum Film Forming Temperature 15 Degrees C.
Minimum Dry Film Thickness 100µm per coat

Typical Applications Typical projects include:
Domestic & Multi Density Residential, Industrial, Commercial, Restaurants, Hospitals, Supermarkets, Service Stations and Workshops where excellent Interior performance and low VOC are required

Appearance White or colour tinted viscous liquid

Coverage / Spread Rate 8 – 10 m²/L
Note: Coverage will depend on the porosity and roughness of the surface. To maximise performance do not over spread.



Packaging:	Part A: 4L Kit, 10L Kit, 20L Kit
Storage	Cool, dry location. Avoid contact with direct sunlight and heat
Shelf life	Un-mixed, Stored 24 months @ 25°C
Substrate Recommendations:	EPiC AquaEpoxy is suitable for a wide range of substrates such as timber, masonry, brick, metal.
NOTE	For greater slip resistance, EPiC AntiSlip – Coarse or Fine can be broadcast on the wet freshly applied surface of the first coat and encapsulated with a subsequent coat of EPiC AquaEpoxy . Testing is recommended before proceeding to ensure that a potential slip hazard is avoided. Refer to your Nutech specialist for alternative recommendations on steep, smooth surfaces.
Mixing/ Thinning	Prior to Commencement: Stir thoroughly prior to use. Part A: 3 Parts Part B: 1 Part After drill mixing leave to stand for 10 minutes before using to allow full activation. Thinning: Clean Water Maximum Thinner dilution; Brush/Roller 1st Coat: Bare concrete and masonry surfaces thin 20% - 25% for excellent penetration and adhesion. Brush/Roller 2nd Coat: Nil Spray: 10% - 15% <i>Note: Stirring by hand with a stirring stick is inadequate to provide a homogeneous mix.</i> <i>DO NOT store mixed product in spray equipment to avoid damage.</i>
Pot Life (when mixed)	2 Hours @ 25°C DO NOT use after pot life has expired
Test Patch	Conduct a small test patch in an inconspicuous area to ensure adequate product performance, substrate porosity and provide an indication of the time required to complete project.
Substrate note:	All surfaces must be clean and in sound condition. Remove all oil, dirt, grease, flaking paint and contamination. Fill cracks and holes in the surface as required. <i>Improperly prepared surfaces may result in coating failure.</i>
Application	Brush Roller Airless Spray
Procedure:	<i>Do not apply to surface temperatures below 10 Deg. C or Above 30 Deg. C and allow for adequate drying time.</i> <i>In cold weather do not overcoat until the first coat is fully dried.</i>



Pre-painted surfaces: should be tested for compatibility and adhesion prior to over coating. See **Nutech Coating Test Kit Fact Sheet**

Rusted and weathered steel:

Must be power wire brushed to remove rust, dirt and scale then treated with **Nu-EcoSafe Rust**, rust converter and inhibitor before applying **EPiC EtchPrimer**.

New Concrete Surfaces:

- Must have a **PH level less than 10 and had a minimum 28 days to cure.**

New and old concrete surfaces:

- Must be etched using 1 Part **Nu-EcoSafe Concrete Etch** to 10 Parts Water.
- High Pressure Water Blast area (>2500Psi) and allow to completely dry.
- Painted concrete in poor condition should be stripped using our **Nu-Ecosafe** range of paint strippers and **Nu-EcoSafe Concrete Etch** before application.

Number of Coats:

Brush or Roller: - 2 Coats

Spray: 2 – 3 coats or minimum of 150µm wet film thickness.

Drying Time Touch Dry 2- 4 hours @ 25°C @ 50% relative humidity.

Recoat After 4 hours but within 24 hours.
If recoating after 7 days, the surface must be abraded.

Hard Cure 7 Days

Clean Up Protecting Our Environment is important to Nutech Paints:
Clean up with clean water. Do not pour leftover paint down drains or in rubbish bins. Unwanted paint should be kept in a sealed container and then disposed of via special waste collection services.
Empty paint containers should be left open in a well ventilated area to dry out.
Dispose of empty paint containers in accordance with local authority's guidelines.
Always check with your local council first.

First Aid **SEEK IMMEDIATE MEDICAL ATTENTION.** Refer to the appropriate **Nutech Material Safety Data Sheet (MSDS)** for further information.
For medical emergencies only, call: 000

- In case of eye contact, flush thoroughly with water for at least 15 minutes.
- In case of skin contact, wash affected areas with soap and water. If irritation persists.
- Remove and wash contaminated clothing.
- If inhalation causes physical discomfort, remove to fresh air.
- If discomfort persists, or any breathing difficulty occurs or if swallowed seek medical advice.

Warranty Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.



Nutech Paint
For a perfect finish!

Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty.

Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages.

Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability

Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.

Disclaimer

The information given on this data sheet is based on many years' experience and is correct to the best of our knowledge. However, since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.'

The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Nutech

Nutech Paint

PTY LTD

☎03 9770 3000

✉sales@nutech.com.au

www.nutechpaint.com.au



Technical Data Sheet PART A & PART B

EPiC AquaEpoxy **PART B**

Product Description **EPiC AquaEpoxy Part B** is to be blended in kit form with **EPiC AquaEpoxy Part A**.
For mixing ratio recommendations please refer to the **EPiC AquaEpoxy Part A** Technical Data Sheet.

Safety Precautions: Observe all Occupation Health and Safety (OH&S) precautions.
Refer to the relevant Safety Data Sheets (SDS) for product safety related information.
For further information and support: **Nutech Paint 03 9770 3000**
www.nutechpaint.com.au

Provisions:

Chemical Type: Water based Crosslinker

Product Attributes Per Cent Volatiles (VOC): 5%
Solubility: In Water
Minimum Film Forming Temperature: 10 Deg.C.

Typical Applications Crosslinker for **PART A**

Appearance Clear viscous liquid

Packaging **Part B: 1L, 2.5L, 5L**

Storage Cool, dry location. Avoid contact with direct sunlight and heat

Shelf life Stored 24 months @ 25°C (Or relevant to specific Product)

Substrate

Recommendations: N/A - REFER PART A TDS

Mixing/ Thinning

Part A: 3 Parts
Part B: 1 Part
After drill mixing leave to stand for 10 minutes before using to allow full activation.
Thinning: Clean water
Maximum Thinner dilution: REFER PART A TDS

***Note:** Stirring by hand with a stirring stick is inadequate to provide a homogeneous mix.*

DO NOT store mixed product in spray equipment to avoid damage.

Application N/A - REFER PART A TDS

Procedure: N/A -REFER PART A TDS



Drying Time N/A - REFER PART A TDS

Recoat N/A - REFER PART A TDS

Clean Up Protecting Our Environment is important to Nutech Paints:
Clean up with clean water or dispose of equipment. Do not pour leftover paint down drains or in rubbish bins. Unwanted paint should be kept in a sealed container and then disposed of via special waste collection services.
Empty paint containers should be left open in a well ventilated area to dry out. Dispose of empty paint containers in accordance with local authority's guidelines. Always check with your local council first.

First Aid **SEEK IMMEDIATE MEDICAL ATTENTION.** Refer to the appropriate **Nutech Material Safety Data Sheet** (MSDS) for further information.
For medical emergencies only, call: 000

- In case of eye contact, flush thoroughly with water for at least 15 minutes.
- In case of skin contact, wash affected areas with soap and water. If irritation persists.
- Remove and wash contaminated clothing.
- If inhalation causes physical discomfort, remove to fresh air.
- If discomfort persists, or any breathing difficulty occurs or if swallowed seek medical advice.



Warranty

Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products. Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty.

Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages.

Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability

Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.

Disclaimer

The information given on this data sheet is based on many years' experience and is correct to the best of our knowledge. However, since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.'

The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Nutech

Nutech Paint

PTY LTD

☎03 9770 3000

✉sales@nutech.com.au

www.nutechpaint.com.au