

# Safety Data Sheet



## Hazardous, Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **EPIC ANTI-CORROSIVE PRIMER**

#### Synonyms

EPIC ANTI-COR PRIME DK GRY 20L ANTI CORROSIVE PRIMER 20L  
EPIC ANTI-COR PRIMER DK GRY 1L ANTI CORROSIVE PRIMER 1L  
EPIC ANTI-COR PRIMER DK GRY 4L ANTI CORROSIVE PRIMER 4L

#### Product Code

EPIC0120  
EPIC0101  
EPIC0104

**Recommended use:** PREPARATORY PRODUCT TO STOP RUST

**Supplier:** Nutech Paint Pty Ltd

**ABN:** 94 242 116 396

**Street Address:** 4 Keppler Circuit  
Seaford VIC 3198  
Australia

**Telephone:** 03 9770-3000

**Facsimile:** 03 9775-1680

**Emergency Telephone number:** 03 9770-3000 (7:45 am-4:30 pm; Mon-Fri, AEST)

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



#### Signal Word

Danger

#### Hazard Classifications

Flammable Liquids - Category 2

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Irritation - Category 2A

Toxic to Reproduction - Category 2

Specific Target Organ Toxicity (Single Exposure) - Category 3 Narcotic Effects

Specific Target Organ Toxicity (Repeated Exposure) - Category 2

Acute Hazard to the Aquatic Environment - Category 3

Chronic Hazard to the Aquatic Environment - Category 3

#### Hazard Statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child .

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### Prevention Precautionary Statements

P102 Keep out of reach of children.

Product Name: EPIC ANTI-CORROSIVE PRIMER

Reference No: NUTP0044

Issued: 2018-05-01

Version: 4

Page 1 of 8



# Safety Data Sheet

- P103 Read label before use.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust, fume, gas, mist, vapours or spray.
- P261 Avoid breathing dust, fume, gas, mist, vapours or spray..
- P264 Wash hands, face and all exposed skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P281 Use personal protective equipment as required.

## Response Precautionary Statements

- P101 If medical advice is needed, have product container or label at hand.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.

## Storage Precautionary Statements

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

## Disposal Precautionary Statement

- P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Poison Schedule:** S5. Caution

## DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**Dangerous Goods Class:** 3

## 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Solvent naphtha, petroleum, light aliphatic	64742-89-8	1 - 10 %
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 10 %
Toluene	108-88-3	10 - 30 %
Xylene	1330-20-7	10 - 30 %
Ingredients determined to be Non-Hazardous		Balance

## 4. FIRST AID MEASURES

# Safety Data Sheet



If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim to fresh air, remove any contaminated clothing to prevent further exposure. Keep victim warm. If symptoms persist seek medical attention.

**Skin Contact:** Remove contaminated clothing and wash affected area with plenty of soap and water. If irritation, swelling or blistering occurs seek medical attention immediately

**Eye contact:** Immediately open eye and flush with plenty of running water for at least 15 minutes. Seek medical attention

**Ingestion:** If swallowed do not induce vomiting. Rinse the mouth out with water and give a glass of water and seek medical attention immediately.

**Notes to physician:** Treat symptomatically. Treat symptomatically. The Poisons Information Centre can be contacted on 131 126 for advice or contact your local doctor or hospital

## 5. FIRE FIGHTING MEASURES

**Hazchem Code:** •3YE

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Highly flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal. Remove all ignition sources. Isolate area. Recover free liquid. Absorb in dry inert material and place in a sealable container and label accordingly. Avoid breathing vapours. Adequate ventilation or the use of breathing apparatus may be needed. Local authorities will need to be advised if spill is of a large enough volume

### LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services. Remove all ignition sources. Isolate area. Recover free liquid. Absorb in dry inert material and place in a sealable container and label accordingly. Avoid breathing vapours. Adequate ventilation or the use of breathing apparatus may be needed. Local authorities will need to be advised if spill is of a large enough volume

**Dangerous Goods – Initial Emergency Response Guide No: 14**

# Safety Data Sheet



## 7. HANDLING AND STORAGE

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Keep out of the reach of children. Avoid contact with eyes or mouth and avoid repeated prolonged contact with skin.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks. Store in a cool dry place out of direct sunlight, away from ignition sources and not stored near oxidising materials. Containers should be sealed when not in use and should be checked on a regular basis for signs of damage or leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison Schedule 5 (Caution) and must be stored, maintained and used in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	
Toluene	50	191	150	574	Sk
Xylene	80	350	150	655	

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

# Safety Data Sheet



Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Practice strict hygiene – wash hands before breaks and after finishing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Base Units:</b>	Litres
<b>Form:</b>	Viscous Liquid
<b>Colour:</b>	Grey
<b>Odour:</b>	Distinct Aromatic Hydrocarbon odour
<b>Solubility:</b>	Insoluble in Water
<b>Solubility in water:</b>	0.5 grams per Litre
<b>Specific Gravity (20 °C):</b>	1.05 - 1.06
<b>Relative Vapour Density (air=1):</b>	4.3
<b>Vapour Pressure (20 °C):</b>	15 kPa @ 20°C
<b>Flash Point (°C):</b>	-20
<b>Flammability Limits (%):</b>	0.6 - 7.5
<b>Autoignition Temperature (°C):</b>	350-536
<b>Boiling Point/Range (°C):</b>	66 - 185
<b>pH:</b>	N/APP
<b>Evaporation Rate (n-Butyl acetate=1):</b>	6.1
<b>Total VOC (g/Litre):</b>	54

(Typical values only - consult specification sheet)  
N Av = Not available, N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal use conditions.

**Conditions to avoid:** Avoid repeated contact with person, contact with food and high temperature conditions with sealed containers.

**Incompatible materials:** Strong oxidising materials

**Hazardous decomposition products:** Oxides of Carbon

**Hazardous reactions:** Hazardous reaction with strong oxidising agents

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Inhalation of the product can produce an irritating effect to the mucous membrane of the respiratory tract. Headache, nausea, loss of balance and drowsiness is common when excess inhalation occurs. Central nervous depression can also occur with excess inhalation, which may lead to unconsciousness. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure

# Safety Data Sheet



is prolonged, unconsciousness.

**Skin contact:** If contact with the skin is made a degreasing effect will be witnessed and will be likely to cause irritation of the skin. Repeated contact can lead to conditions such as dermatitis in the contact area. Absorption of some of the product components may occur and produce the relevant toxic effects.

**Ingestion:** If swallowed nausea, vomiting and depression of the central nervous system can occur.

**Eye contact:** May be irritating to the eye.

## Acute toxicity

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >20 mg/L

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Corrosion/Irritancy:** Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

**Aspiration hazard:** This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

## Chronic Toxicity

**Mutagenicity:** This material has been classified as non-hazardous.

**Carcinogenicity:** This material has been classified as non-hazardous.

**Reproductive toxicity (including via lactation):** This material has been classified as a Category 2 Hazard.

**Specific target organ toxicity (repeat exposure):** This material has been classified as a Category 2 Hazard.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as a Category Acute 3 Hazard. Acute toxicity estimate (based on ingredients): 10 - 100 mg/L Fish :Toxic: 1 < LC/EC/IC50 <= 10 mg/l Aquatic Invertebrates :Toxic: 1 < LC/EC/IC50 <= 10 mg/l Algae : Toxic: 1 < LC/EC/IC50 <= 10 mg/l

**Long-term aquatic hazard:** This material has been classified as a Category Chronic 3 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 10 - 100 mg/L, where the substance is not rapidly degradable and/or BCF  $\geq$  500 and/or log  $K_{ow} \geq$  4.

**Ecotoxicity:** No information available.

**Persistence and degradability:** The product is readily biodegradable.

**Bioaccumulative potential:** No information available.

# Safety Data Sheet



**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Any disposal of material should be done in accordance with the local authorities

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** II  
**Hazchem Code:** •3YE  
**Emergency Response Guide No:** 14

**Proper Shipping Name:** PAINT

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** II

**Proper Shipping Name:** PAINT

### AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.





# Safety Data Sheet



UN No: 1263  
Dangerous Goods Class: 3  
Packing Group: II  
  
Proper Shipping Name: PAINT

## 15. REGULATORY INFORMATION

**This material/constituent(s) is covered by the following requirements:**

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).
- All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

**HSNO Group Standard:** HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard

## 16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.