

# Safety Data Sheet



## Hazardous, Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **PAVECOAT COLOURS**

#### Synonyms

PAVECOAT BEIGE 10LT  
PAVECOAT BEIGE 20LT  
PAVECOAT BEIGE 4LT  
PAVECOAT BENDIGO GREY 10LT  
PAVECOAT BENDIGO GREY 20LT  
PAVECOAT BENDIGO GREY 4LT  
PAVECOAT BIRCH GREY 10L  
PAVECOAT BIRCH GREY 20L  
PAVECOAT BIRCH GREY 4LT  
PAVECOAT BLACK 10LT  
PAVECOAT BLACK 20LT  
PAVECOAT BLACK 4LT  
PAVECOAT BLUE RIDGE 10LT  
PAVECOAT BLUE RIDGE 20LT  
PAVECOAT BLUE RIDGE 4LT  
PAVECOAT BLUESTONE 10LT  
PAVECOAT BLUESTONE 20LT  
PAVECOAT BLUESTONE 4LT  
PAVECOAT BURGUNDY 10LT  
PAVECOAT BURGUNDY 20LT  
PAVECOAT BURGUNDY 4LT  
PAVECOAT BUSHLAND 10LT  
PAVECOAT BUSHLAND 20LT  
PAVECOAT BUSHLAND 4LT  
PAVECOAT CHAMPAGNE 10LT  
PAVECOAT CHAMPAGNE 20LT  
PAVECOAT CHAMPAGNE 4LT  
PAVECOAT CHARCOAL 10LT  
PAVECOAT CHARCOAL 20LT  
PAVECOAT CHARCOAL 4LT  
PAVECOAT CHOCOLATE 10LT  
PAVECOAT CHOCOLATE 20LT  
PAVECOAT CHOCOLATE 4LT  
PAVECOAT CLASSIC RED 10LT  
PAVECOAT CLASSIC RED 20LT  
PAVECOAT CLASSIC RED 4LT  
PAVECOAT CORAL 10LT  
PAVECOAT CORAL 20LT  
PAVECOAT CORAL 4LT  
PAVECOAT DEEP OCEAN 4LT  
PAVECOAT DEEP OCEAN 10LT  
PAVECOAT DEEP OCEAN 20LT  
PAVECOAT DUNE 10LT  
PAVECOAT DUNE 20LT  
PAVECOAT DUNE 4LT  
PAVECOAT EARL GREY 10LT  
PAVECOAT EARL GREY 20LT  
PAVECOAT EARL GREY 4LT  
PAVECOAT GRECIAN TERRACOTTA 10LT  
PAVECOAT GRECIAN TERRACOTTA 20LT  
PAVECOAT GRECIAN TERRACOTTA 4LT  
PAVECOAT GUNMETAL 10LT

#### Product Code

CSCBBEIGE10  
CSCBBEIGE20  
CSCBBEIGE04  
CSBG10  
CSBG20  
CSBG04  
CSCBBIRCH10  
CSCBBIRCH20  
CSCBBIRCH04  
CSBLK10  
CSBLK20  
CSBLK04  
CSBLUERIDGE10  
CSBLUERIDGE20  
CSBLUERIDGE04  
CSBS10  
CSBS20  
CSBS04  
CSBURG18010  
CSBURG18020  
CSBURG18004  
CSBUSHLAND10  
CSBUSHLAND20  
CSBUSHLAND04  
CSCHAMP10  
CSCHAMP20  
CSCHAMP04  
CSCHAR10  
CSCHAR20  
CSCHAR04  
CSCHOCO10  
CSCHOCO20  
CSCHOCO04  
CSCLARED10  
CSCLARED20  
CSCLARED04  
CSCORAL10  
CSCORAL20  
CSCORAL04  
CSDEEPOC04  
CSDEEPOC10  
CSDEEPOC20  
CSDUNE10  
CSDUNE20  
CSDUNE04  
CSEARLGR10  
CSEARLGR20  
CSEARLGR04  
CSGC10  
CSGC20  
CSGC04  
CSGUNM10

# Safety Data Sheet



PAVECOAT GUNMETAL 20LT	CSGUNM20
PAVECOAT GUNMETAL 4LT	CSGUNM04
PAVECOAT HEADLAND 10LT	CSHEADLAND10
PAVECOAT HEADLAND 20LT	CSHEADLAND20
PAVECOAT HEADLAND 4LT	CSHEADLAND04
PAVECOAT HOMESTEAD 10LT	CSCBHS10
PAVECOAT HOMESTEAD 20LT	CSCBHS20
PAVECOAT HOMESTEAD 4LT	CSCBHS04
PAVECOAT INDIAN RED 10LT	CSINDRED10
PAVECOAT INDIAN RED 20LT	CSINDRED20
PAVECOAT INDIAN RED 4LT	CSINDRED04
PAVECOAT IRONSTONE 10LT	CSIRONSTONE10
PAVECOAT IRONSTONE 20LT	CSIRONSTONE20
PAVECOAT IRONSTONE 4LT	CSIRONSTONE04
PAVECOAT JASPER 10LT	CSJASP10
PAVECOAT JASPER 20LT	CSJASP20
PAVECOAT JASPER 4LT	CSJASP04
PAVECOAT LIGHT GREY 10LT	CSLG10
PAVECOAT LIGHT GREY 20LT	CSLG20
PAVECOAT LIGHT GREY 4LT	CSLG04
PAVECOAT MANOR RED 10LT	CSMANORRED10
PAVECOAT MANOR RED 20LT	CSMANORRED20
PAVECOAT MANOR RED 4LT	CSMANORRED04
PAVECOAT MERINO 10LT	CSCBMERINO10
PAVECOAT MERINO 20LT	CSCBMERINO20
PAVECOAT MERINO 4LT	CSCBMERINO04
PAVECOAT MID BRUNSWICK GREEN 10LT	CSMBG10
PAVECOAT MID BRUNSWICK GREEN 20LT	CSMBG20
PAVECOAT MID BRUNSWICK GREEN 4LT	CSMBG04
PAVECOAT MIDNIGHT 10LT	CSMIDNIGHT10
PAVECOAT MIDNIGHT 20LT	CSMIDNIGHT20
PAVECOAT MIDNIGHT 4LT	CSMIDNIGHT04
PAVECOAT MISCELLANEOUS COLOUR 10LT	CSCOL10
PAVECOAT MISCELLANEOUS COLOUR 20LT	CSCOL20
PAVECOAT MISCELLANEOUS COLOUR 4LT	CSCOL04
PAVECOAT MISSION BROWN 10LT	CSMISSBWN10
PAVECOAT MISSION BROWN 20LT	CSMISSBWN20
PAVECOAT MISSION BROWN 4LT	CSMISSBWN04
PAVECOAT MIST GREEN 10L	CSCBMIST10
PAVECOAT MIST GREEN 20L	CSCBMIST20
PAVECOAT MIST GREEN 4LT	CSCBMIST04
PAVECOAT MOUNTAIN BL10L	CSCBMTBLUE10
PAVECOAT MOUNTAIN BL20L	CSCBMTBLUE20
PAVECOAT MOUNTAIN BL4LT	CSCBMTBLUE04
PAVECOAT OXIDE RED 10LT	CSRUST22210
PAVECOAT OXIDE RED 20LT	CSRUST22220
PAVECOAT OXIDE RED 4LT	CSRUST22204
PAVECOAT PALE EUCALYPT 10LT	CSPALEEUCA10
PAVECOAT PALE EUCALYPT 20LT	CSPALEEUCA20
PAVECOAT PALE EUCALYPT 4LT	CSPALEEUCA04
PAVECOAT PAPERBARK 10LT	CSPAPERBARK10
PAVECOAT PAPERBARK 20LT	CSPAPERBARK20
PAVECOAT PAPERBARK 4LT	CSPAPERBARK04
PAVECOAT RIVERGUM 10LT	CSCBRIV10
PAVECOAT RIVERGUM 20LT	CSCBRIV20
PAVECOAT RIVERGUM 4LT	CSCBRIV04
PAVECOAT SADDLE BROWN 10LT	CSTAN61010
PAVECOAT SADDLE BROWN 20LT	CSTAN61020
PAVECOAT SADDLE BROWN 4LT	CSTAN61004
PAVECOAT SAFETY YELLOW 10LT	CSSY10
PAVECOAT SAFETY YELLOW 20LT	CSSY20
PAVECOAT SAFETY YELLOW 4LT	CSSY04

# Safety Data Sheet



PAVECOAT SAHARA 10LT  
PAVECOAT SAHARA 20LT  
PAVECOAT SAHARA 4LT  
PAVECOAT SALTBUSH 10LT  
PAVECOAT SALTBUSH 20LT  
PAVECOAT SALTBUSH 4LT  
PAVECOAT SAMPLE C/MATCH 500M  
PAVECOAT SANDSTONE 10LT  
PAVECOAT SANDSTONE 20LT  
PAVECOAT SANDSTONE 4LT  
PAVECOAT SHALE GREY 10LT  
PAVECOAT SHALE GREY 20LT  
PAVECOAT SHALE GREY 4LT  
PAVECOAT SIENNA 10LT  
PAVECOAT SIENNA 20LT  
PAVECOAT SIENNA 4LT  
PAVECOAT SIGNAL RED 10LT  
PAVECOAT SIGNAL RED 20LT  
PAVECOAT SIGNAL RED 4LT  
PAVECOAT SLATE GREY 10L  
PAVECOAT SLATE GREY 20L  
PAVECOAT SLATE GREY 4LT  
PAVECOAT SUNSET 10LT  
PAVECOAT SUNSET 20LT  
PAVECOAT SUNSET 4LT  
PAVECOAT SURMIST 10LT  
PAVECOAT SURMIST 20LT  
PAVECOAT SURMIST 4LT  
PAVECOAT TERRACOTTA 10LT  
PAVECOAT TERRACOTTA 20LT  
PAVECOAT TERRACOTTA 4LT  
PAVECOAT WHEAT 10LT  
PAVECOAT WHEAT 20LT  
PAVECOAT WHEAT 4LT  
PAVECOAT WILDERNESS 10LT  
PAVECOAT WILDERNESS 20LT  
PAVECOAT WILDERNESS 4LT  
PAVECOAT WOODLAND GREY 10LT  
PAVECOAT WOODLAND GREY 20LT  
PAVECOAT WOODLAND GREY 4LT

CSSAHARA10  
CSSAHARA20  
CSSAHARA04  
CSCBSALT10  
CSCBSALT20  
CSCBSALT04  
CSSAMCM500ML  
CSSS10  
CSSS20  
CSSS04  
CSSHGREY10  
CSSHGREY20  
CSSHGREY04  
CSSIENNA10  
CSSIENNA20  
CSSIENNA04  
CSSR10  
CSSR20  
CSSR04  
CSCBSLATEGR10  
CSCBSLATEGR20  
CSCBSLATEGR04  
CSRED11010  
CSRED11020  
CSRED11004  
CSSURF10  
CSSURF20  
CSSURF04  
CSTC10  
CSTC20  
CSTC04  
CSCBWHEAT10  
CSCBWHEAT20  
CSCBWHEAT04  
CSWILDERN10  
CSWILDERN20  
CSWILDERN04  
CSWOODLGR10  
CSWOODLGR20  
CSWOODLGR04

**Recommended use:** CONCRETE SEALER

**Supplier:** Nutech Paint Pty Ltd  
**ABN:** 94 242 116 396  
**Street Address:** 4 Keppler Circuit  
Seaford VIC 3198  
Australia  
**Telephone:** 03 9770-3000  
**Facsimile:** 03 9775-1680

**Emergency Telephone number:** 03 9770-3000 (7:45 am-4:30 pm; Mon-Fri, AEST)

## 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.

# Safety Data Sheet



## Signal Word

Warning

## Hazard Classifications

Flammable Liquids - Category 3

Acute Toxicity - Dermal - Category 4

Acute Toxicity - Inhalation - Category 4

Skin Corrosion/Irritation - Category 2

Specific Target Organ Toxicity (Single Exposure) - Category 3 Narcotic Effects

Chronic Hazard to the Aquatic Environment - Category 3

## Hazard Statements

- H226 Flammable liquid and vapour.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

## Prevention Precautionary Statements

- P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust, fume, gas, mist, vapours or spray..  
P264 Wash hands, face and all exposed skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

## Response Precautionary Statements

- P101 If medical advice is needed, have product container or label at hand.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P362 Take off contaminated clothing and wash before reuse.  
P363 Wash contaminated clothing before reuse.  
P370+P378 In case of fire: Use (insert appropriate media) for extinction.

## Storage Precautionary Statements

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

## Disposal Precautionary Statement

- P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

# Safety Data Sheet



Poison Schedule: S6. Poison

## DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

### 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Mineral turpentine		1 - 10 %
Solvent naphtha, petroleum, light aromatic	64742-95-6	< 1 %
Xylene	1330-20-7	> 60 %
Ingredients determined to be Non-Hazardous		Balance

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

**Skin Contact:** This material, or a component of the material, can be absorbed through the skin with resultant toxic effects. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**Notes to physician:** Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

**Hazchem Code:** •3Y

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open

# Safety Data Sheet



flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

### LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

**Dangerous Goods – Initial Emergency Response Guide No: 14**

## 7. HANDLING AND STORAGE

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison Schedule 6 (Poison) and must be stored, maintained and used in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**National occupational exposure limits:**

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Mineral turpentine	-	480	-	-	-
Xylene	80	350	150	655	-

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

# Safety Data Sheet



These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Base Units:</b>	Litres
<b>Form:</b>	Viscous Liquid
<b>Colour:</b>	Coloured
<b>Odour:</b>	Distinct Aromatic Hydrocarbon odour
<b>Solubility:</b>	Insoluble in Water
<b>Solubility in water:</b>	0.175 grams per Litre
<b>Specific Gravity (20 °C):</b>	0.95 - 0.97
<b>Relative Vapour Density (air=1):</b>	3.7
<b>Vapour Pressure (20 °C):</b>	0.8-1.2 kPa @ 20°C
<b>Flash Point (°C):</b>	23-27
<b>Flammability Limits (%):</b>	1.0 - 7.1
<b>Autoignition Temperature (°C):</b>	432 - 530
<b>Boiling Point/Range (°C):</b>	136 - 191
<b>pH:</b>	N/APP
<b>Viscosity:</b>	35 - 45 seconds (B4 cup)
<b>Evaporation Rate (n-Butyl acetate=1):</b>	0.76
<b>Total VOC (g/Litre):</b>	68 - 70%

(Typical values only - consult specification sheet)  
N Av = Not available, N App = Not applicable

## 10. STABILITY AND REACTIVITY

# Safety Data Sheet



**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

**Hazardous reactions:** No known hazardous reactions.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Harmful if inhaled. Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Skin contact:** Harmful in contact with skin. Can be absorbed through the skin with resultant toxic effects. Contact with skin will result in irritation.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** May be an eye irritant.

### Acute toxicity

**Inhalation:** This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): 10 - 20 mg/L

**Skin contact:** This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): 1,000 - 2,000 mg/Kg

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

**Aspiration hazard:** This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

### Chronic Toxicity

**Mutagenicity:** This material has been classified as non-hazardous.

**Carcinogenicity:** This material has been classified as non-hazardous.

**Reproductive toxicity (including via lactation):** This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as non-hazardous.



# Safety Data Sheet



## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as a Category Chronic 3 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 10 - 100 mg/L, where the substance is not rapidly degradable and/or BCF  $\geq$  500 and/or log  $K_{ow} \geq$  4.

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III  
**Hazchem Code:** •3Y  
**Emergency Response Guide No:** 14

**Proper Shipping Name:** PAINT RELATED MATERIAL

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime



# Safety Data Sheet

Dangerous Goods Code.



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III  
**Proper Shipping Name:** PAINT RELATED MATERIAL

## AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III  
**Proper Shipping Name:** PAINT RELATED MATERIAL

## 15. REGULATORY INFORMATION

### This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).
- All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

**HSNO Group Standard:** HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard 2006

## 16. OTHER INFORMATION

Reason for issue: First issue

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.