



# Technical Data Sheet

## AquaStop Silicon Sealer

<b>Product Description</b>	<p><b>AquaStop Silicon Sealer</b> is a deep penetrating, water-based sealer for porous concrete, masonry and terracotta building materials.</p> <p><b>AquaStop Silicon Sealer</b> is designed to impart water repellence to porous substrates, producing a water beading effect within a few hours.</p>
<b>Aqua Stop Silicon Sealer Features:</b>	<ul style="list-style-type: none"><li>• Extremely high alkali resistance</li><li>• Suitable for application to slightly damp substrates</li><li>• Matt finish</li><li>• Non-yellowing</li><li>• Does not affect surface colour or texture</li><li>• Fast drying</li><li>• Rapid development of water resistance</li><li>• Low VOC</li></ul>
<b>Safety Precautions</b>	<p>Observe all Occupation Health and Safety (OH&amp;S) precautions.</p> <p>Refer to the relevant Safety Data Sheets (SDS) for product safety related information.</p> <p>For further information and support:</p> <p><b>Nutech Paint 03 9770 3000</b></p> <p><a href="http://www.nutechpaint.com.au">www.nutechpaint.com.au</a></p>
<b>Provisions:</b>	<p>Protect all glass from AquaStop Silicon Sealer</p> <p>DO NOT allow product to pool, remove excess product before drying as this will leave a milky appearance and can not be removed.</p>
<b>Chemical Type:</b>	Silicon emulsion
<b>Product Attributes</b>	<p>pH: 9.0 - 10.0</p> <p>Total VOC (g/Litre): 0%</p> <p>Solubility: Water</p> <p>Minimum Film Forming Temperature N/A</p>
<b>Typical Applications</b>	<p>Typical projects include:</p> <p>Domestic &amp; Multi Density Residential, Industrial, Commercial areas where natural stone protection is required.</p>
<b>Appearance</b>	Clear, slightly cloudy liquid
<b>Coverage / Spread Rates</b>	<p>2 m<sup>2</sup>/L - 10m<sup>2</sup>/L</p> <p>Actual coverage rates may vary depending on the type of substrate, texture and porosity, with higher coverage rates expected on non-porous substrates.</p>
<b>Packaging</b>	4L, 10L, 20L
<b>Shelf life</b>	6 months
<b>Storage</b>	<p>The container must be stored at temperatures not exceeding 25°C. Protect from direct sunlight.</p> <p>Containers must be sealed airtight. <b>AquaStop Silicon Sealer</b> will react with atmospheric humidity.</p>
<b>Substrate Recommendations</b>	Concrete, terracotta floor and roof tiles, mineral plaster, cement sheet, limestone, sandstone, brick masonry, rendered surfaces. (Not suitable for plaster of paris)



<b>Note:</b>	DO NOT apply the <b>AquaStop Silicon Sealer</b> late in the day as the risk of surface damage caused by dew and condensation increases.
<b>Mixing/ Thinning</b>	<b>Prior to Commencement:</b> Stir thoroughly prior to use. No thinning required
<b>Test Patch</b>	It is essential that you test on natural stone and pavers prior to use. <b>AquaStop Silicon Sealer</b> may affect different brands and batches of pavers greatly. Individual jobs should be thoroughly tested before sealing whole areas. A random selection of pavers on every specific job should be individually tested to ensure the sealed appearance of the pavers is consistent and satisfactory.
<b>Substrate note:</b>	All surfaces must be clean and in sound condition. Remove all oil, dirt, grease, and contamination. Application to slightly damp surfaces is possible.
<b>Application</b>	Brush, Roller, Spray, Broom
<b>Procedure:</b>	The solution should be applied to saturation without pressure. Observing recoat times, 3 - 4 coats are sufficient Remove excess product and do not allow to pool on the surface.
<b>Drying Time</b>	@ 25°C ambient conditions 50% relative humidity
<b>Touch</b>	30 minutes
<b>Recoat</b>	The surface should be dry to touch or dry enough to walk on prior to recoating.
<b>Hard Cure</b>	24 hours
<b>Clean Up</b>	Protecting Our Environment is important to Nutech Paints: Clean up with clean fresh water. Do not pour leftover paint down drains or in rubbish bins. Unwanted paint should be kept in a sealed container and then disposed of via special waste collection services. Dispose of empty paint containers in accordance with local authority's guidelines. Always check with your local council first.
<b>First Aid</b>	<b>SEEK IMMEDIATE MEDICAL ATTENTION.</b> Refer to the appropriate <b>Nutech Safety Data Sheet</b> (SDS) for further information. For medical emergencies only, call: 000 <ul style="list-style-type: none"><li>• In case of eye contact, flush thoroughly with water for at least 15 minutes</li><li>• In case of skin contact, wash affected areas with soap and water</li><li>• Remove and wash contaminated clothing</li><li>• If inhalation causes physical discomfort, remove to fresh air</li><li>• If discomfort persists, or any breathing difficulty occurs or if swallowed, seek medical advice</li></ul>



**Nutech Paint**  
For a perfect finish!

---

<b>Warranty</b>	<p>Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.</p> <p>Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty. Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages.</p> <p>Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.</p> <p>Limitation</p>
<b>Limitation of Liability</b>	<p>Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.</p>
<b>Disclaimer</b>	<p>The information given on this data sheet is based on many years' experience and is correct to the best of our knowledge. However, since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.'</p> <p>The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</p>

---



**Nutech Paint**  
For a perfect finish!

# Nutech

---

**Nutech Paint  
PTY LTD**

☎ 03 9770 3000

✉ [sales@nutech.com.au](mailto:sales@nutech.com.au)

[www.nutechpaint.com.au](http://www.nutechpaint.com.au)