Date of Issue: JUNE 2014

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	Nu-EcoSafe-Strip Architectural	
Other Name(s):	Coating Remover	
Recommended Use:	Coating Remover	
Supplier: ABN: Street Address:	Nutech Paint Pty L 94 242 116 396 4 Keppler Circuit Seaford, Victoria, A	
Telephone Number: Fax Number: Website:	+61 3 9770 3000 +61 3 9775 1680 www.nutech.com.a	au
Emergency Numbers:	+61 3 9770 3000 000 131 126	7.45am-4.30pm Mon-Fri Police, Fire and Ambulance For poisons advice contact a Poisons Information Centre (New Zealand 0800 764 7660) or a Doctor at once.

2. HAZARDS IDENTIFICATION

Main Hazards:Harmful by inhalation and if swallowed. Harmful to aquatic organisms,
may cause long term adverse affects in the aquatic environment.

Other Hazards:

Irritating to skin, Irritating to eyes.

3. COMPOSITION / INFORMATION ON INGREDIENTS


100-51-6	30-50
64742-47-8	5-10
102-71-6	1-3

4. FIRST AID MEASURES (SYMPTOMS)

Skin Contact:	There may be mild irritation at the site of contact.
Eye Contact:	There may be irritation, redness or discomfort.
Ingestion:	There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.
Inhalation	Absorption through the lungs can occur causing symptoms similar to those of ingestion.

4. FIRST AID MEASURES (AC	4. FIRST AID MEASURES (ACTIONS)	
Skin Contact:	Wash immediately with plenty of soap and water.	
Eye Contact:	Bathe the eye with running water for 15 minutes.	







Ingestion:Wash out the mouth with water. Do not induce vomiting. If
conscious, give half a litre of water to drink immediately. Consult
a doctor.InhalationRemove casualty from exposure ensuring one's own safety
whilst doing so. Consult a doctor.

5. FIRE FIGHTING MEASURES

Extinguishing Media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
Exposure Hazards:	In combustion emits Toxic fumes.
Protection of Fire fighters:	Wear self – contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Refer to section 8 of MSDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak side up to prevent the escape of liquid.
Environmental Precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.
Clean up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
7. HANDLING AND STORAGE	
Handling Requirements:	Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.
Storage Conditions:	Store in a cool well ventilated area. Keep container tightly closed.
Suitable Packaging:	Must only be kept in original packaging.

8. PERSONAL PROTECTION / EXPOSURE CONTROL

Protective Equipment:



Hazardous Ingredients:

Engineering Measures:







TRIETHANOLAMINE WEL (8 hr TWA): 5mg/m3

Ensure there is sufficient ventilation of the area.



Respiratory Protection:	Gas/Vapour filter, type A: organic vapours (EN141). Self contained breathing apparatus must be available in case of emergency.
Hand Protection:	Rubber gloves. Neoprene gloves.
Eye Protection:	Safety glasses, Safety goggles. Ensure eye bath is to hand.
Skin Protection:	Protective clothing. Rubber apron. Rubber boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Emulsion
Colour:	Yellow
Odour:	Barely perceptible odour
Evaporation Rate:	Slow
Solubility in Water:	Soluble
Viscosity:	Viscous
Flash Point °C	>100 (PMCC)
Relative density:	1.01
pH:	10.0-11.0
VOC g/l:	73.2
10 STABILITY AND REACTIVITY	

10. STABILITY AND REACTIVITY

Stability:	Stable under normal use conditions.
Conditions to Avoid:	Heat.
Incompatible Materials:	Strong Oxidising agents. Strong Acids.
Hazardous Decomposition	In combustion emits toxic fumes of Carbon Dioxide/ Carbon Monoxide. In combustion emits toxic fumes of Nitrogen Oxide.

11. TOXICOLOGICAL INFORMATION

Hazardous Ingredients :	BENZYL ALCOHOL	
	IVN RAT LD50 53 mg/kg	
	ORL MUS LD50 1360 mg/kg	
	ORL RAT LD50 1230 mg/kg	
	TRIETHANOLMINE	
	ORL RAT LD50 8000 mg/kg	
	ORL RBT LD50 2200 mg/kg	
	SKN RAT LD50> 16 ml/kg	
	SKN RBT LD50> 20 ml/kg	



Chronic Toxicity:	Danger of serious damage to health by prolonged exposure through Inhalation. Danger of serious damage to health by prolonged exposure if swallowed. Danger of serious damage to health by prolonged exposure in contact with skin.
Routes of Exposure:	Refer to section 4 of MSDS for routes of exposure and corresponding Symptoms.
12. ECOLOGICAL INFORMATION	
Mobility:	Readily absorbed into soil.
Persistence and degradability:	Biodegradable.
Bioaccumulative Potential:	No bioaccumulation potential.
Other adverse affects:	Negligible ecotoxicity.
13. DISPOSAL INFORMATION	
Disposal Operations:	Collect lifted paint and place it in plastic containers, Add Un-ecosafe-strip Ecozorb to absorb the remaining liquids and dispose of in accordance with local government regulations.
Disposal of Packaging:	Clean with water. Treat the cleaning water following the above method for waste product. Dispose of as normal industrial waste.
NB:	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. **TRANSPORT INFORMATION**

ADR / RID

UN no: Not Classified

IMDG / IMO

UN no: Not Classified

IATA / ICAO

UN no: Not Classified

15. **REGULATORY INFORMATION**



Harmful

Safety Data Sheet

SDS: Nu-EcoSafe-Strip Architectural



Date of Issue: JUNE 2014

Risk Phrase(s):		
	R20/22:	Harmful by inhalation and if swallowed.
	R52/53:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety Phrase(s):		
	S36/37:	Wear suitable protective clothing and suitable gloves.
	S53:	Avoid exposure – obtain special instructions before use.
	S61:	Avoid release to the environment. Refer to special instructions / safety data sheets.
Haz. Ingredients (La	abel):	BENZYL ALCOHOL; AROMATIC SOLVENT.
Note:		The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

MSDS: : Nu-EcoSafe-Strip Architectural Paint Stripper

16. OTHER INFORMATION

Risk Phrases used in s.3:	R20/22: Harmful by inhalation and if swallowed.
	R65: Harmful: may cause lung damage if swallowed.
	R51/53: toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R36/37/38: Irritating to eyes, respiratory system and skin.
Legal Disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Nutech Paint Pty Ltd has prepared this Material Safety Data Sheet.



NUTECH PAINT PTY LTD

Tel: +61 3 9770 3000 Fax: +61 3 9775 1680 Website: www.nutech.com.au Email: sales@nutech.com.au Page 6 of 6

NUTECH PAINT THOMASTOWN 216 Settlement Road Thomastown Victoria Australia 3074 Tel: +61 3 9465 5111 Fax: +61 3 9465 5222 NUTECH PAINT SYDNEY 18 South Street Rydalmere NSW Australia 2116 Tel: +61 2 9638 7089 Fax: +61 2 9638 7911 NUTECH PAINT BRISBANE 3325 Pacific Highway Slacks Creek QLD Australia 4127 Tel: +61 7 3808 74222 Fax: +61 7 3290 2366 NUTECH PAINT WESTERN AUSTRALIA 41 Jade Street Maddington WA Australia 6989 Tel: +61 8 9459 1139 Fax: +61 8 9459 1171 NUTECH PAINT UK Tel: +44 (0)141 945 2005



Date of Issue: November 2012