



Fine Anti-Slip for Two Pack Colour Applications

Description

Nutech Fine Anti-Slip for coloured Two Pack Epic PolyCryl and Two Pack Epic Epoxy coatings provides excellent slip resistance under both wet and dry conditions and is also suitable on surfaces with an incline. The product will produce a Fine Anti-Slip finish increasing the friction of the surface and in most cases eliminating slip potential.

The product is suitable for use with coloured Epic Epoxy and Epic PolyCryl floor coating systems. The product is only suitable for coloured applications because if used on a clear coating the coating will become opaque and no longer be clear.

Typical Properties

Appearance:	Fine White Powder appearance and texture
Solubility In Water:	Nil
Recommended Application Rate:	1kg / 2-5 square metres cast onto the surface

Must be Top Coated to Lock Anti-Slip into coating.

Typical Uses

Sealed concrete surfaces become slippery, particularly when wet, making conditions less safe for pedestrians and vehicles, include Bicycles, Cars and Fork Lifts.

Nutech Fine Anti-Slip imparts a Fine Anti-Slip finish and a slight texture to the surface of floor sealing systems to improve safety under wet and dry conditions.

Typical Projects

<u>SUITABLE SUBSTRATES</u>	<u>TYPICAL PROJECTS</u>
<ul style="list-style-type: none">• Concrete	<ul style="list-style-type: none">• Around Swimming Pools/Wet Areas
<ul style="list-style-type: none">• Fibreglass/Boating	<ul style="list-style-type: none">• Factory Loading Docks
<ul style="list-style-type: none">• Decking	<ul style="list-style-type: none">• Stairs
	<ul style="list-style-type: none">• Entrance Foyers
	<ul style="list-style-type: none">• Public Pedestrian Areas
	<ul style="list-style-type: none">• Vehicle Areas



Fine Anti-Slip for Two Pack Colour Applications

Packaging: 5kg (4lt Pail)
20kg (Metal Pail)

Applications & Features

Application Method

Nutech Fine Anti-Slip cannot be added to the sealer it must be cast onto the surface of the two pack product.

To apply:

- First mix the two pack product according to the manufacturer's instructions
- Apply the first coat usually diluted with the appropriate Thinners.
- Apply to small sections at a time and cast the Fine Anti-Slip onto the wet surface of the two pack product either by hand or mechanical means trying to achieve an even finish.
- Use this method to apply to all areas that require the Anti-Slip product then allow the coating to dry.
- Prior to recoating, the excess Fine Anti-Slip should be removed either by broom, blower or vacuum cleaner.
- When applying the second coat make sure all the Fine Anti-Slip is coated and therefore locked into the coating, more two pack product will be required for the second coat as the Fine Anti-Slip will increase the surface area by 20 to 30 percent.

Nutech Concrete Range

Nutech Paint
Application Instructions & Guidelines
Nutech Concrete Range of Products



DISCLAIMER:

Warranty and Limitation of liability:

Warranty

Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.

Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty.

Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages.

Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability

Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.

Important Note:

The information given on this data sheet is based on many years experience and is correct to the best of our knowledge. However since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in