

## Technical Data Sheet

# AmbientPro – Warm Weather Solution

**Description:** **AmbientPro – Warm Weather Solution** is a water based solution developed as a post addition to improve application properties of Graphenstone mineral based primers and top coats in warmer conditions.

**Features:**

- Developed specifically for mineral and graphene based primers top and coats
- Simple post addition
- Improves flow
- Improves holdout and wet edge

**Safety** Observe all Occupation Health and Safety (OH&S) precautions.

**Precautions:** Refer to the relevant Safety Data Sheets (SDS) for product safety related information.

For further information and support: **Nutech Paint 03 9770 3000**

<https://nutechpaint.com.au/>

**Usage warnings:**

- Protect skin and eyes
- Apply with good ventilation, do not inhale product
- Keep out of reach of children

**Provisions:** DO NOT USE THIS PRODUCT IN COOL AMBIENT CONDITIONS BELOW 20°C  
Wherever possible, observe the recommended ambient conditions for application outlined in the relevant Graphenstone product TDS.

**Chemical Type:** Diol and water dispersion

**Product** pH: 7

**Attributes:** Total Volatile Organic Compounds (TVOC):

Solubility: In Water

Minimum Film Forming Temperature: N/A

**Typical Applications:** For use in Graphenstone lime and mineral silicate based primers and top coats

**Recommended Substrates:** N/A - Refer to the relevant Graphenstone lime or mineral silicate based primer or top coat TDS for further details

**Coverage / Spread Rate:** N/A - Refer to the relevant Graphenstone lime or mineral silicate based primer or top coat TDS for further details

**Test Patch:** After addition, conduct a small test patch in an inconspicuous area to ensure adequate product performance, substrate porosity and provide an indication of the time required to complete project.

**Packaging:** 1Lt.

**Storage:** Cool, dry location. Keep from freezing and avoid contact with direct sunlight and heat.

**Shelf life:** Stored 12 months @ 25°C

**Preparation:** Ensure a clean dust free environment and observe addition requirements per pack size, prior to addition.

**Mixing/** Recommended Warm Weather Solution additions;

**Thinning:** **5L Pail – 250ml**

**10L Pail – 500ml**

**Directions:** Add directly into a full pail of Graphenstone primer or top coat in the recommended dose outlined in this TDS.

After addition, stir thoroughly, avoiding harsh agitation and bubbles

**Drying Times:** Dry times will be increased.  
Refer to the relevant primer or top coat TDS for general dry time details allowing an extra 10 – 20 minutes prior to recoat.

**Note:** Allow extra dry time in high humidity.

---

**Clean Up:** Protecting Our Environment is important to Nutech Paint:  
Clean up with clean warm water. Do not pour leftover paint down drains or in rubbish bins. Unwanted paint should be kept in a sealed container and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Dispose of empty paint containers in accordance with local authority's guidelines. Always check with your local council first.

---

**First Aid:** **SEEK IMMEDIATE MEDICAL ATTENTION.** Refer to the appropriate *Nutech Safety Data Sheet* (SDS) for further information. For medical emergencies only, call: 000

- In case of eye contact, flush thoroughly with water for at least 15 minutes
- In case of skin contact, wash affected areas with soap and water
- Remove and wash contaminated clothing
- If inhalation causes physical discomfort, remove to fresh air
- If discomfort persists, or any breathing difficulty occurs or if swallowed seek medical advice

---

**Warranty:** Nutech Paint warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the non-conforming products. Any claim under this Warranty must be made by Buyer to Nutech Paint in writing within five days (5) of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech Paint of such non-conformance as required herein shall bar Buyer from recovery under this Warranty. Nutech Paint makes no other warranties concerning the product. No other warranties, whether express, implied or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech Paint be liable for consequential or incidental damages.

Our goods come with guarantees that cannot be excluded under Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

---

**Limitation of Liability:** Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.

---

**Disclaimer:** The information provided in this data sheet is based on many years' experience and is correct to the best of our knowledge. However, since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact Nutech Paint. As this information is of a general nature, we cannot assume any responsibility in individual cases.

The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Any recommendation or suggestion relating to the use of the products made by Nutech Paint, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by buyers having requisite skill and know-how in the industry and therefore it is for buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

---



**Nutech Paint**  
For a perfect finish!

[www.nutechpaints.com.au](http://www.nutechpaints.com.au)

2-4 Keppler Circuit, Seaford, Victoria.

+613 9770 3000



---

**GRAPHENSTONE®**

---

**PAINTS FOR THE**  
*green*  
**GENERATION**