

Safety Data Sheet

HiTEC® 22520 Performance Additive

SDS no.

H22520

Section 1. Identification

: HiTEC® 22520 Performance Additive **Product identifier**

: Petrochemical industry: Lubricating Oil Additive. **Product use**

: 19 October 2022 **Date of issue/Revisions**

In case of emergency - Chemical

+1-703-527-3887 (International)

+65-3158-1349 (Asia Pacific)

+61-290372994 (Australia)

4001-204937 (China)

+81-345209637 (Japan)

00-308-13-2549 (South Korea)

+1-703-741-5979 (Spanish language)

+44-870-8200418 (UK)

1-800-424-9300 (ÙS & Canada)

Manufacturer / Supplier

Afton Chemical Asia Pte. Ltd. 103 Penang Road #09-01 Visioncrest Commercial Singapore 238467

Telephone number: +65 6732 0822

Fax: +65 6737 4123

Afton Chemical (Suzhou) Co., Ltd. No. 26 Pingsheng Road, Suzhou Industrial Park, Suzhou

215126 China

Tel: +86-512-62605099

Afton Chemical (Beijing) Co., Ltd. Room 707 China World Office 1 No. 1 Jian Guo Men Wai Avenue

Beijing 100004 China

Telephone number: +86 10 6535 0000

Afton Chemical Japan Corporation Hirakawacho Mori Tower 7F, 2-16-1 Hirakawacho, Chiyoda-ku Tokyo Japan

Afton Chemical Asia Pacific Company Level 12, 20 Berry Street North Sydney, NSW 2060 Australia

Telephone number: +61 299785800

Business Hours: 9:00am - 5:00pm

Afton Chemical Korea Co., Ltd. 511 Yeongdong-daero, Gangnam-gu, 27th Floor Trade Tower Seoul City 06164 Republic of Korea Telephone number: +82- 2 -2191-4000

Afton Chemical Corporation 500 Spring St. Richmond, VA 23219 USA

Non-Emergency Telephone: +1-804-788-5800

: 10/19/2022 : 4/7/2022 Version: 1.03 Date of issue/Date of revision Date of previous issue

Section 2. Hazards identification

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 3 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

GHS label elements

Hazard pictograms :

Signal word : Warning

Hazard statements : Causes mild skin irritation.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention: Avoid release to the environment.

Response : If skin irritation occurs: Get medical advice or attention.

Storage : Store in a well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do not result in classification

: When heated above 90°C (194°F), thermal decomposition may occur producing CO,

CO2, phosphorus oxides, metal oxide/ oxides, hydrogen sulfide.

Please note some GHS hazard classifications listed above may not be applicable in your country or region and are shown for informational purposes only.

For other GHS hazard classifications not listed above, the classification is not applicable in your region.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	CAS number	%	GHS Classification	Тур
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	≥10 - ≤15	Not classified.	[2]
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)	2215-35-2	≥5 - ≤10	ACUTE TOXICITY (oral) - Category 5 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	≥5 - ≤10	ASPIRATION HAZARD - Category 1	[1] [2]
Distillates (petroleum), solvent-refined	64741-88-4	≥5 - ≤10	Not classified.	[2]

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 2/2

Section 3. Composition/information on ingredients

heavy paraffinic				
bis(nonylphenyl)amine	36878-20-3	≥5 - ≤10	SKIN CORROSION/IRRITATION - Category 3	[1]
zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate)	4259-15-8		ACUTE TOXICITY (oral) - Category 5 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	[1]

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Please note some GHS hazard classifications listed above may not be applicable in your country or region and are shown for informational purposes only.

Type

- [1] Substance classified with a physical, health or environmental hazard
- [2] Substance with a workplace exposure limit

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If irritation persists, get medical attention.

Inhalation

: If inhaled, remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. If not breathing, give artificial respiration. If breathing is difficult, administer oxygen.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if adverse health effects persist or are severe. Wash clothing before reuse. Clean shoes thoroughly before reuse. Continue to rinse for at least 15 minutes.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

Section 4. First aid measures

as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: Causes mild skin irritation.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-

aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

: In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable

extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides sulfur oxides phosphorus oxides metal oxide/oxides Hydrogen sulphide

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 4/21

Section 5. Firefighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Take precautions to limit storage vessel surface temperature to below 121°C (250°F).

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 5/21

Section 7. Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

The following information is provided for health and safety purposes. Please refer to individual product specification documents for quality-related storage and handling. Preferred storage temperature is between ambient and 70°C.

Exposure to elevated temperatures will increase the rate of hydrogen sulfide (H2S) and mercaptan generation.

Temperatures above 90°C should be avoided unless an appropriate engineering review has been conducted on the process.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	Safe Work Australia (Australia, 12/2019). TWA: 5 mg/m³ 8 hours. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Safe Work Australia (Australia, 12/2019). TWA: 5 mg/m³ 8 hours. Form: Mist
Distillates (petroleum), solvent-refined heavy paraffinic	Safe Work Australia (Australia, 12/2019). TWA: 5 mg/m³ 8 hours. Form: Mist

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 6/21

Section 8. Exposure controls/personal protection

Hand protection

: Hand Protection: Wear chemical resistant gloves. Nitrile gloves of minimum thickness 0.4 mm have an expected breakthrough time of 480 minutes or less when in frequent contact with the product. Due to variable exposure conditions the user must consider that the practical use of a chemical-protective glove in practice may be much shorter than the permeation time above. Manufacturer's directions for use, especially about the minimum thickness and the minimum breakthrough time, must be observed. This information does not replace suitability tests by the end user since glove protection varies depending on the conditions under which the product is used.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Physical state : Liquid. [Viscous]

Colour : Brown. [Dark]
Odour : Petroleum-like

Odour threshold : Not available.

pH : Not available.

Melting point : Not available.

Boiling point : Not available.

Flash point : Closed cup: 130°C (266°F) [Pensky-Martens Minimum]

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper : Not available.

explosive (flammable)

limits

Vapour pressure : Not available.

Relative vapour density : Not available.

Vapour density : Not available.

Density : 0.977 g/cm³ [59°F (15°C)]

Relative density : Not available.

Solubility(ies) : Not available.

Partition coefficient: n- : Not applicable.

Partition coefficient: n-

octanol/water

. Not applicable

Auto-ignition

: Not available.

temperature

: Not available.

Decomposition temperature

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 7/21

HiTEC® 22520 Performance Additive In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific)

Section 9. Physical and chemical properties

Viscosity : Kinematic (40°C): 957 mm²/s (957 cSt) Minimum

67 cSt @ 100°C

Explosive properties : Not available. **Oxidising properties** : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Page: 8/21

Conditions to avoid : High temperatures, sparks, and open flames.

Incompatible materials: Strong oxidising and reducing agents.

Hazardous : Hydrogen sulphide

decomposition products

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient	Test	Result	Species	Dose	Exposure	Remarks
name						
Distillates (petroleum),	403 Acute	LC50 Inhalation	Rat	>5.53 mg/l	4 hours	Based on data
hydrotreated heavy paraffinic	Inhalation Toxicity	Dusts and mists				for a similar substance.
	402 Acute	LD50 Dermal	Rabbit	>5000 mg/kg	_	Based on data
	Dermal Toxicity			3. 3		for a similar
	404 A	L D50 0	D. 4	5000		substance.
	401 Acute Oral Toxicity	LD50 Oral	Rat	>5000 mg/kg	-	Based on data for a similar
	TOXICITY					substance.
zinc O,O,O',O'-tetrakis	403 Acute	LC50 Inhalation	Rat	>2 mg/l	1 hours	Based on data
(1,3-dimethylbutyl) bis	Inhalation	Vapour				for a similar
(phosphorodithioate)	Toxicity 402 Acute	LD50 Dermal	Rabbit	>25000 mg/kg	_	substance.
	Dermal Toxicity	LB00 Bonnar	Rabbit	20000 mg/kg		
	401 Acute Oral	LD50 Oral	Rat	2230 mg/kg	-	-
Distillator (notroloum)	Toxicity	LCEO Inhalation	Dot	> E E2 mg/l	1 hours	
Distillates (petroleum), solvent-dewaxed heavy	403 Acute Inhalation	LC50 Inhalation Vapour	Rat	>5.53 mg/l	4 hours	-
paraffinic	Toxicity	, apour				
·	402 Acute	LD50 Dermal	Rabbit	>5000 mg/kg	-	-

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 8/21

>5000 mg/kg - -
>5.53 mg/l 4 hours Based on data
for a similar
substance.
obit >2000 mg/kg - -
>5000 mg/kg - -
>2000 mg/kg - Based on data
for a similar
substance.
>5000 mg/kg - Based on data
for a similar
substance.
obit >5000 mg/kg
3100 mg/kg - -
>5.53 mg/l 4 hours Based on d for a similal substance. >5000 mg/kg

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient	Test	Species	Result	Remarks
name				
Distillates (petroleum), hydrotreated heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis (phosphorodithioate)	None available.	Rabbit	Eyes - Visible necrosis	Not H319 at <15%. On basis of test data. Not H318 at <20%. On basis of test data.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Irritant	Not H315 at <15%. On basis of test data.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
bis(nonylphenyl)amine	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Mild irritant	Based on data for a similar substance.
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Visible necrosis	Not H319 at <50%. On basis of test data. Not H318 at <80%. On basis of test data.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	-

Skin

: Causes mild skin irritation. Based on test data for this or similar products.

Eyes

: Non-irritating to the eyes. Based on test data for this or similar products.

Date of issue/Date of revision :10/19/2022 Date of previous issue :4/7/2022 Version :1.03 9/21

Respiratory

: Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Test	Route of exposure	Species	Result	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic zinc O,O,O',O'-tetrakis	406 Skin Sensitization 406 Skin	skin skin	Guinea pig Guinea pig	Not sensitizing Not	Based on data for a similar substance.
(1,3-dimethylbutyl) bis (phosphorodithioate) Distillates (petroleum), solvent-dewaxed heavy	Sensitization 406 Skin Sensitization	skin	Guinea pig	sensitizing Not sensitizing	Based on data for a similar substance.
paraffinic Distillates (petroleum), solvent-refined heavy	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
paraffinic bis(nonylphenyl)amine	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	-

Conclusion/Summary

Skin

: Based on available data, the classification criteria are not met.

Respiratory

: Based on available data, the classification criteria are not met.

Mutagenicity

Product/ingredient name	Test	Experiment	Result	Remarks
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
hydrotreated heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.
	476 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Cell Gene Mutation Test	Subject: Mammalian-Animal		similar substance.
	474 Mammalian	Experiment: In vivo	Negative	Based on data for a
	Erythrocyte Micronucleus Test	Subject: Mammalian-Animal		similar substance.
zinc O,O,O',O'-tetrakis	476 In vitro Mammalian	Experiment: In vitro	Positive	Based on data for a
(1,3-dimethylbutyl) bis (phosphorodithioate)	Cell Gene Mutation Test	Subject: Mammalian-Animal		similar substance. WOE does not support classification
	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
	Mutation Test	Subject: Bacteria		similar substance.
	474 Mammalian	Experiment: In vivo	Negative	Based on data for a
	Erythrocyte Micronucleus Test	Subject: Mammalian-Animal		similar substance.
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
solvent-dewaxed heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
i e	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
solvent-refined heavy	Mutation Test	Subject: Bacteria		similar substance.

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 10/21

paraffinic				
	473 In vitro Mammalian Chromosomal Aberration Test	Experiment: In vitro Subject: Mammalian-Animal	Negative	Based on data for a similar substance.
bis(nonylphenyl)amine	471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative	Based on data for a similar substance.
	473 In vitro Mammalian Chromosomal Aberration Test	Experiment: In vitro Subject: Mammalian-Animal	Negative	Based on data for a similar substance.
	478 Genetic Toxicology: Rodent Dominant Lethal Test	Experiment: In vitro Subject: Mammalian-Animal	Negative	Based on data for a similar substance.
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	None available.	Experiment: In vitro Subject: Mammalian-Animal	Positive	WOE does not support classification
	471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative	-
	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal	Negative	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

Product/ingredient	Test	Species	Exposure	Result	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/ingredient name	Test	Route of exposure	- p	Maternal toxicity	Fertility	Developmental toxin	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis (phosphorodithioate)	422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Dermal	Rat	Negative	Negative	Negative	Based on data for a similar substance.
	421 Reproduction/	Oral	Rat	Negative	Negative	Negative	Based on

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 11/21

HiTEC® 22520 Performance Additive

Page:

Section 11. Toxicological information

Developmental Toxicity Screening Test Distillates (petroleum), solvent-refined heavy paraffinic zinc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate) Developmental Toxicity Screening Test 421 Reproduction/ Developmental Toxicity Screening Test	Oral Oral	Rat Rat	Negative Negative	Negative Negative	Negative Negative	data for a similar substance. Based on data for a similar substance.
---	--------------	------------	----------------------	----------------------	----------------------	--

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Teratogenicity

Product/ingredient name	Test	Species	Result	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
bis(nonylphenyl)amine	414 Prenatal Developmental Toxicity Study	Rat	Negative - Oral	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Skin, Eyes, Ingestion, and Inhalation

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact : Causes mild skin irritation.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 12/21

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

effects

: Inhalation of oil mist or vapours at elevated temperatures may cause respiratory

irritation. Ingestion may cause gastrointestinal irritation and diarrhoea.

Potential delayed

effects

: Not available.

Long term exposure

Potential immediate

effects

: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the

skin.

Potential delayed

effects

: Not available.

Potential chronic health effects

Product/ingredient	Test	Species	Dose	Exposure	Result	Remarks
name						
Distillates (petroleum), hydrotreated heavy paraffinic	408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	125 mg/kg	-	Sub-chronic LOAEL Oral	Based on data for a similar substance.
	410 Řepeated Dose Dermal Toxicity: 21/28-day Study	Rabbit	1000 mg/kg	-	Sub-acute NOAEL Dermal	Based on data for a similar substance.
	411 Subchronic Dermal Toxicity: 90-day Study	Rat	30 mg/kg	-	Sub-chronic NOAEL Dermal	Based on data for a similar substance.
	None available.	Rat	0.15 mg/l	13 weeks	Sub-chronic NOAEL Inhalation Dusts and mists	Based on data for a similar substance.
	None available.	Rat	0.22 mg/l	4 weeks	Sub-chronic NOAEL Inhalation Dusts and mists	Based on data for a similar substance.
zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis (phosphorodithioate)	422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Rat	160 mg/kg	-	Sub-acute NOAEL Oral	Based on data for a similar substance.

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 13/21

Distillates (petroleum),	410 Repeated Dose	Rabbit	1000 mg/kg	-	Sub-acute	Based on data
solvent-dewaxed heavy	Dermal Toxicity:				NOAEL Dermal	for a similar
paraffinic	21/28-day Study					substance.
	None available.	Rat	0.05 mg/l	13 weeks	Sub-chronic NOAEL	-
					Inhalation	
					Vapour	
Distillates (petroleum),	410 Repeated Dose	Rabbit	1000 mg/kg	-	Sub-acute	Based on data
solvent-refined heavy	Dermal Toxicity:				NOAEL Dermal	
paraffinic	21/28-day Study					substance.
	None available.	Rat	0.15 mg/l	13 weeks	Sub-chronic	Based on data
					NOAEL Inhalation	for a similar substance.
					Vapour	Substance.
	None available.	Rat	0.22 mg/l	28 days	Sub-acute	Based on data
				•	NOAEL	for a similar
					Inhalation	substance.
					Vapour	
bis(nonylphenyl)amine	408 Repeated Dose	Rat	100 mg/kg	-	Sub-chronic	-
	90-Day Oral Toxicity Study in Rodents				LOAEL Oral	
zinc bis[O,O-bis(2-ethylhexyl)]	407 Repeated Dose	Rat	125 mg/kg	_	Sub-acute	_
bis(dithiophosphate)	28-day Oral Toxicity		1.20 1119/119		NOAEL Oral	
	Study in Rodents					

Conclusion/Summary

: Based on available data, the classification criteria are not met.

General

: No known significant effects or critical hazards.

Carcinogenicity

: No known significant effects or critical hazards.

Mutagenicity
Teratogenicity

No known significant effects or critical hazards.No known significant effects or critical hazards.

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

: No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEL 1000 mg/l	Fish - Oncorhynchus mykiss	14 days	QSAR result.

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 14/21

zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis	Acute EL50 24 mg/l	Algae - Desmodesmus subspicatus	72 hours	Based on data for a similar
(phosphorodithioate)	Acute EL50 23 mg/l	Daphnia - Daphnia magna	48 hours	substance. Based on data for a similar
	Acute EL50 >10000	Micro-organism	3 hours	substance. Based on data
	mg/l			for a similar substance.
	Acute LL50 4.5 mg/l	Fish - Oncorhynchus mykiss	96 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Algae - Desmodesmus subspicatus	72 hours	Based on data for a similar
	Chronic NOEL 0.4 mg/l	Daphnia - Daphnia magna	21 days	substance. Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
paraminic	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	substance. Based on data for a similar substance.
	Chronic NOEL 1000	Fish - Oncorhynchus mykiss	14 days	QSAR result.
Distillates (petroleum), solvent-refined heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
paramino	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEL 1000	Fish - Oncorhynchus mykiss	14 days	QSAR result.
bis(nonylphenyl)amine	Acute EL50 >100 mg/	Algae - Pseudokirchneriella subcapitata	72 hours	-
	Acute EL50 >100 mg/	Daphnia - Daphnia magna	48 hours	-
	Acute IC50 >100 mg/l	Micro-organism	3 hours	Based on data for a similar substance.
	Acute LL50 >100 mg/	Fish - Danio rerio	96 hours	Based on data for a similar
	Chronic EL10 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	substance.
	Chronic EL10 4.12	Crustaceans - Daphnia magna	21 days	-

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 15/21

	9			
	mg/l Fresh water Chronic NOEL 10 mg/l Fresh water	Fish - Danio rerio	34 days	-
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	Acute EL50 410 mg/l	Algae - Desmodesmus subspicatus	72 hours	-
	Acute EL50 75 mg/l	Daphnia - Daphnia magna	48 hours	-
	Acute EL50 380 mg/l	Micro-organism	16 hours	-
	Acute LL50 4.4 mg/l	Fish - Oncorhynchus mykiss	96 hours	-
	Chronic NOEL 220 mg/l	Algae - Desmodesmus subspicatus	72 hours	-
	Chronic NOEL 0.4	Daphnia - Daphnia magna	21 days	Based on data
	mg/l			for a similar substance.

Conclusion/Summary

: Harmful to aquatic life with long lasting effects.

Persistence and degradability

Product/ingredient	Test	Result	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis (phosphorodithioate)	OECD 301B Ready Biodegradability - CO2 Evolution Test	1.5 % - Not readily - 28 days	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
bis(nonylphenyl)amine	OECD 301C Ready Biodegradability - Modified MITI Test (I)	24 % - Not readily - 28 days	-
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	OECD 301D Ready Biodegradability - Closed Bottle Test	<5 % - Not readily - 27 days	-

Bioaccumulative potential

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 16/21

In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific)

Page:

Section 12. Ecological information

HiTEC® 22520 Performance Additive

Product/ingredient	LogPow	BCF	Potential
name			
Distillates (petroleum), solvent-refined heavy paraffinic	3.9 to 6	-	high
bis(nonylphenyl)amine zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	3.64 to 7.02 3.59	1730	high low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility
Hazardous to the ozone layer

Not available.Not applicable.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	ADG	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class (es)	-	-	-	-
14.4 Packing group	-	-	-	-

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 17/2

HiTEC® 22520 Performance Additive In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific) Page:

Section 14. Transport information

14.5
Environmental hazards

No. No. No.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Section 15. Regulatory information

China

List of Goods banned for Importing

None of the components are listed.

List of Goods banned for Exporting

None of the components are listed.

List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

Singapore

Singapore - hazardous chemicals under government control

Ingredient name	Status
Anionic surface active agent	Listed

Australia

Standard for the Uniform Scheduling of Medicines and Poisons

Not applicable.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Japan

Fire Service Law

Category	Substance name/Type	Danger category
Category IV	Class III petroleums	III

Industrial Safety and Health Act

Label Requirements and Chemicals Requiring Notification

Ingredient name	%
Mineral oil Molybdenum and its compounds	≥25 - ≤35 ≥0.30 - ≤0.50

Chemical Substances Control Law (CSCL)

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 18/21

HiTEC® 22520 Performance Additive

Page:

Section 15. Regulatory information

None of the components are listed.

Poisonous and Deleterious Substances

None of the components are listed.

Pollutant Release and Transfer Registers (PRTR)

None of the components are listed.

Japan - Water Pollution Control Law

Ingredient name

n-Hexane Extracts (mineral oil)

Zinc compounds Boron compounds

Korea

Regulation according to ISHA

: None of the components are listed. **ISHA** article 117

(Harmful substances prohibited from manufacture)

: None of the components are listed. **ISHA** article 118

(Harmful substances requiring permission)

Regulation according to K-REACH/CCA

	Chemical name	%	Remarks
K-REACH/CCA	: diphenylamine	<0.1	Impurity
Toxic chemicals			

K-REACH/CCA -

: None of the components are listed.

: Class: Class 4 - Flammable Liquid

Banned

: None of the components are listed. K-REACH/CCA -

Restricted

: The following components are listed: Boron compounds, Zinc and its compounds K-REACH/CCA

Article - TRI

Dangerous Materials Safety Management

Item: 5. Class 3 petroleums - Water-insoluble liquid

Threshold: 2000 L Act Danger category: III

Signal word: Contact with sources of ignition prohibited

International Inventory Status

: All components are listed or exempted. **Australia** All components are listed or exempted. Canada : All components are listed or exempted. **China**

: 4/7/2022 Version: 1.03 : 10/19/2022 Date of issue/Date of revision Date of previous issue

In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific)

HiTEC® 22520 Performance Additive

Page:

Section 15. Regulatory information

: For information on compliance with this regulation please contact your Afton **Europe**

representative

(EHS.CustomerVolumes@AftonChemical.com).

All components are listed or exempted. Japan : All components are listed or exempted. Republic of Korea

: All components are listed or exempted. **New Zealand** : All components are listed or exempted. **Philippines**

: For information on compliance with this regulation please contact your Afton representative **Switzerland**

(EHS.CustomerVolumes@AftonChemical.com).

: For information on compliance with this regulation please contact your Afton representative **Turkey**

(EHS.CustomerVolumes@AftonChemical.com).

: All components are listed or exempted. Taiwan

United Kingdom

: For information on compliance with this regulation please contact your Afton representative (EHS.CustomerVolumes@AftonChemical.com). (UK)

: All components are active or exempted. **United States**

Active

Section 16. Other information

History

Date of issue/Date of

revision

: 10/19/2022

EHS Department (Tel: +1 804 788 5800)

: ATE = Acute Toxicity Estimate **Key to abbreviations**

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations WOE = Weight of Evidence

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 3 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	

: CORR A20 **Toxicological and**

Ecotoxicological Test Data Summary(s)

 $m ec{}$ Indicates information that has changed from previously issued version.

Notice to reader

: 4/7/2022 Version: 1.03 : 10/19/2022 20/21 Date of issue/Date of revision Date of previous issue

Section 16. Other information

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. Afton makes no representation as to completeness or accuracy. In no event will Afton be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.

Date of issue/Date of revision : 10/19/2022 Date of previous issue : 4/7/2022 Version : 1.03 21/21