

## **Safety Data Sheet**

### **HiTEC® 12360 Performance Additive**

SDS no.

H12360

### **Section 1. Identification**

Product identifier : HiTEC® 12360 Performance Additive

**Product use** : Petrochemical industry: Lubricating Oil Additive.

Date of issue/Revisions : 2 May 2023

#### In case of emergency - Chemical

+1-703-527-3887 (International)

+65-3158-1349 (Asia Pacific)

+61-290372994 (Australia)

4001-204937 (China)

+81-345209637 (Japan)

00-308-13-2549 (South Korea)

+1-703-741-5979 (Spanish language)

+44-870-8200418 (UK)

1-800-424-9300 (ÙS & Canada)

### **Manufacturer / Supplier**

Afton Chemical Asia Pte. Ltd. 103 Penang Road #09-01 Visioncrest Commercial Singapore 238467

Telephone number: +65 6732 0822

Fax: +65 6737 4123

Afton Chemical (Suzhou) Co., Ltd. No. 26 Pingsheng Road, Suzhou Industrial Park, Suzhou

215126 China

Tel: +86-512-62605099

Afton Chemical (Beijing) Co., Ltd. Room 707 China World Office 1 No. 1 Jian Guo Men Wai Avenue

Beijing 100004 China

Telephone number: +86 10 6535 0000

Afton Chemical Japan Corporation Hirakawacho Mori Tower 7F, 2-16-1 Hirakawacho, Chiyoda-ku Tokyo Japan Afton Chemical Asia Pacific Company Level 12, 20 Berry Street North Sydney, NSW 2060 Australia

Telephone number: +61 299785800 Business Hours: 9:00am - 5:00pm Afton Chemical Korea Co., Ltd. 511 Yeongdong-daero, Gangnam-gu, 27th Floor Trade Tower Seoul City 06164 Republic of Korea Telephone number: +82- 2 -2191-4000

500 Spring St. Richmond, VA 23219 USA

Afton Chemical Corporation

Non-Emergency Telephone: +1-804-788-5800

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 1/24

Page: 2/24

#### **HiTEC® 12360 Performance Additive**

**Section 2. Hazards identification** 

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 3 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

**GHS label elements** 

Hazard pictograms :

Signal word : Warning

**Hazard statements** : Causes mild skin irritation.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** : Avoid release to the environment.

**Response** : If skin irritation occurs: Get medical advice or attention.

**Storage** : Store in a well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do

not result in classification

: None known.

Please note some GHS hazard classifications listed above may not be applicable in your country or region and are shown for informational purposes only.

For other GHS hazard classifications not listed above, the classification is not applicable in your region.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	CAS number	%	GHS Classification	Туре
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	≥15 - ≤25	Not classified.	[2]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	≥5 - ≤10	ASPIRATION HAZARD - Category 1	[1] [2]
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	≥5 - ≤10	Not classified.	[2]
bis(nonylphenyl)amine	36878-20-3	≥5 - ≤10	SKIN CORROSION/IRRITATION - Category 3	[1]
Alkyl esters of alkyl phenate alkanoic acid	Proprietary	≥5 - ≤10	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4	[1]
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	122384-87-6	≥5 - ≤10	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4	[1]

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 2/24

### Section 3. Composition/information on ingredients

Phosphorodithioic acid, mixed O,O-bis (2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	85940-28-9	≥3 - ≤5	ACUTE TOXICITY (oral) - Category 5 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	[1]
Alcohols, C12-16, ethoxylated	68551-12-2	≥0.1 - ≤0.3	SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 (M=1) LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	[1]
phenol, (tetrapropenyl) deriva-tives	74499-35-7	≥0.1 - <0.3	ACUTE TOXICITY (oral) - Category 5 SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 REPRODUCTIVE TOXICITY (Fertility) - Category 1B SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 (M=10) LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 (M=10)	[1]

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Please note some GHS hazard classifications listed above may not be applicable in your country or region and are shown for informational purposes only.

#### Type

- [1] Substance classified with a physical, health or environmental hazard
- [2] Substance with a workplace exposure limit

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If irritation persists, get medical attention.

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 3/24

### Section 4. First aid measures

#### **Inhalation**

: If inhaled, remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. If not breathing, give artificial respiration. If breathing is difficult, administer oxygen.

#### **Skin contact**

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if adverse health effects persist or are severe. Wash clothing before reuse. Clean shoes thoroughly before reuse. Continue to rinse for at least 15 minutes.

#### Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### **Potential acute health effects**

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: Causes mild skin irritation.

**Ingestion** : No known significant effects or critical hazards.

#### **Over-exposure signs/symptoms**

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-**

aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 4/24

### **Section 5. Firefighting measures**

### **Extinguishing media**

Suitable extinguishing

: In case of fire, use water spray (fog), foam, dry chemical or CO2.

media

Unsuitable extinguishing media

: Do not use water jet.

metal oxide/oxides Hydrogen sulphide

## Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

# Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

# Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

# Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

# For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# **Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and material for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 5/24

### Section 6. Accidental release measures

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	Safe Work Australia (Australia, 12/2019). TWA: 5 mg/m³ 8 hours. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Safe Work Australia (Australia, 12/2019). TWA: 5 mg/m³ 8 hours. Form: Mist
Distillates (petroleum), solvent-refined heavy paraffinic	Safe Work Australia (Australia, 12/2019). TWA: 5 mg/m³ 8 hours. Form: Mist

# Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

# **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 6/24

### Section 8. Exposure controls/personal protection

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn. unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### **Skin protection**

### **Hand protection**

: Hand Protection: Wear chemical resistant gloves. Nitrile gloves of minimum thickness 0.4 mm have an expected breakthrough time of 480 minutes or less when in frequent contact with the product. Due to variable exposure conditions the user must consider that the practical use of a chemical-protective glove in practice may be much shorter than the permeation time above. Manufacturer's directions for use, especially about the minimum thickness and the minimum breakthrough time, must be observed. This information does not replace suitability tests by the end user since glove protection varies depending on the conditions under which the product is used.

#### **Body protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

: Liquid. **Physical state** Brown.

: Not available. Odour : Not available. **Odour threshold** : Not available. pН : Not available. **Melting point** : Not available. **Boiling point** 

Closed cup: 135°C (275°F) [Pensky-Martens Minimum] **Flash point** 

: Not available. **Evaporation rate** : Not available. Flammability (solid, gas) : Not available. **Lower and upper** 

**explosive (flammable)** 

limits

Colour

: Not available. **Vapour pressure** : Not available. **Relative vapour density** : Not available. Vapour density

: 5/2/2023 : 12/8/2022 Version: 3.09 Date of issue/Date of revision Date of previous issue

In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific)

Page: 8/24

: 0.957 g/cm³ [59°F (15°C)] **Density** 

: Not available. **Relative density** : Not available. Solubility(ies)

HiTEC® 12360 Performance Additive

Partition coefficient: n-

octanol/water

: Not applicable.

Section 9. Physical and chemical properties

**Auto-ignition** 

temperature

: Not available.

**Decomposition** temperature

: Not available.

**Viscosity** 

133 cSt @ 100°C

: Not available. **Explosive properties** : Not available. **Oxidising properties** 

**Particle characteristics** 

: Not applicable. **Median particle size** 

### Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

: The product is stable. **Chemical stability** 

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : High temperatures, sparks, and open flames.

: Strong oxidising and reducing agents. **Incompatible materials** 

**Hazardous** Hydrogen sulphide

decomposition products

### **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Test	Result	Species	Dose	Exposure	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours	Based on data for a similar substance.
	402 Acute Dermal Toxicity	LD50 Dermal	Rabbit	>5000 mg/kg	-	Based on data for a similar substance.
	401 Acute Oral Toxicity	LD50 Oral	Rat	>5000 mg/kg	-	Based on data for a similar

: 5/2/2023 : 12/8/2022 Version: 3.09 8/24 Date of issue/Date of revision Date of previous issue

	1		1			substance.
Distillates (petroleum),	403 Acute	LC50 Inhalation	Rat	>5.53 mg/l	4 hours	-
solvent-dewaxed heavy	Inhalation	Vapour		3		
paraffinic	Toxicity	'				
	402 Acute	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	Dermal Toxicity					
	401 Acute Oral	LD50 Oral	Rat	>5000 mg/kg	-	-
	Toxicity					
Distillates (petroleum),	403 Acute	LC50 Inhalation	Rat	>5.53 mg/l	4 hours	Based on data
solvent-refined heavy	Inhalation	Vapour				for a similar
paraffinic	Toxicity	DEC D	5			substance.
	None available.	LD50 Dermal	Rabbit	>2000 mg/kg	-	-
his/nonylphonyl)amino	None available. 402 Acute	LD50 Oral LD50 Dermal	Rat Rat	>5000 mg/kg	-	Based on data
bis(nonylphenyl)amine	Dermal Toxicity	LD30 Dermai	Rai	>2000 mg/kg	-	for a similar
	Definal Toxicity					substance.
	401 Acute Oral	LD50 Oral	Rat	>5000 mg/kg	_	Based on data
	Toxicity	LB00 Orai	rtat	r 0000 mg/kg		for a similar
						substance.
Alkyl esters of alkyl phenate	402 Acute	LD50 Dermal	Rat	>2000 mg/kg	_	-
alkanoic acid	Dermal Toxicity					
	401 Acute Oral	LD50 Oral	Rat	>2000 mg/kg	-	-
	Toxicity					
Phenol, tetrapropylene-,	403 Acute	LC50 Inhalation	Rat	>1.67 mg/l	1 hours	-
sulfurized, carbonates,	Inhalation	Vapour				
calcium salts, overbased	Toxicity	D50 D	D-1-1-14	. 4000//		
	402 Acute	LD50 Dermal	Rabbit	>4000 mg/kg	-	-
	Dermal Toxicity 401 Acute Oral	LD50 Oral	Rat	>5000 mg/kg	_	_
	Toxicity	LD30 Orai	INGL	2000 Hig/kg	_	_
Phosphorodithioic acid,	403 Acute	LC50 Inhalation	Rat	>2.3 mg/l	4 hours	Based on data
mixed O,O-bis(2-ethylhexyl	Inhalation	Vapour	1 101	2.0 mg/.	1110410	for a similar
and iso-Bu and iso-Pr) esters,	Toxicity	'				substance.
zinc salts						
	402 Acute	LD50 Dermal	Rabbit	>20000 mg/kg	-	-
	Dermal Toxicity					
	401 Acute Oral	LD50 Oral	Rat	3080 mg/kg	-	-
Al1-1-040 401-1-1	Toxicity	1.050 1.1.1.1.1	D. 4	. 4 0	4 1	D I I.t.
Alcohols, C12-16, ethoxylated		LC50 Inhalation	Rat	>1.6 mg/l	4 hours	Based on data
	Inhalation Toxicity	Vapour				for a similar substance.
	402 Acute	LD50 Dermal	Rabbit	>2000 mg/kg		Based on data
	Dermal Toxicity	LD30 Deimai	Nabbit	- 2000 mg/kg	_	for a similar
	Dominal Toxicity					substance.
	401 Acute Oral	LD50 Oral	Rat	>2000 mg/kg	_	-
	Toxicity					
phenol, (tetrapropenyl) deriva-	402 Acute	LD50 Dermal	Rabbit	15000 mg/kg	-	-
tives	Dermal Toxicity					
	401 Acute Oral	LD50 Oral	Rat	2200 mg/kg	-	-
	Toxicity					
•	•			•	•	•

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 9/24

<u>Irritation/Corrosion</u>

Product/ingredient	Test	Species	Result	Remarks
name				
Distillates (petroleum), hydrotreated heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
bis(nonylphenyl)amine	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Mild irritant	Based on data for a similar substance.
Alkyl esters of alkyl phenate alkanoic acid	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	-
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	-
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	-
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Severe irritant	Not H319 at <15%. On basis of test data. Not H318 at <20%. On basis of test data.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Irritant	Not H315 at <15%. On basis of test data.
Alcohols, C12-16, ethoxylated	Irritation/Corrosion	Rabbit	Eyes - Severe irritant	-
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Irritant	-
phenol, (tetrapropenyl) derivatives	Irritation/Corrosion	Rabbit	Eyes - Visible necrosis	-
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Visible necrosis	-

Skin

: Causes mild skin irritation.

**Eyes** 

: Non-irritating to the eyes. Based on test data for this or similar products.

**Respiratory** 

: Based on available data, the classification criteria are not met.

**Sensitisation** 

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 10/24

Product/ingredient name	Test	Route of exposure	Species	Result	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
bis(nonylphenyl)amine	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
Alkyl esters of alkyl phenate alkanoic acid	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	-
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	406 Skin Sensitization	skin	Guinea pig	Ambiguous	WOE does not support classification
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	-
Alcohols, C12-16, ethoxylated	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	-
phenol, (tetrapropenyl) derivatives	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	-

### **Conclusion/Summary**

Skin

: Based on available data, the classification criteria are not met.

Respiratory

: Based on available data, the classification criteria are not met.

### **Mutagenicity**

Product/ingredient	Test	Experiment	Result	Remarks
name				
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
hydrotreated heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.
	476 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Cell Gene Mutation Test	Subject: Mammalian-Animal		similar substance.
	474 Mammalian	Experiment: In vivo	Negative	Based on data for a
	Erythrocyte Micronucleus Test	Subject: Mammalian-Animal		similar substance.
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
solvent-dewaxed heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
solvent-refined heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.
bis(nonylphenyl)amine	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a

Date of issue/Date of revision :5/2/2023 Date of previous issue :12/8/2022 Version :3.09 11/24

473 In vitro Mammalian Experiment: In vitro Negative Based on dat Subject: Mammalian-Animal Test	
	nce.
Test	
478 Genetic Toxicology: Experiment: In vitro Negative Based on dat	a for a
Rodent Dominant Lethal Subject: Mammalian-Animal similar substa	nce.
Test	
Alkyl esters of alkyl phenate   471 Bacterial Reverse   Experiment: In vitro   Negative   -	
alkanoic acid Mutation Test Subject: Bacteria	
473 In vitro Mammalian   Experiment: In vitro   Negative  -	
Chromosomal Aberration   Subject: Mammalian-Animal	
Test	
Phenol, tetrapropylene-, 471 Bacterial Reverse Experiment: In vitro Negative -	
sulfurized, carbonates, Mutation Test Subject: Bacteria	
calcium salts, overbased	
476 In vitro Mammalian   Experiment: In vitro   Negative  -	
Cell Gene Mutation Test   Subject: Mammalian-Animal	
Phosphorodithioic acid, None available. Experiment: In vitro Positive Based on dat	a for a
mixed O,O-bis(2-ethylhexyl Subject: Mammalian-Animal similar substa	nce.
and iso-Bu and iso-Pr) esters, WOE does no	ot
zinc salts support	
classification	
471 Bacterial Reverse   Experiment: In vitro   Negative  -	
Mutation Test Subject: Bacteria	
476 In vitro Mammalian Experiment: In vitro Negative Based on dat	a for a
Cell Gene Mutation Test   Subject: Mammalian-Animal   similar substa	nce.
Alcohols, C12-16, ethoxylated   471 Bacterial Reverse   Experiment: In vitro   Negative   -	
Mutation Test Subject: Bacteria	
473 In vitro Mammalian   Experiment: In vitro   Negative   Based on dat	a for a
Chromosomal Aberration   Subject: Mammalian-Animal   similar substa	nce.
Test	
phenol, (tetrapropenyl) deriva-   471 Bacterial Reverse   Experiment: In vitro   Negative   -	
tives Mutation Test Subject: Bacteria	
476 In vitro Mammalian   Experiment: In vitro   Negative  -	
Cell Gene Mutation Test   Subject: Mammalian-Animal	

### **Conclusion/Summary**

: Based on available data, the classification criteria are not met.

### **Carcinogenicity**

Product/ingredient name	Test	Species	Exposure	Result	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.
Alkyl esters of alkyl phenate alkanoic acid	453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat	104 weeks	Negative - Oral - NOAEL	Based on data for a similar substance.

# Conclusion/Summary Reproductive toxicity

: Based on available data, the classification criteria are not met.

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 12/24

Product/ingredient	Test	Route of	Species	Maternal	Fertility	Developmental	Remarks
name		exposure		toxicity		toxin	
Distillates (petroleum), hydrotreated heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Dermal	Rat	Negative	Negative	Negative	Based on data for a similar substance.
	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Alkyl esters of alkyl phenate alkanoic acid	415 One- Generation Reproduction Toxicity Study	Oral	Mouse	Positive	Negative	Negative	-
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	415 One- Generation Reproduction Toxicity Study	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Phosphorodithioic acid, mixed O,O-bis (2-ethylhexyl and iso- Bu and iso-Pr) esters, zinc salts	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Alcohols, C12-16, ethoxylated	416 Two- Generation Reproduction Toxicity Study	Dermal	Rat	Positive	Negative	Negative	Based on data for a similar substance.
phenol, (tetrapropenyl) deriva-tives	416 Two- Generation Reproduction Toxicity Study	Oral	Rat	Positive	Positive	Positive	-

**Conclusion/Summary** 

: North America and South America GHS classification: May damage fertility. For other regional GHS classifications: Not classified.

### **Teratogenicity**

Product/ingredient name	Test	Species	Result	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
bis(nonylphenyl)amine	414 Prenatal Developmental Toxicity Study	Rat	Negative - Oral	-
Alkyl esters of alkyl phenate	414 Prenatal Developmental	Rabbit	Equivocal - Oral	WOE does not

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 13/24

In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific) Page: HiTEC® 12360 Performance Additive

### **Section 11. Toxicological information**

alkanoic acid Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	Toxicity Study 414 Prenatal Developmental Toxicity Study	Rat	Negative - Oral	support classification
---	--	-----	-----------------	------------------------

: Based on available data, the classification criteria are not met. **Conclusion/Summary** 

### Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

### Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1

**Information on likely** routes of exposure

Skin, Eyes, Ingestion, and Inhalation

#### **Potential acute health effects**

: No known significant effects or critical hazards. **Eye contact Inhalation** No known significant effects or critical hazards.

: Causes mild skin irritation. **Skin contact** 

: No known significant effects or critical hazards. Ingestion

### Symptoms related to the physical, chemical and toxicological characteristics

: Adverse symptoms may include the following: **Eye contact** 

pain or irritation watering redness

: No specific data. Inhalation

: Adverse symptoms may include the following: **Skin contact** 

> irritation redness

: No specific data. Ingestion

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Short term exposure**

**Potential immediate** 

effects

: Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation. Ingestion may cause gastrointestinal irritation and diarrhoea.

**Potential delayed** 

effects

: Not available.

#### Long term exposure

**Potential immediate** 

effects

: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

: 5/2/2023 : 12/8/2022 Version: 3.09 14/24 Date of issue/Date of revision Date of previous issue

Potential delayed effects

: Not available.

### **Potential chronic health effects**

Product/ingredient	Test	Species	Dose	Exposure	Result	Remarks
name						
Distillates (petroleum), hydrotreated heavy paraffinic	408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	125 mg/kg	-	Sub-chronic LOAEL Oral	Based on data for a similar substance.
	410 Repeated Dose Dermal Toxicity: 21/28-day Study	Rabbit	1000 mg/kg	-	Sub-acute NOAEL Dermal	Based on data for a similar substance.
	411 Subchronic Dermal Toxicity: 90-day Study	Rat	30 mg/kg	-	Sub-chronic NOAEL Dermal	Based on data for a similar substance.
	None available.	Rat	0.15 mg/l	13 weeks	Sub-chronic NOAEL Inhalation Dusts and mists	Based on data for a similar substance.
	None available.	Rat	0.22 mg/l	4 weeks	Sub-chronic NOAEL Inhalation Dusts and mists	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	410 Repeated Dose Dermal Toxicity: 21/28-day Study	Rabbit	1000 mg/kg	-	Sub-acute NOAEL Dermal	Based on data for a similar substance.
	None available.	Rat	0.05 mg/l	13 weeks	Sub-chronic NOAEL Inhalation Vapour	-
Distillates (petroleum), solvent-refined heavy paraffinic	410 Repeated Dose Dermal Toxicity: 21/28-day Study	Rabbit	1000 mg/kg	-	Sub-acute NOAEL Dermal	Based on data for a similar substance.
	None available.	Rat	0.15 mg/l	13 weeks	Sub-chronic NOAEL Inhalation Vapour	Based on data for a similar substance.
	None available.	Rat	0.22 mg/l	28 days	Sub-acute NOAEL Inhalation Vapour	Based on data for a similar substance.
bis(nonylphenyl)amine	408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	100 mg/kg	-	Sub-chronic LOAEL Oral	-
Alkyl esters of alkyl phenate alkanoic acid	408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	3 mg/kg	-	Sub-chronic NOAEL Oral	-
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	410 Repeated Dose Dermal Toxicity: 21/28-day Study	Rat	250 mg/kg	-	Sub-acute NOAEL Dermal	-
, , , , , , , , , , , , , , , , , , , ,	422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental	Rat	200 mg/kg	-	Sub-acute NOAEL Oral	-

Date of issue/Date of revision :5/2/2023 Date of previous issue :12/8/2022 Version :3.09 15/24

Page:

#### **HiTEC® 12360 Performance Additive**

### **Section 11. Toxicological information**

r	Phosphorodithioic acid, nixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, tinc salts	Toxicity Screening Test 407 Repeated Dose 28-day Oral Toxicity Study in Rodents	Rat	125 mg/kg	-	Sub-acute NOAEL Oral	Based on data for a similar substance.
		407 Repeated Dose 28-day Oral Toxicity Study in Rodents	Rat	100 mg/kg	-	Sub-acute NOAEL Oral	-
	ohenol, (tetrapropenyl) deriva- ives	-	Rat	60 mg/kg	-	Sub-acute NOAEL Oral	-
		416 Two-Generation Reproduction Toxicity Study	Rat	15 mg/kg	-	Sub-chronic NOAEL Oral	-
		408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	100 mg/kg	-	Sub-chronic NOAEL Oral	-

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

**General** 

: No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.No known significant effects or critical hazards.

Mutagenicity
Teratogenicity

: No known significant effects or critical hazards.

**Developmental effects** 

: No known significant effects or critical hazards.

Fertility effects

: No known significant effects or critical hazards.

### **Section 12. Ecological information**

### **Toxicity**

Product/ingredient name	Result	Species	Exposure	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEL 1000 mg/l	Fish - Oncorhynchus mykiss	14 days	QSAR result.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.

Date of issue/Date of revision :5/2/2023 Date of previous issue :12/8/2022 Version :3.09 16/24

	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	substance. Based on data for a similar substance.
	Chronic NOEL 1000	Fish - Oncorhynchus mykiss	14 days	QSAR result.
Distillates (petroleum), solvent-refined heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
paramine	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEL 1000	Fish - Oncorhynchus mykiss	14 days	QSAR result.
bis(nonylphenyl)amine	Acute EL50 >100 mg/	Algae - Pseudokirchneriella subcapitata	72 hours	-
	Acute EL50 >100 mg/	Daphnia - Daphnia magna	48 hours	-
	Acute IC50 >100 mg/l	Micro-organism	3 hours	Based on data for a similar substance.
	Acute LL50 >100 mg/	Fish - Danio rerio	96 hours	Based on data for a similar substance.
	Chronic EL10 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	-
	Chronic EL10 4.12 mg/l Fresh water	Crustaceans - Daphnia magna	21 days	-
	Chronic NOEL 10 mg/l Fresh water	Fish - Danio rerio	34 days	-
Alkyl esters of alkyl phenate alkanoic acid	Acute EL50 >3 mg/l	Algae - Desmodesmus subspicatus	72 hours	No effects at saturation.
	Acute EL50 >0.9 mg/l		48 hours	No effects at saturation.
	Acute IC50 >100 mg/l	Micro-organism	3 hours	No effects at saturation.
	Acute LC50 >74 mg/l	Fish - Danio rerio	96 hours	No effects at saturation.
	Chronic NOEL >3 mg/l	Algae - Desmodesmus subspicatus	72 hours	No effects at saturation.
	Chronic NOEL >0.001 mg/l	Fish - Danio rerio	36 days	No effects at saturation.
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	Acute EL50 >500 mg/	Algae - Pseudokirchneriella subcapitata	96 hours	-
, ======	Acute EL50 >1000 mg/l	Daphnia - Daphnia magna	48 hours	-
	Acute EL50 >10000 mg/l	Micro-organism	3 hours	Based on data for a similar substance.
	Acute LL50 >1000	Fish - Pimephales promelas	96 hours	-

Date of issue/Date of revision :5/2/2023 Date of previous issue :12/8/2022 Version :3.09 17/24

1	I //		ı	<u> </u>
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	mg/l Acute EL50 2.1 mg/l	Algae - Selenastrum capricornutum	96 hours	Based on data for a similar substance.
Zino Gaile	Acute EL50 5.4 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
	Acute EL50 >10000 mg/l	Micro-organism	3 hours	Based on data for a similar substance.
	Acute LL50 4.5 mg/l	Fish - Oncorhynchus mykiss	96 hours	Based on data for a similar substance.
	Chronic NOEL 1 mg/l	Algae - Selenastrum capricornutum	96 hours	Based on data for a similar substance.
	Chronic NOEL 0.4 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
Alcohols, C12-16, ethoxylated	Acute EL50 0.41 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Acute EL50 0.39 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
	Acute EL50 >2 mg/l	Micro-organism	5 hours	Based on data for a similar substance.
	Acute LC50 0.876 mg/l	Fish - Danio rerio	96 hours	Based on data for a similar substance.
	Chronic NOEC 0.77 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEC 0.16 mg/l	Fish - Pimephales promelas	10 days	Based on data for a similar substance.
	Chronic NOEL 0.31 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
phenol, (tetrapropenyl) derivatives	Acute EL50 0.36 mg/l	Algae - Desmodesmus subspicatus	72 hours	-
	Acute EL50 0.037 mg/l	Daphnia - Daphnia magna	48 hours	-
	Acute EL50 >1000 mg/l	Micro-organism	3 hours	-
	Acute LL50 40 mg/l Chronic NOEL 0.07	Fish - Pimephales promelas Algae - Desmodesmus	96 hours 72 hours	-
	mg/l Chronic NOEL 0.0037 mg/l	subspicatus Daphnia - Daphnia magna	21 days	-
		fe with long lasting effects		

**Conclusion/Summary** 

: Harmful to aquatic life with long lasting effects.

### **Persistence and degradability**

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 18/24

Product/ingredient	Test	Result	Remarks
name			
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
bis(nonylphenyl)amine	OECD 301C Ready Biodegradability - Modified MITI Test (I)	24 % - Not readily - 28 days	-
Alkyl esters of alkyl phenate alkanoic acid	OECD 301B Ready Biodegradability - CO2 Evolution Test	2 % - Not readily - 28 days	-
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	OECD 301B Ready Biodegradability - CO2 Evolution Test	13.4 % - Not readily - 28 days	Based on data for a similar substance.
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	OECD 301B Ready	1.5 % - Not readily - 28 days	Based on data for a similar substance.
Alcohols, C12-16, ethoxylated	OECD 301F Ready Biodegradability - Manometric Respirometry Test	95 % - Readily - 28 days	Based on data for a similar substance.
phenol, (tetrapropenyl) derivatives	OECD 301B Ready Biodegradability - CO2 Evolution Test	6 to 25 % - Not readily - 28 days	-

### **Bioaccumulative potential**

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 19/24

In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific)

Page:

### **Section 12. Ecological information**

HiTEC® 12360 Performance Additive

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), solvent-refined heavy paraffinic	3.9 to 6	-	high
bis(nonylphenyl)amine Alkyl esters of alkyl phenate alkanoic acid	3.64 to 7.02 9.2	1730 260	high low
Phenol, tetrapropylene-, sulfurized, carbonates, calcium salts, overbased	9.5	-	high
phenol, (tetrapropenyl) derivatives	-	289 to 1601	high

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

Hazardous to the ozone laver

: Not applicable.

Other adverse effects

: No known significant effects or critical hazards.

### **Section 13. Disposal considerations**

#### **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **Section 14. Transport information**

	UN	ADG	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
		-	-	-

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 20/24

14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific)

Page:

14.7 Transport in bulk according to IMO instruments

: Not available.

### Section 15. Regulatory information

### China

### **List of Goods banned for Importing**

HiTEC® 12360 Performance Additive

None of the components are listed.

### **List of Goods banned for Exporting**

None of the components are listed.

### **List of Toxic Chemicals Severely Restricted for Importing & Exporting by China**

None of the components are listed.

### **Singapore**

### Singapore - hazardous chemicals under government control

None.

### **Australia**

### **Standard for the Uniform Scheduling of Medicines and Poisons**

Not applicable.

### **Model Work Health and Safety Regulations - Scheduled Substances**

No listed substance

### **Japan**

#### **Fire Service Law**

Category	Substance name/Type	Danger category
Category IV	Class III petroleums	III

#### **Industrial Safety and Health Act**

#### **Label Requirements and Chemicals Requiring Notification**

Date of issue/Date of revision :5/2/2023 Date of previous issue :12/8/2022 Version :3.09 21/24

### **Section 15. Regulatory information**

Ingredient name	%
Mineral oil Molybdenum and its compounds	≥35 - ≤45 ≥0.30 - ≤0.50

### **Chemical Substances Control Law (CSCL)**

Ingredient name	%		Reference number
alpha-Alkyl(C12-15)-omega-hydroxypoly(oxyethylene) (It is limited that a number-average molecular weight of the polymer is less than 1,000.)	≥0.10 - ≤0.30	Priority assessment	189

### **Poisonous and Deleterious Substances**

None of the components are listed.

### **Pollutant Release and Transfer Registers (PRTR)**

None of the components are listed.

### **Japan - Water Pollution Control Law**

### **Ingredient name**

n-Hexane Extracts (mineral oil)

Zinc compounds

Boron compounds

Phenol derivative compounds

### Korea

#### **Regulation according to ISHA**

: None of the components are listed. **ISHA** article 117

(Harmful

substances

prohibited from

manufacture)

**ISHA** article 118

: None of the components are listed.

(Harmful

substances

requiring

permission)

### Regulation according to K-REACH/CCA

	Chemical name	<b>%</b>	Remarks
K-REACH/CCA Toxic chemicals	: diphenylamine	<0.1	Impurity
	Triphenylphosphine	<0.001	Impurity

K-REACH/CCA -

**Banned** 

: None of the components are listed.

K-REACH/CCA -

: None of the components are listed.

**Restricted** 

K-REACH/CCA

: The following components are listed: Boron compounds, Zinc and its compounds

**Article - TRI** 

: 5/2/2023 : 12/8/2022 Version: 3.09 22/24 Date of issue/Date of revision Date of previous issue

### Section 15. Regulatory information

**Dangerous Materials** Safety Management

Act

: Class: Class 4 - Flammable Liquid

Item: 5. Class 3 petroleums - Water-insoluble liquid

Threshold: 2000 L Danger category: III

Signal word: Contact with sources of ignition prohibited

**International Inventory Status** 

: All components are listed or exempted. Australia (AIIC)

Canada (DSL/NDSL) : At least one component is not listed. China (IECSC)

: All components are listed or exempted.

Notified. Please contact your supplier for information on the inventory status of this material. : For information on compliance with this regulation please contact your Afton representative

(EHS.CustomerVolumes@AftonChemical.com).

: At least one component is not listed. Japan (ENCS)

Notified. Please contact your supplier for information on the inventory status of this material.

Republic of Korea (ECL)

**Europe (REACh)** 

: At least one component is not listed.

Exempted. Please contact your supplier for information on the inventory status of this

material.

**New Zealand** 

(NZIoC)

: All components are listed or exempted.

: All components are listed or exempted.

**Philippines (PICCS)** 

Switzerland (SWISS): For information on compliance with this regulation please contact your Afton representative

(EHS.CustomerVolumes@AftonChemical.com).

Turkey (KKDIK)

: For information on compliance with this regulation please contact your Afton representative

(EHS.CustomerVolumes@AftonChemical.com).

Taiwan (TCSI) **United Kingdom** (UK REACh)

: All components are listed or exempted.

: For information on compliance with this regulation please contact your Afton representative (EHS.CustomerVolumes@AftonChemical.com).

**United States Active (TSCA)**  : All components are active or exempted.

### Section 16. Other information

### **History**

Date of issue/Date of revision

: 5/2/2023

EHS Department (Tel: +1 804 788 5800)

**Key to abbreviations** 

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations WOE = Weight of Evidence

: 5/2/2023 Version: 3.09 : 12/8/2022 23/24 Date of issue/Date of revision Date of previous issue

### **Section 16. Other information**

### Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 3 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	

Toxicological and

: CMR A1, CORR A21

**Ecotoxicological Test** 

**Data Summary(s)** 

 $m ec{}$  Indicates information that has changed from previously issued version.

#### **Notice to reader**

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. Afton makes no representation as to completeness or accuracy. In no event will Afton be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.

Date of issue/Date of revision : 5/2/2023 Date of previous issue : 12/8/2022 Version : 3.09 24/24