

# **Safety Data Sheet**

### **HiTEC® 644 Performance Additive**

SDS no.

H644

### **Section 1. Identification**

Product identifier : HiTEC® 644 Performance Additive

Product use : Petrochemical industry: Dispersant

Date of issue/Revisions : 15 March 2024

#### In case of emergency - Chemical

+1-703-527-3887 (International)

+65-3158-1349 (Asia Pacific)

+61-290372994 (Australia)

4001-204937 (China)

+81-345209637 (Japan)

00-308-13-2549 (South Korea)

+1-703-741-5979 (Spanish language)

+44-870-8200418 (UK)

1-800-424-9300 (US & Canada)

#### **Manufacturer / Supplier**

Afton Chemical Asia Pte. Ltd. 103 Penang Road #09-01 Visioncrest Commercial Singapore 238467 Telephone number: +65 6732 0822

Fax: +65 6737 4123

Afton Chemical Japan Corporation Hirakawacho Mori Tower 7F, 2-16-1 Hirakawacho, Chiyoda-ku Tokyo Japan

Afton Chemical Corporation 500 Spring St. Richmond, VA 23219 USA

Non-Emergency Telephone: +1-804-788-5800

Afton Chemical (Suzhou) Co., Ltd. No. 26 Pingsheng Road, Suzhou Industrial Park, Suzhou 215126 China

Tel: +86-512-62605099

Afton Chemical Asia Pacific Company Suite 2, Level 1, 9-11 Grosvenor Street, Neutral Bay, NSW 2089 Australia

Telephone number: +61 299785800 Business Hours: 9:00am - 5:00pm Afton Chemical (Beijing) Co., Ltd. Room 707 China World Office 1 No. 1 Jian Guo Men Wai Avenue Beijing 100004 China Telephone number: +86 10 6535 0000

Afton Chemical Korea Co., Ltd. 511 Yeongdong-daero, Gangnam-gu, 27th Floor Trade Tower Seoul City 06164 Republic of Korea

Telephone number: +82- 2 -2191-4000

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 1/18

Page: 2/18

### **Section 2. Hazards identification**

Classification of the substance or mixture

: Not classified.

**GHS** label elements

Hazard pictograms

**Signal word** : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.

Response : Not applicable.

**Storage** : Store in a well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do

not result in classification

: None known.

Please note some GHS hazard classifications listed above may not be applicable in your country or region and are shown for informational purposes only.

For other GHS hazard classifications not listed above, the classification is not applicable in your region.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	CAS number	%	GHS Classification	Туре
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	≥10 - ≤15	ASPIRATION HAZARD - Category 1	[1] [2]
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	≥10 - ≤15	Not classified.	[2]
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	≥3 - ≤5	Not classified.	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Please note some GHS hazard classifications listed above may not be applicable in your country or region and are shown for informational purposes only.

#### **Type**

# Section 3. Composition/information on ingredients

- 📶 Substance classified with a physical, health or environmental hazard
- [2] Substance with a workplace exposure limit

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

**Inhalation** 

: If inhaled, remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial respiration. If breathing is difficult, administer oxygen.

**Skin contact** 

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

**Ingestion** 

: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

#### **Potential acute health effects**

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

#### **Over-exposure signs/symptoms**

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** 

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-**

: No action shall be taken involving any personal risk or without suitable training.

aiders

### See toxicological information (Section 11)

# **Section 5. Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing

: In case of fire, use water spray (fog), foam, dry chemical or CO2.

media

Unsuitable : Do not use water jet.

extinguishing media

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 3/18

## **Section 5. Firefighting measures**

# **Specific hazards arising** from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

# Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# **Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 4/18

## Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
pstillates (petroleum), solvent-dewaxed heavy paraffinic	Safe Work Australia (Australia, 10/2022). [Oil mist, refined mineral]  TWA: 5 mg/m³ 8 hours. Form: Mist Japan Society for Occupational Health (Japan, 9/2022). [Oil mist, mineral]  OEL-M: 3 mg/m³ 8 hours. Form: Mist Workplace Safety and Health Act (Singapore, 2/2006). [Oil Mist, mineral]  PEL (long term): 5 mg/m³ 8 hours. Form: Mist  PEL (short term): 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	Safe Work Australia (Australia, 10/2022). [Oil mist, refined mineral]  TWA: 5 mg/m³ 8 hours. Form: Mist Japan Society for Occupational Health (Japan, 9/2022). [Oil mist, mineral]  OEL-M: 3 mg/m³ 8 hours. Form: Mist Workplace Safety and Health Act (Singapore, 2/2006). [Oil Mist, mineral]  PEL (long term): 5 mg/m³ 8 hours. Form: Mist  PEL (short term): 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-refined heavy paraffinic	Safe Work Australia (Australia, 10/2022). [Oil mist, refined mineral]  TWA: 5 mg/m³ 8 hours. Form: Mist Japan Society for Occupational Health (Japan, 9/2022). [Oil mist, mineral]  OEL-M: 3 mg/m³ 8 hours. Form: Mist Workplace Safety and Health Act (Singapore, 2/2006). [Oil Mist, mineral]  PEL (long term): 5 mg/m³ 8 hours. Form: Mist  PEL (short term): 10 mg/m³ 15 minutes. Form: Mist

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Date of issue/Date of revision** : 3/15/2024 **Date of previous issue** : 1/9/2023 **Version** : 1.04 5/18

## Section 8. Exposure controls/personal protection

### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

### **Hand protection**

: Hand Protection: Wear chemical resistant gloves. Nitrile gloves of minimum thickness 0.4 mm have an expected breakthrough time of 480 minutes or less when in frequent contact with the product. Due to variable exposure conditions the user must consider that the practical use of a chemical-protective glove in practice may be much shorter than the permeation time above. Manufacturer's directions for use, especially about the minimum thickness and the minimum breakthrough time, must be observed. This information does not replace suitability tests by the end user since glove protection varies depending on the conditions under which the product is used.

#### **Body protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

**Boiling point** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

: Liquid. [Viscous] **Physical state** Brown. [Dark] Colour : Not available. **Odour** : Not available. **Odour threshold** : Not available. pН : Not available. **Melting point** : Not available.

: Closed cup: 150°C (302°F) [Pensky-Martens. Minimum] Flash point

: Not available. **Evaporation rate** : Not available. Flammability (solid, gas)

: 1/9/2023 Version: 1.04 : 3/15/2024 Date of issue/Date of revision Date of previous issue

HiTEC® 644 Performance Additive In case of emergency 4001-204937 (China) +65-3158-1349 (Asia Pacific)

Section 9. Physical and chemical properties

**Lower and upper** 

**explosive (flammable)** 

limits

**Density** 

: Not available.

: Not available.

Vapour pressure
Relative vapour density

Not available.Not available.

Vapour density

: 0.92 g/cm³ [60.1°F (15.6°C)]

**Relative density** 

0.922

Solubility(ies)

Media

cold water

.

ı	 	-		
-				

Result
Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition

ition : Not available.

temperature

**Decomposition** 

: Not available.

temperature

**Viscosity** : Kinematic (40°C): 9900 mm²/s (9900 cSt)

Minimum

Page: 7/18

320 cSt @ 100°C

**Explosive properties** 

: Not available.

**Oxidising properties** 

: Not available.

**Particle characteristics** 

Median particle size

: Not applicable.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : High temperatures, sparks, and open flames.

**Incompatible materials**: Strong oxidising and reducing agents.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 7/18

# **Section 11. Toxicological information**

### **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient	Test	Result	Species	Dose	Exposure	Remarks
name						
istillates (petroleum), solvent-dewaxed heavy paraffinic	403 Acute Inhalation Toxicity	LC50 Inhalation Vapour	Rat	>5.53 mg/l	4 hours	-
	402 Acute Dermal Toxicity	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	401 Acute Oral Toxicity	LD50 Oral	Rat	>5000 mg/kg	-	-
Distillates (petroleum), hydrotreated heavy paraffinic	403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours	Based on data for a similar substance.
	402 Acute Dermal Toxicity	LD50 Dermal	Rabbit	>5000 mg/kg	-	Based on data for a similar substance.
	401 Acute Oral Toxicity	LD50 Oral	Rat	>5000 mg/kg	-	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours	Based on data for a similar substance.
	402 Acute Dermal Toxicity	LD50 Dermal	Rabbit	>5000 mg/kg	-	Based on data for a similar substance.
	401 Acute Oral Toxicity	LD50 Oral	Rat	>5000 mg/kg	-	Based on data for a similar substance.

#### **Conclusion/Summary**

Eased on available data, the classification criteria are not met.

### **Irritation/Corrosion**

Product/ingredient name	Test	Species	Result	Remarks
Distillates (petroleum), solvent-dewaxed heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not irritant	Based on data for a similar substance.
'	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not irritant	Based on data for a similar substance.
Distillates (petroleum), hydrotreated heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not irritant	Based on data for a similar substance.
, , ,	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Not irritant	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not irritant	Based on data for a similar substance.
•	None available.	Rabbit	Skin - Not irritant	Based on data for a similar substance.

#### **Conclusion/Summary**

**Skin** : Sased on available data, the classification criteria are not met.

**Eyes** : Based on available data, the classification criteria are not met.

**Respiratory** : Sased on available data, the classification criteria are not met.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 8/18

# **Section 11. Toxicological information**

#### **Sensitisation**

Product/ingredient name	Test	Route of exposure	Species	Result	Remarks
Distillates (petroleum), solvent-dewaxed heavy paraffinic	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
Distillates (petroleum), hydrotreated heavy paraffinic	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.

#### **Conclusion/Summary**

**Skin** : Based on available data, the classification criteria are not met.

**Respiratory** : Sased on available data, the classification criteria are not met.

### **Mutagenicity**

Product/ingredient	Test	Experiment	Result	Remarks
name				
<b>D</b> istillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
solvent-dewaxed heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
hydrotreated heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.
	476 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Cell Gene Mutation Test	Subject: Mammalian-Animal		similar substance.
	474 Mammalian	Experiment: In vivo	Negative	Based on data for a
	Erythrocyte Micronucleus Test	Subject: Mammalian-Animal		similar substance.
Distillates (petroleum),	471 Bacterial Reverse	Experiment: In vitro	Negative	Based on data for a
solvent-refined heavy paraffinic	Mutation Test	Subject: Bacteria		similar substance.
	473 In vitro Mammalian	Experiment: In vitro	Negative	Based on data for a
	Chromosomal Aberration Test	Subject: Mammalian-Animal		similar substance.

#### **Conclusion/Summary**

Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Product/ingredient name	Test	Species	Exposure	Result	Remarks
Distillates (petroleum), solvent-dewaxed heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.
Distillates (petroleum), hydrotreated heavy paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.

#### **Conclusion/Summary**

Eased on available data, the classification criteria are not met.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 9/18

## **Section 11. Toxicological information**

#### **Reproductive toxicity**

Product/ingredient name	Test	Route of exposure	opeoies	Maternal toxicity	Fertility	Developmental toxin	Remarks
Distillates (petroleum), solvent-dewaxed heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Dermal	Rat	Negative	Negative	Negative	Based on data for a similar substance.
	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Distillates (petroleum), hydrotreated heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.

#### **Conclusion/Summary**

Based on available data, the classification criteria are not met.

#### **Teratogenicity**

Product/ingredient name	Test	Species	Result	Remarks
istillates (petroleum), solvent-dewaxed heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
Distillates (petroleum), hydrotreated heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
	414 Prenatal Developmental Toxicity Study	Rat	Negative - Oral	Based on data for a similar substance.

**Conclusion/Summary** 

: Not available.

#### Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

#### **Specific target organ toxicity (repeated exposure)**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Name	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

: Skin, Eyes, Ingestion, and Inhalation

### **Potential acute health effects**

Eye contactInhalationNo known significant effects or critical hazards.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 10/18

Page:

## **Section 11. Toxicological information**

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Short term exposure**

**Potential immediate** 

effects

: Inhalation of oil mist or vapours at elevated temperatures may cause respiratory

irritation. Ingestion may cause gastrointestinal irritation and diarrhoea.

**Potential delayed** 

effects

: Not available.

**Long term exposure** 

Potential immediate

effects

: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the

skin.

**Potential delayed** 

effects

: Not available.

#### Potential chronic health effects

Product/ingredient	Test	Species	Dose	Exposure	Result	Remarks
name						
istillates (petroleum), solvent-dewaxed heavy paraffinic	410 Repeated Dose Dermal Toxicity: 21/28-day Study	Rabbit	1000 mg/kg	-	Sub-acute NOAEL Dermal	Based on data for a similar substance.
	None available.	Rat	0.05 mg/l	13 weeks	Sub-chronic NOAEL Inhalation Vapour	-
Distillates (petroleum), hydrotreated heavy paraffinic	408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	125 mg/kg	-	Sub-chronic LOAEL Oral	Based on data for a similar substance.
	410 Repeated Dose Dermal Toxicity: 21/28-day Study	Rabbit	1000 mg/kg	-	Sub-acute NOAEL Dermal	Based on data for a similar substance.
	411 Subchronic Dermal Toxicity: 90-day Study	Rat	30 mg/kg	-	Sub-chronic NOAEL Dermal	Based on data for a similar substance.
	None available.	Rat	0.15 mg/l	13 weeks	Sub-chronic NOAEL Inhalation Dusts and mists	Based on data for a similar substance.
	None available.	Rat	0.22 mg/l	4 weeks	Sub-chronic NOAEL Inhalation Dusts and mists	Based on data for a similar substance.
Distillates (petroleum),	410 Repeated Dose	Rabbit	1000 mg/kg	-	Sub-acute	Based on data

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 11/18

#### **HiTEC® 644 Performance Additive**

(Asia Pacific) Page:

# Section 11. Toxicological information

solvent-refined heavy	Dermal Toxicity:				NOAEL Dermal	for a similar
paraffinic	21/28-day Study					substance.
	411 Subchronic	Rat	2000 mg/kg	13 weeks	Sub-chronic	Based on data
	Dermal Toxicity:				NOAEL Dermal	for a similar
	90-day Study					substance.
	412 Repeated Dose	Rat	220 mg/m <sup>3</sup>	4 weeks	Sub-acute	Based on data
	Inhalation Toxicity:				NOAEL	for a similar
	28-day or 14-day				Inhalation	substance.
	Study				Dusts and	
	,				mists	

Conclusion/Summary

: Not available.

**General** 

: No known significant effects or critical hazards.

**Carcinogenicity** 

: No known significant effects or critical hazards.

**Mutagenicity** 

No known significant effects or critical hazards.No known significant effects or critical hazards.

Teratogenicity

Developmental effects

: No known significant effects or critical hazards.

**Fertility effects** 

: No known significant effects or critical hazards.

# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure	Remarks
istillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
para	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEL 1000 mg/l	Fish - Oncorhynchus mykiss	14 days	QSAR result.
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEL 1000 mg/l	Fish - Oncorhynchus mykiss	14 days	QSAR result.
Distillates (petroleum), solvent-refined heavy paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.

Date of issue/Date of revision

: 3/15/2024

Date of previous issue

: 1/9/2023

Version: 1.04

12/18

## **Section 12. Ecological information**

9.00			
Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
Chronic NOEL 1000 mg/l	Fish - Oncorhynchus mykiss	14 days	QSAR result.

#### **Conclusion/Summary**

Eased on available data, the classification criteria are not met.

### **Persistence and degradability**

Product/ingredient name	Test	Result	Remarks
vistillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.
Distillates (petroleum), solvent-refined heavy paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
istillates (petroleum), solvent-refined heavy paraffinic	3.9 to 6	-	high

#### **Mobility in soil**

layer

Soil/water partition

: Not available.

coefficient (Koc)
Mobility

: Not available.: Not applicable.

Hazardous to the ozone

Other adverse effects

: No known significant effects or critical hazards.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 13/18

# **Section 13. Disposal considerations**

#### **Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	ADG	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class (es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

This product is classified as non hazardous for transport when shipped in non-bulk quantities but when shipped in bulk by road, rail or sea may be classified as UN3257, Elevated temperature liquid, n.o.s. (Polyolefin amide alkeneamine; Petroleum distillates), 9, III

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

# Section 15. Regulatory information

#### China

#### **List of Goods banned for Importing**

None of the components are listed.

#### **List of Goods banned for Exporting**

None of the components are listed.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 14/18

### Section 15. Regulatory information

#### List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

### **Singapore**

#### Singapore - hazardous chemicals under government control

None.

#### **Australia**

#### **Standard for the Uniform Scheduling of Medicines and Poisons**

Not applicable.

#### **Model Work Health and Safety Regulations - Scheduled Substances**

No listed substance

### **Japan**

### Fire Service Law

Category	Substance name/Type	Danger category
Category IV	Class III petroleums	III

#### **Industrial Safety and Health Act**

# <u>Label Requirements, Chemicals Requiring Notification and/or Substances that are corrosive to the skin</u>

Ingredient name	%
Mineral oil	≥25 - ≤35

#### **Chemical Substances Control Law (CSCL)**

None of the components are listed.

#### **Poisonous and Deleterious Substances**

None of the components are listed.

#### **Pollutant Release and Transfer Registers (PRTR)**

None of the components are listed.

#### **Japan - Water Pollution Control Law**

#### **Ingredient name**

Hexane Extracts (mineral oil)

#### Korea

#### **Regulation according to ISHA**

**ISHA article 117** : None of the components are listed.

(Harmful substances prohibited from

manufacture)

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 15/18

**HiTEC® 644 Performance Additive** 

Page:

# Section 15. Regulatory information

**ISHA** article 118

: None of the components are listed.

: metal working fluids: oil mist, mineral

(Harmful

substances

requiring

permission)

**Exposure Limits of** 

**Chemical** 

**Substances and Physical Factors** 

**Standard of** 

**Industrial Safety** 

and Health Annex

12 (Hazardous

substances subject

to control)

**ISHA Enforcement** 

**Regs Annex 19** 

(Exposure

standards

established for

harmful factors)

**ISHA Enforcement** 

**Regs Annex 21** 

(Harmful factors

subject to Work

**Environment** 

**Measurement)** 

**ISHA Enforcement** 

**Regs Annex 22** (Harmful Factors

**Subject to Special** 

**Health Check-up)** 

**Wastes regulation** 

: Designated waste

Regulation according to K-REACH/CCA

**Chemical name** 

% **Remarks** 

K-REACH/CCA

: None of the components are listed.

**Toxic chemicals** 

K-REACH/CCA -

**Banned** 

: None of the components are listed.

K-REACH/CCA -

: None of the components are listed.

**Restricted** 

K-REACH/CCA

: None of the components are listed.

**Article - TRI** 

: 3/15/2024 : 1/9/2023 Version: 1.04 16/18 Date of issue/Date of revision Date of previous issue

Page:

## Section 15. Regulatory information

K-REACH/CCA

: None of the components are listed.

**Article 39 (Accident** 

**Precaution Chemicals**)

Act

**Dangerous Materials Safety Management** 

: Class: Class 4 - Flammable Liquid Item: 5. Class 3 petroleums - Water-insoluble liquid

Threshold: 2000 L Danger category: III

Signal word: Contact with sources of ignition prohibited

**International Inventory Status** 

Australia (AIIC) : All components are listed or exempted. Canada (DSL/NDSL) : All components are listed or exempted. : All components are listed or exempted. China (IECSC)

: For information on compliance with this regulation please contact your Afton representative **Europe (REACh)** 

(EHS.CustomerVolumes@AftonChemical.com).

: All components are listed or exempted. Japan (ENCS) Republic of Korea : All components are listed or exempted.

(ECL)

New Zealand (NZIoC) : All components are listed or exempted. **Philippines (PICCS)** : All components are listed or exempted.

Switzerland (SWISS) : For information on compliance with this regulation please contact your Afton representative

(EHS.CustomerVolumes@AftonChemical.com).

**Turkey (KKDIK)** : For information on compliance with this regulation please contact your Afton representative

(EHS.CustomerVolumes@AftonChemical.com).

Taiwan (TCSI) : All components are listed or exempted.

**United Kingdom (UK** 

REACh)

**United States Active** : All components are active or exempted.

(TSCA)

: For information on compliance with this regulation please contact your Afton representative

(EHS.CustomerVolumes@AftonChemical.com).

### Section 16. Other information

**History** 

Date of issue/Date of

revision

: 3/15/2024

EHS Department (Tel: +1 804 788 5800)

: ATE = Acute Toxicity Estimate **Key to abbreviations** 

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations WOE = Weight of Evidence

Indicates information that has changed from previously issued version.

**Notice to reader** 

: 3/15/2024 : 1/9/2023 Version: 1.04 17/18 Date of issue/Date of revision Date of previous issue

### **Section 16. Other information**

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. Afton makes no representation as to completeness or accuracy. In no event will Afton be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.

Date of issue/Date of revision : 3/15/2024 Date of previous issue : 1/9/2023 Version : 1.04 18/18