

PEAK GLOBAL DIESEL 15W40

PREMIUM MINERAL DIESEL OIL

DESCRIPTION & APPLICATION:

PEAK GLOBAL DIESEL 15W40 is a multi-grade diesel engine oil formulated to provide outstanding protection for diesel engines used in the toughest on and off-road applications.

PEAK GLOBAL DIESEL 15W40 is recommended for vehicles where performance specifications API CI-4/SL, Volvo VDS-3 and Global DHD-1. Is suitable for use in diesel, passenger cars, 4WD's, light & heavy-duty commercial engines in trucks, tractors, agricultural & earthmoving, forklifts and stationary engines. It is also suitable for Petrol, E10 and LPG.

BENEFITS:

- Excellent detergent and dispersant additives for a cleaner engine.
- Unique viscosity control additives prevent thickening of the oil.
- Very high shear stability resulting in superior load carrying ability.
- Suitable for a multitude of vehicles both Diesel and Petrol.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE	
Density 15° C g/cm³	0.874	
Viscosity 40°C cSt	121.1	
Viscosity 100°C cSt	15.7	
Viscosity Index	135.8	
Flash Point °C	>220	
Colour	L 2.5	

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKDM1540G001	1 Litre	6
PKDM1540G005	5 Litre	4
PKDM1540G007	7 Litre	3
PKDM1540G010	10 Litre	
PKDM1540G020	20 Litre	
PKDM1540G205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API CI-4 / SL
- ✓ ACEA E7 -16
- ✓ MB 228.3
- ✓ Volvo VDS-3
- ✓ Renault Truck RLD-2

- ✓ Global DHD-1
- ✓ Mack EO-N / M Plus
- ✓ MAN M3275
- ✓ Cummins CES 20076 / 20077 / 20078
- ✓ MTU Type 2
- ✓ Deutz DQC III-10
- ✓ Detroit Diesel DDC 93K215
- ✓ CAT ECF-1A / 2

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 January 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.





HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

