



PEAK 20W50

PREMIUM MINERAL ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 20W50 is a high-quality engine oil formulated with a combination of premium mineral base oils and high-performance additives making it suitable for engines requiring API SN, ACEA A3 / B4.

PEAK 20W50 is recommended for petrol engines (multivalve and turbo) with or without a catalytic converter.

BENEFITS:

- Engine seals stay soft and pliable to minimize and reduce oil leakages.
- Excellent detergent additives to improved engine cleanliness.
- Outstanding shear stability
- Outstanding thermal and oxidation stability

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.881
Viscosity 40°C cSt	150.9
Viscosity 100°C cSt	17.18
Viscosity Index	123.7
Flash Point °C	>220
Colour	L 2.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEM2050001	1 Litre	6
PKEM2050005	5 Litre	4
PKEM2050020	20 Litre	
PKEM2050205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN
- ✓ ACEA A3 / B4
- ✓ VW 501 01 / 505 00

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 12 May 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982