

PEAK 15W50

PREMIUM MINERAL ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 15W50 is a high-quality engine oil formulated with a combination of premium mineral base oils and high-performance additives making it suitable for engines requiring API SN.

PEAK 15W50 is recommended for petrol engines (multivalve and turbo) with or without a catalytic converter.

BENEFITS:

- Engine seals stay soft and pliable to minimize and reduce oil leakages.
- Excellent detergent additives to improved engine cleanliness.
- Outstanding shear stability
- Outstanding thermal and oxidation stability

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.870
Viscosity 40°C cSt	143.3
Viscosity 100°C cSt	18.4
Viscosity Index	140
Flash Point °C	>220
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEM1550005	5 Litre	4
PKEM1550006	6 Litre	4
PKEM1550020	20 Litre	
PKEM1550205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN / SM

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 9 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982