



STELLA™ UNIVERSAL COMPOUND

FOOD GRADE ANTI-SEIZE COMPOUND

DESCRIPTION & APPLICATION:

STELLA™ UNIVERSAL COMPOUND is a white, non-toxic grease-like compound with a high solids content designed for use as an assembly lubricant for lubricating bushes, sliding surfaces and small open plastic or metal gears.

STELLA™ UNIVERSAL COMPOUND is NSF H1 registered for use where incidental contact with food may occur in food, drink and pharmaceutical processing and packaging equipment

STELLA™ UNIVERSAL COMPOUND is also suitable as an anti-seize compound for threaded fasteners. The product is designed to prevent damage during start up and protect against premature wear during the running in period.

BENEFITS:

- Provides protection against scuffing during assembly
- Prevents seizure of threaded components enabling easy and quick dismantling
- Exceptional water resistance extending re-lubrication intervals
- Prevents seizure of threaded components enabling easy and quick dismantling
- Safe for use in HACCP Certified Food and Packaging Manufacturing Plants

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE
PKGXFASUC.500	500g

TYPICAL CHARACTERISTICS*:

TEST	RESULT
Appearance	Off White Smooth Paste
Base Oil	Synthetic
Solid lubricant	White lubricating solids
Operating Temperature – Service lubricant	-30°C to +150°C
Operating Temperature – Anti-seize	-30°C to +1100°C
4 Ball Weld Load kg	600

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ NSF H1 registered

Stella™ Universal compound should be applied sparingly, as a thin film, using a brush or lint-free cloth.

Surfaces must be cleaned well before application.

Due to its high solids content, it is not suitable for the lubrication of anti-friction bearings.

Stella™ is a trademark of Food Grade Oils Pty Ltd

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 26 August 2022

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982