



Additional information is listed in the Safety Data Sheet. Please scan the OR code for more information

Peak Lubricants Pty Ltd

224-230 South Gippsland Highway, Dandenong South, Victoria, 3175. Ph: (03) 9799 0977

www.peakoil.com.au

TECHNICAL LUBELINE 1300 722 256

FIND US ON [] [[] [in]











IN A TRANSPORT EMERGENCY DIAL 000, POLICE OR FIRE BRIGADE. **KEEP THIS PACKAGE TIGHTLY CLOSED.** UN NO. 3082 PACK GRP. Ш HAZCHEM. 3Z

PROPER SHIPPING NAME: **ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S**

ATTENTION: As the use of the product sold is beyond the control of the seller, all conditions and warranties of all kinds in relation to its use or application or otherwise are hereby excluded save for those non-exclusive warranties implied by The Trade Practices Act. 1974 (Cth.) or any other Act.

NEAT CUT D

NEAT CUTTING OIL

PEAK NEAT CUT D is a heavy, transparent, active, non-emulsifying, high additive EP cutting oil for use on ferrous metals, stainless and nickel/chrome hi-tensile steels. It is mainly confined to uses where a high viscosity oil is required. Pipe threading by hand or machine are typical applications.

PEAK NEAT CUT D can also be used on stainless and nickel / chrome steels. It is suitable for machining steels in various types of lathes – automatics, turrets and hand screw machines. Being high in extreme pressure antiwear additive, it is generally used on heavy duty operations such as gear cutting. broaching, turning, threading and tapping.

APPLICATION: Used neat.



205L BATCH NO: