



# PEAK 0W20

## FULL SYNTHETIC ENGINE OIL

### DESCRIPTION & APPLICATION:

PEAK 0W20 is a full synthetic engine oil that uses premium quality full synthetic base oil and high-quality additives making this engine oil suitable for vehicles requiring API SP and ILSAC GF-6.

PEAK 0W20 is designed for use in modern naturally aspirated, supercharged & turbocharged petrol, low emission engines and hybrids vehicles.

PEAK 0W20 is recommended for passenger cars, 4WD's and light commercial vehicles where Petrol, E10 and E85 fuels are used.

### BENEFITS:

- Improved power and engine responsiveness
- Very high shear stability with a fast-flowing formula
- Specifically formulated for use in GDI and TGD engines
- Excellent Deposit Control

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	0.850
Viscosity 40°C cSt	44.1
Viscosity 100°C cSt	8.3
Viscosity Index	167.5
Flash Point °C	>210
Colour	L 2.0

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEF020005	5 Litre	4
PKEF020010	10 Litre	
PKEF020020	20 Litre	
PKEF020205	205 Litre	

### SPECIFICATIONS & PERFORMANCE LEVEL:

✓ API SP

✓ ILSAC GF-6

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 January 2021

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

#### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982