



# PEAK PSHF - POWER STEER AND HYDRAULIC

## FULLY SYNTHETIC POWER STEER FLUID

### DESCRIPTION & APPLICATION:

**PEAK PSHF** is a fully synthetic long-life hydraulic fluid especially formulated for late model vehicles with electro-hydraulic systems, hydro-pneumatic suspensions and power steer units.

**PEAK PSHF** is also recommended for modern dual clutch transmission for the mechatronics and actuator systems.

**PEAK PSHF** is blended using premium quality additives, polymers and esters in Polyalphaolefin (PAO) base oils ensuring it maintains high performance under the most extreme conditions.

### BENEFITS:

- Superior thermal stability.
- Extends seal and hose and component life
- Minimises shudder and noise
- Outstanding anti-wear, anti-corrosion properties.

### SPECIFICATIONS & PERFORMANCE

#### LEVEL:

- |                                      |  |
|--------------------------------------|--|
| ✓ Audi/VW G 00200                    | ✓ Mercedes Benz 236.3 PN 000 989 88 03 |
| ✓ Audi/VW G 002012                   | ✓ Mercedes Benz 345.0 PN 001 989 24 03 |
| ✓ Chrysler MS-1872                   | ✓ Mitsubishi PS FLUID                  |
| ✓ Chrysler MS-5931 PN 04883077       | ✓ Mitsubishi Diamond SP III            |
| ✓ Chrysler MS-9602 ATF+4             | ✓ Nissan PSF-II                        |
| ✓ Chrysler MS-1872                   | ✓ Pentosin CHF 7.1                     |
| ✓ Ford M2C195-A                      | ✓ Pentosin CHF 11S                     |
| ✓ Ford M2C204A (Extended Temp Range) | ✓ Pentosin CHF 202                     |
| ✓ GM PN 88901975                     | ✓ Saab PN (45) 30 09 800               |
| ✓ GM PN 89021184                     | ✓ Saab PN 30 32 380                    |
| ✓ GM 9985010 PN 1052884              | ✓ Subaru PN K0209A0080                 |
| ✓ GM9985835 PN12345866               | ✓ Toyota PSF Type EH PN 00886-01       |
| ✓ Hyundai Kia PSF-3                  | ✓ Volvo PN 1161529                     |
| ✓ Hyundai Kia PSF-4                  |  |

\*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PDS 14/10/2023



#### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982



# PEAK PSHF - POWER STEER AND HYDRAULIC

## FULLY SYNTHETIC POWER STEER FLUID

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15°C g/cm <sup>3</sup>	0.842
Viscosity 40°C cSt	29.96
Viscosity 100°C cSt	6.57
Viscosity Index	183.2
Flash Point °C	>245
Pour point	>-55
Colour	L1.0

### PRODUCT PACK SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKTFSPSH001	1 Litre	6
PKTFSPSH1000	1000 Litre	

4/10/2023

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



#### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982