



PEAK SYNPRO DIESEL 10W40

SEMI SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK SYNPRO DIESEL 10W40 is a semi synthetic super-high performance engine oil formulated to meet the requirements of modern light and heavy-duty diesel engines including those fitted with/without a DPF (Diesel Particulate Filter).

PEAK SYNPRO DIESEL 10W40 is suitable for extended drain intervals where OEM operating conditions are satisfied and it can also be used in other light commercial vehicles where a semi synthetic diesel engine oil is required or recommended by the OEM.

BENEFITS:

- Excellent sludge and deposit control.
- Outstanding low temperature performance for reduced wear on start-up.
- Improved engine resilience and fuel economy
- Suitable for DPF models requiring stringent emission control requirements.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.860
Viscosity 40°C cSt	93.5
Viscosity 100°C cSt	13.7
Viscosity Index	149
Flash Point °C	>215
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKDS1040010	10 Litre	
PKDS1040020	20 Litre	
PKDS1040205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ACEA E7, E9
- ✓ API CJ-4 / SN
- ✓ CAT ECF-1A, ECF-2, ECF-3
- ✓ Cummins CES20076, 20077 & 20081
- ✓ Mercedes Benz 228.31
- ✓ Mack EO-N
- ✓ MAN 3271
- ✓ Renault RLD-3
- ✓ Volvo VDS-3, VDS-4

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 18 January 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256
EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982