

PEAK ST GREASE MULTIPURPOSE

LITHIUM COMPLEX GREASE - NLGI 1.5

DESCRIPTION & APPLICATION:

Peak ST Grease Multipurpose is an NLGI 1.5 grade extreme pressure grease with ISO VG 460 synthetic base fluid specially developed for outstanding bearing protection under heavy loads at low-to-moderate speeds and in applications where water resistance is a critical factor.

Peak ST Grease Multipurpose has wide application temperature ranges, with excellent protection at high temperatures as well as easy start-up at low temperatures

BENEFITS:

- Extended service life with longer intervals between relubrication and improved bearing life resulting in reduced downtime and maintenance costs.
- Excellent protection against wear, rust and corrosion.
- Reliable lubrication of bearings using centralized grease systems or grease dispensers with excellent pumpability.
- Outstanding structural stability in the presence of water and retains excellent grease performance in hostile aqueous environment

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
NLGI Grade	1.5
Soap/Thickener Type	Lithium Complex
Dropping point °C	255
Oil Viscosity 40°C cSt	460
4 Ball Weld Load, Kg	250
Operating Temperature Range °C	-30°C to 150°C
Colour	Red

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGXST020	20 KG	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 7 April 2021