



PEAK 75W90

SEMI SYNTHETIC GEAR OIL

DESCRIPTION & APPLICATION:

PEAK 75W90 is a high-performance gear lubricant enhanced by using the synthetic and high-quality mineral base fluids for use in manual gearbox and transaxle oil for modern-day passenger cars and light commercials vehicles.

PEAK 75W90 has a shear stable formulation ensuring full protection during extended drain intervals.

BENEFITS:

- Excellent shear stability
- Excellent low-temperature properties
- Good corrosion protection and rust prevention for longer component life
- Excellent wear protection

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.859
Viscosity 40°C cSt	117.9
Viscosity 100°C cSt	17.0
Viscosity Index	157
Flash Point °C	>210
Colour	L 1.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGS759002.5	2.5 Litre	6
PKGS7590020	20 Litre	
PKGS7590060	60 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-4/ GL-5
- ✓ ZF TE-ML 07A
- ✓ ZF TE-ML 08
- ✓ ZF TE-ML 24A

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 7 August 2023



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982